MC78XX/LM78XX/MC78XXA

3-Terminal 1A Positive Voltage Regulator

Features

- Output Current up to 1A
- Output Voltages of 5, 6, 8, 9, 10, 12, 15, 18, 24V
- Thermal Overload Protection
- Short Circuit Protection
- Output Transistor Safe Operating Area Protection

Description

The MC78XX/LM78XX/MC78XXA series of three terminal positive regulators are available in the TO-220/D-PAK package and with several fixed output voltages, making them useful in a wide range of applications. Each type employs internal current limiting, thermal shut down and safe operating area protection, making it essentially indestructible. If adequate heat sinking is provided, they can deliver over 1A output current. Although designed primarily as fixed voltage regulators, these devices can be used with external components to obtain adjustable voltages and currents.

TO-220



1


D-PAK



1

1. Input 2. GND 3. Output

Internal Block Digram



Rev. 1.0.1

©2001 Fairchild Semiconductor Corporation

Absolute Maximum Ratings

Parameter	Symbol	Value	Unit
Input Voltage (for V_O = 5V to 18V) (for V_O = 24V)	V_I V_I	35 40	V V
Thermal Resistance Junction-Cases (TO-220)	$R_{\theta JC}$	5	$^oC/W$
Thermal Resistance Junction-Air (TO-220)	$R_{\theta JA}$	65	$^oC/W$
Operating Temperature Range	T_{OPR}	0 ~ +125	^oC
Storage Temperature Range	T_{STG}	-65 ~ +150	^oC

Electrical Characteristics (MC7805/LM7805)

(Refer to test circuit ,0°C < T_J < 125°C, I_O = 500mA, V_I = 10V, C_I= 0.33µF, C_O= 0.1µF, unless otherwise specified)

Parameter	Symbol	Conditions		MC7805/LM7805			Unit
				Min.	Typ.	Max.	
Output Voltage	V_O	T_J =+25 ^oC		4.8	5.0	5.2	V
		5.0mA ≤ Io ≤ 1.0A, P_O ≤ 15W V_I = 7V to 20V		4.75	5.0	5.25	
Line Regulation (Note1)	Regline	T_J=+25 ^oC	V_O = 7V to 25V	-	4.0	100	mV
			V_I = 8V to 12V	-	1.6	50	
Load Regulation (Note1)	Regload	T_J=+25 ^oC	I_O = 5.0mA to1.5A	-	9	100	mV
			I_O =250mA to 750mA	-	4	50	
Quiescent Current	I_Q	T_J =+25 ^oC		-	5.0	8.0	mA
Quiescent Current Change	ΔI_Q	I_O = 5mA to 1.0A		-	0.03	0.5	mA
		V_I= 7V to 25V		-	0.3	1.3	
Output Voltage Drift	$\Delta V_O/\Delta T$	I_O= 5mA		-	-0.8	-	mV/ ^oC
Output Noise Voltage	V_N	f = 10Hz to 100KHz, T_A=+25 ^oC		-	42	-	µV/Vo
Ripple Rejection	RR	f = 120Hz V_O = 8V to 18V		62	73	-	dB
Dropout Voltage	V_{Drop}	I_O = 1A, T_J =+25 ^oC		-	2	-	V
Output Resistance	r_O	f = 1KHz		-	15	-	mΩ
Short Circuit Current	I_{SC}	V_I = 35V, T_A =+25 ^oC		-	230	-	mA
Peak Current	I_{PK}	T_J =+25 ^oC		-	2.2	-	A

Note:

1. Load and line regulation are specified at constant junction temperature. Changes in V_o due to heating effects must be taken into account separately. Pulse testing with low duty is used.

Electrical Characteristics (MC7806)

(Refer to test circuit ,0°C < T_J < 125°C, I_O = 500mA, V_I =11V, C_I= 0.33µF, C_O= 0.1µF, unless otherwise specified)

Parameter	Symbol	Conditions		MC7806			Unit
				Min.	Typ.	Max.	
Output Voltage	V_O	T_J =+25 °C		5.75	6.0	6.25	V
		5.0mA ≤ I_O ≤ 1.0A, P_O ≤ 15W V_I = 8.0V to 21V		5.7	6.0	6.3	
Line Regulation (Note1)	Regline	T_J =+25 °C	V_I = 8V to 25V	-	5	120	mV
			V_I = 9V to 13V	-	1.5	60	
Load Regulation (Note1)	Regload	T_J =+25 °C	I_O =5mA to 1.5A	-	9	120	mV
			I_O =250mA to750A	-	3	60	
Quiescent Current	I_Q	T_J =+25 °C		-	5.0	8.0	mA
Quiescent Current Change	ΔI_Q	I_O = 5mA to 1A		-	-	0.5	mA
		V_I = 8V to 25V		-	-	1.3	
Output Voltage Drift	$\Delta V_O/\Delta T$	I_O = 5mA		-	-0.8	-	mV/ °C
Output Noise Voltage	V_N	f = 10Hz to 100KHz, T_A =+25 °C		-	45	-	µV/Vo
Ripple Rejection	RR	f = 120Hz V_I = 9V to 19V		59	75	-	dB
Dropout Voltage	V_{Drop}	I_O = 1A, T_J =+25 °C		-	2	-	V
Output Resistance	r_O	f = 1KHz		-	19	-	mΩ
Short Circuit Current	I_{SC}	V_I= 35V, T_A=+25 °C		-	250	-	mA
Peak Current	I_{PK}	T_J =+25 °C		-	2.2	-	A

Note:

1. Load and line regulation are specified at constant junction temperature. Changes in V_O due to heating effects must be taken into account separately. Pulse testing with low duty is used.

Electrical Characteristics (MC7808)

(Refer to test circuit ,0°C < T_J < 125°C, I_O = 500mA, V_I =14V, C_I= 0.33µF, C_O= 0.1µF, unless otherwise specified)

Parameter	Symbol	Conditions		MC7808			Unit
				Min.	Typ.	Max.	
Output Voltage	V_O	T_J =+25 °C		7.7	8.0	8.3	V
		5.0mA ≤ I_O ≤ 1.0A, P_O ≤ 15W V_I = 10.5V to 23V		7.6	8.0	8.4	
Line Regulation (Note1)	Regline	T_J =+25 °C	V_I = 10.5V to 25V	-	5.0	160	mV
			V_I = 11.5V to 17V	-	2.0	80	
Load Regulation (Note1)	Regload	T_J =+25 °C	I_O = 5.0mA to 1.5A	-	10	160	mV
			I_O= 250mA to 750mA	-	5.0	80	
Quiescent Current	I_Q	T_J =+25 °C		-	5.0	8.0	mA
Quiescent Current Change	ΔI_Q	I_O = 5mA to 1.0A		-	0.05	0.5	mA
		V_I = 10.5A to 25V		-	0.5	1.0	
Output Voltage Drift	$\Delta V_O/\Delta T$	I_O = 5mA		-	-0.8	-	mV/ °C
Output Noise Voltage	V_N	f = 10Hz to 100KHz, T_A =+25 °C		-	52	-	µV/Vo
Ripple Rejection	RR	f = 120Hz, V_I= 11.5V to 21.5V		56	73	-	dB
Dropout Voltage	V_{Drop}	I_O = 1A, T_J=+25 °C		-	2	-	V
Output Resistance	r_O	f = 1KHz		-	17	-	mΩ
Short Circuit Current	I_{SC}	V_I= 35V, T_A =+25 °C		-	230	-	mA
Peak Current	I_{PK}	T_J =+25 °C		-	2.2	-	A

Note:

1. Load and line regulation are specified at constant junction temperature. Changes in V_O due to heating effects must be taken into account separately. Pulse testing with low duty is used.

Electrical Characteristics (MC7809)

(Refer to test circuit ,0°C < T_J < 125°C, I_O = 500mA, V_I =15V, C_I= 0.33µF, C_O= 0.1µF, unless otherwise specified)

Parameter	Symbol	Conditions		MC7809			Unit
				Min.	Typ.	Max.	
Output Voltage	V_O	T_J =+25°C		8.65	9	9.35	V
		5.0mA≤ I_O ≤1.0A, P_O ≤15W V_I= 11.5V to 24V		8.6	9	9.4	
Line Regulation (Note1)	Regline	T_J=+25°C	V_I = 11.5V to 25V	-	6	180	mV
			V_I = 12V to 17V	-	2	90	
Load Regulation (Note1)	Regload	T_J=+25°C	I_O = 5mA to 1.5A	-	12	180	mV
			I_O = 250mA to 750mA	-	4	90	
Quiescent Current	I_Q	T_J=+25°C		-	5.0	8.0	mA
Quiescent Current Change	ΔI_Q	I_O = 5mA to 1.0A		-	-	0.5	**mA**
		V_I = 11.5V to 26V		-	-	1.3	
Output Voltage Drift	$\Delta V_O/\Delta T$	I_O = 5mA		-	-1	-	mV/ °C
Output Noise Voltage	V_N	f = 10Hz to 100KHz, T_A =+25 °C		-	58	-	µV/Vo
Ripple Rejection	RR	f = 120Hz V_I = 13V to 23V		56	71	-	dB
Dropout Voltage	V_{Drop}	I_O = 1A, T_J=+25°C		-	2	-	V
Output Resistance	r_O	f = 1KHz		-	17	-	mΩ
Short Circuit Current	I_{SC}	V_I= 35V, T_A =+25°C		-	250	-	mA
Peak Current	I_{PK}	T_J= +25°C		-	2.2	-	A

Note:

1. Load and line regulation are specified at constant junction temperature. Changes in V_O due to heating effects must be taken into account separately. Pulse testing with low duty is used.

Electrical Characteristics (MC7810)

(Refer to test circuit ,0°C< T_J < 125°C, I_O = 500mA, V_I =16V, C_I= 0.33µF, C_O=0.1µF, unless otherwise specified)

Parameter	Symbol	Conditions		MC7810			Unit
				Min.	Typ.	Max.	
Output Voltage	V_O	T_J =+25 °C		9.6	10	10.4	V
		5.0mA ≤ I_O≤1.0A, P_O ≤15W V_I = 12.5V to 25V		9.5	10	10.5	
Line Regulation (Note1)	Regline	T_J =+25°C	V_I = 12.5V to 25V	-	10	200	mV
			V_I = 13V to 25V	-	3	100	
Load Regulation (Note1)	Regload	T_J =+25°C	I_O = 5mA to 1.5A	-	12	200	mV
			I_O = 250mA to 750mA	-	4	400	
Quiescent Current	I_Q	T_J =+25°C		-	5.1	8.0	mA
Quiescent Current Change	ΔI_Q	I_O = 5mA to 1.0A		-	-	0.5	mA
		V_I = 12.5V to 29V		-	-	1.0	
Output Voltage Drift	$\Delta V_O/\Delta T$	I_O = 5mA		-	-1	-	mV/°C
Output Noise Voltage	V_N	f = 10Hz to 100KHz, T_A =+25 °C		-	58	-	µV/Vo
Ripple Rejection	RR	f = 120Hz V_I = 13V to 23V		56	71	-	dB
Dropout Voltage	V_{Drop}	I_O = 1A, T_J=+25 °C		-	2	-	V
Output Resistance	r_O	f = 1KHz		-	17	-	mΩ
Short Circuit Current	I_{SC}	V_I = 35V, T_A=+25 °C		-	250	-	mA
Peak Current	I_{PK}	T_J =+25 °C		-	2.2	-	A

Note:

1. Load and line regulation are specified at constant junction temperature. Changes in V_O due to heating effects must be taken into account separately. Pulse testing with low duty is used.

Electrical Characteristics (MC7812)

(Refer to test circuit ,0°C < T_J < 125°C, I_O = 500mA, V_I =19V, C_I= 0.33μF, C_O=0.1μF, unless otherwise specified)

Parameter	Symbol	Conditions		MC7812			Unit
				Min.	Typ.	Max.	
Output Voltage	V_O	T_J =+25 °C		11.5	12	12.5	V
		5.0mA ≤ I_O≤1.0A, P_O≤15W V_I = 14.5V to 27V		11.4	12	12.6	
Line Regulation (Note1)	Regline	T_J =+25 °C	V_I = 14.5V to 30V	-	10	240	mV
			V_I = 16V to 22V	-	3.0	120	
Load Regulation (Note1)	Regload	T_J =+25 °C	I_O = 5mA to 1.5A	-	11	240	mV
			I_O = 250mA to 750mA	-	5.0	120	
Quiescent Current	I_Q	T_J =+25 °C		-	5.1	8.0	mA
Quiescent Current Change	ΔI_Q	I_O = 5mA to 1.0A		-	0.1	0.5	mA
		V_I = 14.5V to 30V		-	0.5	1.0	
Output Voltage Drift	$\Delta V_O/\Delta T$	I_O = 5mA		-	-1	-	mV/ °C
Output Noise Voltage	V_N	f = 10Hz to 100KHz, T_A =+25 °C		-	76	-	μV/Vo
Ripple Rejection	RR	f = 120Hz V_I = 15V to 25V		55	71	-	dB
Dropout Voltage	V_{Drop}	I_O = 1A, T_J=+25 °C		-	2	-	V
Output Resistance	r_O	f = 1KHz		-	18	-	mΩ
Short Circuit Current	I_{SC}	V_I = 35V, T_A=+25 °C		-	230	-	mA
Peak Current	I_{PK}	T_J = +25 °C		-	2.2	-	A

Note:

1. Load and line regulation are specified at constant junction temperature. Changes in V_O due to heating effects must be taken into account separately. Pulse testing with low duty is used.

Electrical Characteristics (MC7815)

(Refer to test circuit ,0°C < T_J < 125°C, I_O = 500mA, V_I =23V, C_I= 0.33µF, C_O=0.1µF, unless otherwise specified)

Parameter	Symbol	Conditions		MC7815			Unit
				Min.	Typ.	Max.	
Output Voltage	V_O	T_J =+25 °C		14.4	15	15.6	V
		5.0mA ≤ I_O ≤ 1.0A, P_O ≤ 15W V_I = 17.5V to 30V		14.25	15	15.75	
Line Regulation (Note1)	Regline	T_J =+25 °C	V_I = 17.5V to 30V	-	11	300	mV
			V_I = 20V to 26V	-	3	150	
Load Regulation (Note1)	Regload	T_J =+25 °C	I_O = 5mA to 1.5A	-	12	300	mV
			I_O = 250mA to 750mA	-	4	150	
Quiescent Current	I_Q	T_J =+25 °C		-	5.2	8.0	mA
Quiescent Current Change	ΔI_Q	I_O = 5mA to 1.0A		-	-	0.5	mA
		V_I = 17.5V to 30V		-	-	1.0	
Output Voltage Drift	$\Delta V_O/\Delta T$	I_O = 5mA		-	-1	-	mV/ °C
Output Noise Voltage	V_N	f = 10Hz to 100KHz, T_A =+25 °C		-	90	-	µV/Vo
Ripple Rejection	RR	f = 120Hz V_I = 18.5V to 28.5V		54	70	-	dB
Dropout Voltage	V_{Drop}	I_O = 1A, T_J=+25 °C		-	2	-	V
Output Resistance	r_O	f = 1KHz		-	19	-	mΩ
Short Circuit Current	I_{SC}	V_I = 35V, T_A=+25 °C		-	250	-	mA
Peak Current	I_{PK}	T_J =+25 °C		-	2.2	-	A

Note:

1. Load and line regulation are specified at constant junction temperature. Changes in V_O due to heating effects must be taken into account separately. Pulse testing with low duty is used.

Electrical Characteristics (MC7818)

(Refer to test circuit ,0°C < T_J < 125°C, I_O = 500mA, V_I =27V, C_I= 0.33μF, C_O=0.1μF, unless otherwise specified)

Parameter	Symbol	Conditions		MC7818			Unit
				Min.	Typ.	Max.	
Output Voltage	V_O	T_J =+25 °C		17.3	18	18.7	V
		5.0mA ≤ I_O ≤1.0A, P_O ≤15W V_I = 21V to 33V		17.1	18	18.9	
Line Regulation (Note1)	Regline	T_J =+25 °C	V_I = 21V to 33V	-	15	360	mV
			V_I = 24V to 30V	-	5	180	
Load Regulation (Note1)	Regload	T_J =+25 °C	I_O = 5mA to 1.5A	-	15	360	mV
			I_O = 250mA to 750mA	-	5.0	180	
Quiescent Current	I_Q	T_J =+25 °C		-	5.2	8.0	mA
Quiescent Current Change	ΔI_Q	I_O = 5mA to 1.0A		-	-	0.5	mA
		V_I = 21V to 33V		-	-	1	
Output Voltage Drift	$\Delta V_O/\Delta T$	I_O = 5mA		-	-1	-	mV/ °C
Output Noise Voltage	V_N	f = 10Hz to 100KHz, T_A =+25 °C		-	110	-	μV/Vo
Ripple Rejection	RR	f = 120Hz V_I = 22V to 32V		53	69	-	dB
Dropout Voltage	V_{Drop}	I_O = 1A, T_J=+25 °C		-	2	-	V
Output Resistance	r_O	f = 1KHz		-	22	-	mΩ
Short Circuit Current	I_{SC}	V_I = 35V, T_A=+25 °C		-	250	-	mA
Peak Current	I_{PK}	T_J =+25 °C		-	2.2	-	A

Note:

1. Load and line regulation are specified at constant junction temperature. Changes in V_O due to heating effects must be taken into account separately. Pulse testing with low duty is used.

Electrical Characteristics (MC7824)

(Refer to test circuit ,0°C < T_J < 125°C, I_O = 500mA, V_I =33V, C_I= 0.33μF, C_O=0.1μF, unless otherwise specified)

Parameter	Symbol	Conditions		MC7824			Unit
				Min.	Typ.	Max.	
Output Voltage	V_O	T_J =+25 °C		23	24	25	V
		5.0mA ≤ I_O ≤ 1.0A, P_O ≤ 15W V_I = 27V to 38V		22.8	24	25.25	
Line Regulation (Note1)	Regline	T_J =+25 °C	V_I = 27V to 38V	-	17	480	mV
			V_I = 30V to 36V	-	6	240	
Load Regulation (Note1)	Regload	T_J =+25 °C	I_O = 5mA to 1.5A	-	15	480	mV
			I_O = 250mA to 750mA	-	5.0	240	
Quiescent Current	I_Q	T_J =+25 °C		-	5.2	8.0	mA
Quiescent Current Change	ΔI_Q	I_O = 5mA to 1.0A		-	0.1	0.5	mA
		V_I = 27V to 38V		-	0.5	1	
Output Voltage Drift	$\Delta V_O/\Delta T$	I_O = 5mA		-	-1.5	-	mV/ °C
Output Noise Voltage	V_N	f = 10Hz to 100KHz, T_A =+25 °C		-	60	-	μV/Vo
Ripple Rejection	RR	f = 120Hz V_I = 28V to 38V		50	67	-	dB
Dropout Voltage	V_{Drop}	I_O = 1A, T_J=+25 °C		-	2	-	V
Output Resistance	r_O	f = 1KHz		-	28	-	mΩ
Short Circuit Current	I_{SC}	V_I = 35V, T_A=+25 °C		-	230	-	mA
Peak Current	I_{PK}	T_J =+25 °C		-	2.2	-	A

Note:

1. Load and line regulation are specified at constant junction temperature. Changes in V_O due to heating effects must be taken into account separately. Pulse testing with low duty is used.

Electrical Characteristics (MC7805A)

(Refer to the test circuits. 0°C < T_J < 125°C, I_O =1A, V_I = 10V, C_I=0.33μF, C_O=0.1μF, unless otherwise specified)

Parameter	Symbol	Conditions		Min.	Typ.	Max.	Unit
Output Voltage	V_O	T_J =+25 °C		4.9	5	5.1	V
		I_O = 5mA to 1A, $P_O \leq$ 15W V_I = 7.5V to 20V		4.8	5	5.2	
Line Regulation (Note1)	Regline	V_I = 7.5V to 25V I_O = 500mA		-	5	50	mV
		V_I = 8V to 12V		-	3	50	
		T_J =+25 °C	V_I= 7.3V to 20V	-	5	50	
			V_I= 8V to 12V	-	1.5	25	
Load Regulation (Note1)	Regload	T_J =+25 °C I_O = 5mA to 1.5A		-	9	100	mV
		I_O = 5mA to 1A		-	9	100	
		I_O = 250mA to 750mA		-	4	50	
Quiescent Current	I_Q	T_J =+25 °C		-	5.0	6	mA
Quiescent Current Change	ΔI_Q	I_O = 5mA to 1A		-	-	0.5	mA
		V_I = 8 V to 25V, I_O = 500mA		-	-	0.8	
		V_I = 7.5V to 20V, T_J =+25 °C		-	-	0.8	
Output Voltage Drift	$\Delta V/\Delta T$	Io = 5mA		-	-0.8	-	mV/ °C
Output Noise Voltage	V_N	f = 10Hz to 100KHz T_A =+25 °C		-	10	-	μV/Vo
Ripple Rejection	RR	f = 120Hz, I_O = 500mA V_I = 8V to 18V		-	68	-	dB
Dropout Voltage	V_{Drop}	I_O = 1A, T_J =+25 °C		-	2	-	V
Output Resistance	r_O	f = 1KHz		-	17	-	mΩ
Short Circuit Current	I_{SC}	V_I= 35V, T_A =+25 °C		-	250	-	mA
Peak Current	I_{PK}	T_J= +25 °C		-	2.2	-	A

Note:

1. Load and line regulation are specified at constant junction temperature. Change in V_O due to heating effects must be taken into account separately. Pulse testing with low duty is used.

Electrical Characteristics (MC7806A)

(Refer to the test circuits. 0°C < T_J < 125°C, I_O =1A, V_I =11V, C_I=0.33µF, C_O=0.1µF, unless otherwise specified)

Parameter	Symbol	Conditions		Min.	Typ.	Max.	Unit
Output Voltage	V_O	T_J =+25 °C		5.58	6	6.12	V
		I_O = 5mA to 1A, $P_O \leq$ 15W V_I = 8.6V to 21V		5.76	6	6.24	
Line Regulation (Note1)	Regline	V_I= 8.6V to 25V I_O = 500mA		-	5	60	mV
		V_I= 9V to 13V		-	3	60	
		T_J =+25 °C	V_I= 8.3V to 21V	-	5	60	
			V_I= 9V to 13V	-	1.5	30	
Load Regulation (Note1)	Regload	T_J =+25 °C I_O = 5mA to 1.5A		-	9	100	mV
		I_O = 5mA to 1A		-	4	100	
		I_O = 250mA to 750mA		-	5.0	50	
Quiescent Current	I_Q	T_J =+25 °C		-	4.3	6	mA
Quiescent Current Change	ΔI_Q	I_O = 5mA to 1A		-	-	0.5	mA
		V_I = 9V to 25V, I_O = 500mA		-	-	0.8	
		V_I= 8.5V to 21V, T_J =+25 °C		-	-	0.8	
Output Voltage Drift	$\Delta V/\Delta T$	I_O = 5mA		-	-0.8	-	mV/ °C
Output Noise Voltage	V_N	f = 10Hz to 100KHz T_A =+25 °C		-	10	-	µV/Vo
Ripple Rejection	RR	f = 120Hz, I_O = 500mA V_I = 9V to 19V		-	65	-	dB
Dropout Voltage	V_{Drop}	I_O = 1A, T_J =+25 °C		-	2	-	V
Output Resistance	r_O	f = 1KHz		-	17	-	mΩ
Short Circuit Current	I_{SC}	V_I= 35V, T_A =+25 °C		-	250	-	mA
Peak Current	I_{PK}	T_J=+25 °C		-	2.2	-	A

Note:

1. Load and line regulation are specified at constant junction temperature. Change in V_O due to heating effects must be taken into account separately. Pulse testing with low duty is used.

Electrical Characteristics (MC7808A)

(Refer to the test circuits. 0°C < T_J < 125°C, I_O =1A, V_I = 14V, C_I=0.33µF, C_O=0.1µF, unless otherwise specified)

Parameter	Symbol	Conditions		Min.	Typ.	Max.	Unit
Output Voltage	V_O	T_J =+25 °C		7.84	8	8.16	V
		I_O = 5mA to 1A, P_O ≤15W V_I = 10.6V to 23V		7.7	8	8.3	
Line Regulation (Note1)	Regline	V_I= 10.6V to 25V I_O = 500mA		-	6	80	mV
		V_I= 11V to 17V		-	3	80	
		T_J =+25 °C	V_I= 10.4V to 23V	-	6	80	
			V_I= 11V to 17V	-	2	40	
Load Regulation (Note1)	Regload	T_J =+25 °C I_O = 5mA to 1.5A		-	12	100	mV
		I_O = 5mA to 1A		-	12	100	
		I_O = 250mA to 750mA		-	5	50	
Quiescent Current	I_Q	T_J =+25 °C		-	5.0	6	mA
Quiescent Current Change	ΔI_Q	I_O = 5mA to 1A		-	-	0.5	mA
		V_I = 11V to 25V, I_O = 500mA		-	-	0.8	
		V_I= 10.6V to 23V, T_J =+25 °C		-	-	0.8	
Output Voltage Drift	$\Delta V/\Delta T$	I_O = 5mA		-	-0.8	-	mV/ °C
Output Noise Voltage	V_N	f = 10Hz to 100KHz T_A =+25 °C		-	10	-	µV/Vo
Ripple Rejection	RR	f = 120Hz, I_O = 500mA V_I = 11.5V to 21.5V		-	62	-	dB
Dropout Voltage	V_{Drop}	I_O = 1A, T_J =+25 °C		-	2	-	V
Output Resistance	r_O	f = 1KHz		-	18	-	mΩ
Short Circuit Current	I_{SC}	V_I= 35V, T_A =+25 °C		-	250	-	mA
Peak Current	I_{PK}	T_J=+25 °C		-	2.2	-	A

Note:

1. Load and line regulation are specified at constant junction temperature. Change in V_O due to heating effects must be taken into account separately. Pulse testing with low duty is used.

Electrical Characteristics (MC7809A)

(Refer to the test circuits. 0°C < T_J < 125°C, I_O =1A, V_I = 15V, C_I=0.33μF, C_O=0.1μF, unless otherwise specified)

Parameter	Symbol	Conditions		Min.	Typ.	Max.	Unit
Output Voltage	V_O	T_J =+25°C		8.82	9.0	9.18	V
		I_O = 5mA to 1A, P_O≤15W V_I = 11.2V to 24V		8.65	9.0	9.35	
Line Regulation (Note1)	Regline	V_I= 11.7V to 25V I_O = 500mA		-	6	90	mV
		V_I= 12.5V to 19V		-	4	45	
		T_J =+25°C	V_I= 11.5V to 24V	-	6	90	
			V_I= 12.5V to 19V	-	2	45	
Load Regulation (Note1)	Regload	T_J =+25°C I_O = 5mA to 1.0A		-	12	100	mV
		I_O = 5mA to 1.0A		-	12	100	
		I_O = 250mA to 750mA		-	5	50	
Quiescent Current	I_Q	T_J =+25 °C		-	5.0	6.0	mA
Quiescent Current Change	ΔI_Q	V_I = 11.7V to 25V, T_J=+25 °C		-	-	0.8	mA
		V_I = 12V to 25V, I_O = 500mA		-	-	0.8	
		I_O = 5mA to 1.0A		-	-	0.5	
Output Voltage Drift	$\Delta V/\Delta T$	I_O = 5mA		-	-1.0	-	mV/ °C
Output Noise Voltage	V_N	f = 10Hz to 100KHz T_A =+25 °C		-	10	-	μV/Vo
Ripple Rejection	RR	f = 120Hz, I_O = 500mA V_I = 12V to 22V		-	62	-	dB
Dropout Voltage	V_{Drop}	I_O = 1A, T_J =+25 °C		-	2.0	-	V
Output Resistance	r_O	f = 1KHz		-	17	-	mΩ
Short Circuit Current	I_{SC}	V_I= 35V, T_A =+25 °C		-	250	-	mA
Peak Current	I_{PK}	T_J=+25°C		-	2.2	-	A

Note:

1. Load and line regulation are specified at constant, junction temperature. Change in V_O due to heating effects must be taken into account separately. Pulse testing with low duty is used.

Electrical Characteristics (MC7810A)

(Refer to the test circuits. 0°C < T_J < 125°C, I_O =1A, V_I = 16V, C_I=0.33μF, C_O=0.1μF, unless otherwise specified)

Parameter	Symbol	Conditions		Min.	Typ.	Max.	Unit
Output Voltage	V_O	T_J =+25°C		9.8	10	10.2	V
		I_O = 5mA to 1A, $P_O \leq$ 15W V_I =12.8V to 25V		9.6	10	10.4	
Line Regulation (Note1)	Regline	V_I= 12.8V to 26V I_O = 500mA		-	8	100	mV
		V_I= 13V to 20V		-	4	50	
		T_J =+25 °C	V_I= 12.5V to 25V	-	8	100	
			V_I= 13V to 20V	-	3	50	
Load Regulation (Note1)	Regload	T_J =+25 °C I_O = 5mA to 1.5A		-	12	100	mV
		I_O = 5mA to 1.0A		-	12	100	
		I_O = 250mA to 750mA		-	5	50	
Quiescent Current	I_Q	T_J =+25 °C		-	5.0	6.0	mA
Quiescent Current Change	ΔI_Q	V_I = 13V to 26V, T_J=+25 °C		-	-	0.5	mA
		V_I = 12.8V to 25V, I_O = 500mA		-	-	0.8	
		I_O = 5mA to 1.0A		-	-	0.5	
Output Voltage Drift	$\Delta V/\Delta T$	I_O = 5mA		-	-1.0	-	mV/°C
Output Noise Voltage	V_N	f = 10Hz to 100KHz T_A =+25 °C		-	10	-	μV/Vo
Ripple Rejection	RR	f = 120Hz, I_O = 500mA V_I = 14V to 24V		-	62	-	dB
Dropout Voltage	V_{Drop}	I_O = 1A, T_J =+25°C		-	2.0	-	V
Output Resistance	r_O	f = 1KHz		-	17	-	mΩ
Short Circuit Current	I_{SC}	V_I= 35V, T_A =+25 °C		-	250	-	mA
Peak Current	I_{PK}	T_J=+25 °C		-	2.2	-	A

Note:

1. Load and line regulation are specified at constant junction temperature. Change in V_O due to heating effects must be taken into account separately. Pulse testing with low duty is used.

Electrical Characteristics (MC7812A)

(Refer to the test circuits. 0°C < T_J < 125°C, I_O =1A, V_I = 19V, C_I=0.33μF, C_O=0.1μF, unless otherwise specified)

Parameter	Symbol	Conditions		Min.	Typ.	Max.	Unit
Output Voltage	V_O	T_J =+25 °C		11.75	12	12.25	V
		I_O = 5mA to 1A, P_O ≤15W V_I = 14.8V to 27V		11.5	12	12.5	
Line Regulation (Note1)	Regline	V_I= 14.8V to 30V I_O = 500mA		-	10	120	mV
		V_I= 16V to 22V		-	4	120	
		T_J =+25 °C	V_I= 14.5V to 27V	-	10	120	
			V_I= 16V to 22V	-	3	60	
Load Regulation (Note1)	Regload	T_J =+25 °C I_O = 5mA to 1.5A		-	12	100	mV
		I_O = 5mA to 1.0A		-	12	100	
		I_O = 250mA to 750mA		-	5	50	
Quiescent Current	I_Q	T_J =+25°C		-	5.1	6.0	mA
Quiescent Current Change	ΔI_Q	V_I = 15V to 30V, T_J=+25 °C		-		0.8	mA
		V_I = 14V to 27V, I_O = 500mA		-		0.8	
		I_O = 5mA to 1.0A		-		0.5	
Output Voltage Drift	$\Delta V/\Delta T$	I_O = 5mA		-	-1.0	-	mV/°C
Output Noise Voltage	V_N	f = 10Hz to 100KHz T_A =+25°C		-	10	-	μV/Vo
Ripple Rejection	RR	f = 120Hz, I_O = 500mA V_I = 14V to 24V		-	60	-	dB
Dropout Voltage	V_{Drop}	I_O = 1A, T_J =+25°C		-	2.0	-	V
Output Resistance	r_O	f = 1KHz		-	18	-	mΩ
Short Circuit Current	I_{SC}	V_I= 35V, T_A =+25 °C		-	250	-	mA
Peak Current	I_{PK}	T_J=+25 °C		-	2.2	-	A

Note:

1. Load and line regulation are specified at constant junction temperature. Change in V_O due to heating effects must be taken into account separately. Pulse testing with low duty is used.

Electrical Characteristics (MC7815A)

(Refer to the test circuits. 0°C < T_J < 125°C, I_O =1A, V_I =23V, C_I=0.33μF, C_O=0.1μF, unless otherwise specified)

Parameter	Symbol	Conditions		Min.	Typ.	Max.	Unit
Output Voltage	V_O	T_J =+25 °C		14.7	15	15.3	V
		I_O = 5mA to 1A, P_O ≤15W V_I = 17.7V to 30V		14.4	15	15.6	
Line Regulation (Note1)	Regline	V_I= 17.9V to 30V I_O = 500mA		-	10	150	mV
		V_I= 20V to 26V		-	5	150	
		T_J =+25°C	V_I= 17.5V to 30V	-	11	150	
			V_I= 20V to 26V	-	3	75	
Load Regulation (Note1)	Regload	T_J =+25 °C I_O = 5mA to 1.5A		-	12	100	mV
		I_O = 5mA to 1.0A		-	12	100	
		I_O = 250mA to 750mA		-	5	50	
Quiescent Current	I_Q	T_J =+25 °C		-	5.2	6.0	mA
Quiescent Current Change	ΔI_Q	V_I = 17.5V to 30V, T_J =+25 °C		-	-	0.8	mA
		V_I = 17.5V to 30V, I_O = 500mA		-	-	0.8	
		I_O = 5mA to 1.0A		-	-	0.5	
Output Voltage Drift	$\Delta V/\Delta T$	I_O = 5mA		-	-1.0	-	mV/°C
Output Noise Voltage	V_N	f = 10Hz to 100KHz T_A =+25 °C		-	10	-	μV/Vo
Ripple Rejection	RR	f = 120Hz, I_O = 500mA V_I = 18.5V to 28.5V		-	58	-	dB
Dropout Voltage	V_{Drop}	I_O = 1A, T_J =+25 °C		-	2.0	-	V
Output Resistance	r_O	f = 1KHz		-	19	-	mΩ
Short Circuit Current	I_{SC}	V_I= 35V, T_A =+25 °C		-	250	-	mA
Peak Current	I_{PK}	T_J=+25°C		-	2.2	-	A

Note:

1. Load and line regulation are specified at constant junction temperature. Change in V_O due to heating effects must be taken into account separately. Pulse testing with low duty is used.

Electrical Characteristics (MC7818A)

(Refer to the test circuits. 0°C < T_J < 125°C, I_O =1A, V_I = 27V, C_I=0.33μF, C_O=0.1μF, unless otherwise specified)

Parameter	Symbol	Conditions		Min.	Typ.	Max.	Unit
Output Voltage	V_O	T_J =+25 °C		17.64	18	18.36	V
		I_O = 5mA to 1A, P_O ≤15W V_I = 21V to 33V		17.3	18	18.7	
Line Regulation (Note1)	Regline	V_I= 21V to 33V I_O = 500mA		-	15	180	mV
		V_I= 21V to 33V		-	5	180	
		T_J =+25 °C	V_I= 20.6V to 33V	-	15	180	
			V_I= 24V to 30V	-	5	90	
Load Regulation (Note1)	Regload	T_J =+25°C I_O = 5mA to 1.5A		-	15	100	mV
		I_O = 5mA to 1.0A		-	15	100	
		I_O = 250mA to 750mA		-	7	50	
Quiescent Current	I_Q	T_J =+25 °C		-	5.2	6.0	mA
Quiescent Current Change	ΔI_Q	V_I = 21V to 33V, T_J=+25 °C		-	-	0.8	mA
		V_I = 21V to 33V, I_O = 500mA		-	-	0.8	
		I_O = 5mA to 1.0A		-	-	0.5	
Output Voltage Drift	$\Delta V/\Delta T$	I_O = 5mA		-	-1.0	-	mV/ °C
Output Noise Voltage	V_N	f = 10Hz to 100KHz T_A =+25°C		-	10	-	μV/Vo
Ripple Rejection	RR	f = 120Hz, I_O = 500mA V_I = 22V to 32V		-	57	-	dB
Dropout Voltage	V_{Drop}	I_O = 1A, T_J =+25°C		-	2.0	-	V
Output Resistance	r_O	f = 1KHz		-	19	-	mΩ
Short Circuit Current	I_{SC}	V_I= 35V, T_A =+25°C		-	250	-	mA
Peak Current	I_{PK}	T_J=+25 °C		-	2.2	-	A

Note:

1. Load and line regulation are specified at constant junction temperature. Change in V_O due to heating effects must be taken into account separately. Pulse testing with low duty is used.

Electrical Characteristics (MC7824A)

(Refer to the test circuits. 0°C < T_J < 125°C, I_O =1A, V_I = 33V, C_I=0.33μF, C_O=0.1μF, unless otherwise specified)

Parameter	Symbol	Conditions		Min.	Typ.	Max.	Unit
Output Voltage	V_O	T_J =+25 °C		23.5	24	24.5	V
		I_O = 5mA to 1A, P_O ≤15W V_I = 27.3V to 38V		23	24	25	
Line Regulation (Note1)	Regline	V_I= 27V to 38V I_O = 500mA		-	18	240	mV
		V_I= 21V to 33V		-	6	240	
		T_J =+25 °C	V_I= 26.7V to 38V	-	18	240	
			V_I= 30V to 36V	-	6	120	
Load Regulation (Note1)	Regload	T_J =+25 °C I_O = 5mA to 1.5A		-	15	100	mV
		I_O = 5mA to 1.0A		-	15	100	
		I_O = 250mA to 750mA		-	7	50	
Quiescent Current	I_Q	T_J =+25 °C		-	5.2	6.0	mA
Quiescent Current Change	ΔI_Q	V_I = 27.3V to 38V, T_J =+25 °C		-	-	0.8	mA
		V_I = 27.3V to 38V, I_O = 500mA		-	-	0.8	
		I_O = 5mA to 1.0A		-	-	0.5	
Output Voltage Drift	$\Delta V/\Delta T$	I_O = 5mA		-	-1.5	-	mV/ °C
Output Noise Voltage	V_N	f = 10Hz to 100KHz T_A = 25 °C		-	10	-	μV/Vo
Ripple Rejection	RR	f = 120Hz, I_O = 500mA V_I = 28V to 38V		-	54	-	dB
Dropout Voltage	V_{Drop}	I_O = 1A, T_J =+25 °C		-	2.0	-	V
Output Resistance	r_O	f = 1KHz		-	20	-	mΩ
Short Circuit Current	I_{SC}	V_I= 35V, T_A =+25 °C		-	250	-	mA
Peak Current	I_{PK}	T_J=+25 °C		-	2.2	-	A

Note:

1. Load and line regulation are specified at constant junction temperature. Change in VO due to heating effects must be taken into account separately. Pulse testing with low duty is used.

Typical Perfomance Characteristics




Figure 1. Quiescent Current




Figure 2. Peak Output Current




Figure 3. Output Voltage




Figure 4. Quiescent Current

Typical Applications




Figure 5. DC Parameters




Figure 6. Load Regulation




Figure 7. Ripple Rejection




Figure 8. Fixed Output Regulator





Figure 9. Constant Current Regulator

Notes:

(1) To specify an output voltage. substitute voltage value for "XX." A common ground is required between the input and the Output voltage. The input voltage must remain typically 2.0V above the output voltage even during the low point on the input ripple voltage.

(2) C_I is required if regulator is located an appreciable distance from power Supply filter.


(3) C_O improves stability and transient response.



$$I_{RI} \geq 5IQ$$

$$V_O = V_{XX}(1+R_2/R_1)+I_QR_2$$

Figure 10. Circuit for Increasing Output Voltage



$$I_{RI} \geq 5\ I_Q$$

$$V_O = V_{XX}(1+R_2/R_1)+I_QR_2$$

Figure 11. Adjustable Output Regulator (7 to 30V)




Figure 12. High Current Voltage Regulator




Figure 13. High Output Current with Short Circuit Protection




Figure 14. Tracking Voltage Regulator




Figure 15. Split Power Supply (±15V-1A)




Figure 16. Negative Output Voltage Circuit





Figure 17. Switching Regulator

Mechanical Dimensions

Package


TO-220



Mechancal Dimensions (Continued)

Package

D-PAK



Ordering Information

Product Number	Output Voltage Tolerance	Package	Operating Temperature
LM7805CT	±4%	TO-220	0 ~ + 125°C

Product Number	Output Voltage Tolerance	Package	Operating Temperature
MC7805CT	±4%	TO-220	0 ~ + 125°C
MC7806CT			
MC7808CT			
MC7809CT			
MC7810CT			
MC7812CT			
MC7815CT			
MC7818CT			
MC7824CT			
MC7805CDT		D-PAK	
MC7806CDT			
MC7808CDT			
MC7809CDT			
MC7810CDT			
MC7812CDT			
MC7805ACT	±2%	TO-220	
MC7806ACT			
MC7808ACT			
MC7809ACT			
MC7810ACT			
MC7812ACT			
MC7815ACT			
MC7818ACT			
MC7824ACT			

DISCLAIMER

FAIRCHILD SEMICONDUCTOR RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION OR DESIGN. FAIRCHILD DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS.

LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF THE PRESIDENT OF FAIRCHILD SEMICONDUCTOR CORPORATION. As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, and (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury of the user.
2. A critical component in any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

© 2001 Fairchild Semiconductor Corporation

ENTEGRECİ

Bu belge www.entegreci.com üzerinden sunulmaktadır.

Elektronik komponent tedarikinde Entegreci

Entegreci, Eskişehir merkezli, Türkiye geneline satış yapan bir elektronik komponent mağazasıdır. Entegreler (IC), mikrodenetleyiciler, transistörler, diyotlar, pasif elemanlar, konnektörler, modüller ve geliştirme kartları tek adetten seri üretim adetlerine kadar satılır. Ürün sayfalarında güncel stok durumunu, fiyatı ve datasheet bağlantısını bulabilirsiniz.

Parça koduyla arama

Üretici parça numarasını yazın; stok ve fiyatı hemen görün.

www.entegreci.com

Ürün kategorileri

Entegreden kapasitöre tüm elektronik komponent kategorileri.

Kategorilere göz atın

Üreticiler

Aradığınız üreticinin ürünlerini tek sayfada inceleyin.

Üreticileri görün

Toplu alım ve teklif

Listede olmayan ya da yüksek adetli parçalar için teklif isteyin.

Teklif isteyin

www.entegreci.com | **destek@entegreci.com** | **0850 305 90 34**

Entegreci is an online electronic components store based in Türkiye. Search by manufacturer part number to see stock, prices and datasheets for integrated circuits, microcontrollers, transistors, passive components and connectors, or request a quote for parts that are not listed.

Bu sayfa Entegreci tarafından eklenmiştir. Belgenin önceki sayfaları asıl yayıncısına aittir ve içeriği değiştirilmemiştir; en güncel sürüm için belgenin yayıncısına başvurun.