FAIRCHILD SEMICONDUCTOR™

October 1987
Revised January 2004

CD4511BC
BCD-to-7 Segment Latch/Decoder/Driver

General Description

The CD4511BC BCD-to-seven segment latch/decoder/driver is constructed with complementary MOS (CMOS) enhancement mode devices and NPN bipolar output drivers in a single monolithic structure. The circuit provides the functions of a 4-bit storage latch, an 8421 BCD-to-seven segment decoder, and an output drive capability. Lamp test (LT), blanking (BI), and latch enable (LE) inputs are used to test the display, to turn-off or pulse modulate the brightness of the display, and to store a BCD code, respectively. It can be used with seven-segment light emitting diodes (LED), incandescent, fluorescent, gas discharge, or liquid crystal readouts either directly or indirectly.

Applications include instrument (e.g., counter, DVM, etc.) display driver, computer/calculator display driver, cockpit display driver, and various clock, watch, and timer uses.


Features

- Low logic circuit power dissipation
- High current sourcing outputs (up to 25 mA)
- Latch storage of code
- Blanking input
- Lamp test provision
- Readout blanking on all illegal input combinations
- Lamp intensity modulation capability
- Time share (multiplexing) facility
- Equivalent to Motorola MC14511

Ordering Code:


Order Number	Package Number	Package Description
CD4511BCWM	M16B	16-Lead Small Outline Intergrated Circuit (SOIC), JEDEC MS-013, 0.300" Wide
CD4511BCN	N16E	16-Lead Plastic Dual-In-Line Package (PDIP), JEDEC MS-001, 0.300" Wide

Connection Diagrams



Top View

Segment Identification



© 2004 Fairchild Semiconductor Corporation


Truth Table

Inputs							Outputs							
LE	$\overline{BI}$	$\overline{LT}$	D	C	B	A	a	b	c	d	e	f	g	Display
X	X	0	X	X	X	X	1	1	1	1	1	1	1	B
X	0	1	X	X	X	X	0	0	0	0	0	0	0	
0	1	1	0	0	0	0	1	1	1	1	1	1	0	0
0	1	1	0	0	0	1	0	1	1	0	0	0	0	1
0	1	1	0	0	1	0	1	1	0	1	1	0	1	2
0	1	1	0	0	1	1	1	1	1	1	0	0	1	3
0	1	1	0	1	0	0	0	1	1	0	0	1	1	4
0	1	1	0	1	0	1	1	0	1	1	0	1	1	5
0	1	1	0	1	1	0	0	0	1	1	1	1	1	6
0	1	1	0	1	1	1	1	1	1	0	0	0	0	7
0	1	1	1	0	0	0	1	1	1	1	1	1	1	8
0	1	1	1	0	0	1	1	1	1	0	0	1	1	9
0	1	1	1	0	1	0	0	0	0	0	0	0	0	
0	1	1	1	0	1	1	0	0	0	0	0	0	0	
0	1	1	1	1	0	0	0	0	0	0	0	0	0	
0	1	1	1	1	0	1	0	0	0	0	0	0	0	
0	1	1	1	1	1	0	0	0	0	0	0	0	0	
0	1	1	1	1	1	1	0	0	0	0	0	0	0	
1	1	1	X	X	X	X				*				*

X = Don't Care

*Depends upon the BCD code applied during the 0 to 1 transition of LE.

Display



Absolute Maximum Ratings(Note 1)

DC Supply Voltage (V_{DD})	−0.5V to +18V
Input Voltage (V_{IN})	−0.5V to V_{DD} +0.5V
Storage Temperature Range (T_S)	−65°C to +150°C
Power Dissipation (P_D)	
Dual-In-Line	700 mW
Small Outline	500 mW
Lead Temperature (T_L)	
(Soldering, 10 seconds)	260°C

Recommended Operating Conditions

DC Supply Voltage (V_{DD})	3V to 15V
Input Voltage (V_{IN})	0V to V_{DD}
Operating Temperature Range (T_A)	−55°C to +125°C

Note 1: Devices should not be connected with power on.

DC Electrical Characteristics

Symbol	Parameter	Conditions	−55°C		+25°C			+125°C		Units
			Min	Max	Min	Typ	Max	Min	Max	
I_{DD}	Quiescent	V_{DD} = 5V		5			5		150	
	Supply Current	V_{DD} = 10V		10			10		300	µA
		V_{DD} = 15V		20			20		600	
V_{OL}	Output Voltage	V_{DD} = 5V		0.01		0	0.01		0.05	
	Logical “0”	V_{DD} = 10V		0.01		0	0.01		0.05	V
	Level	V_{DD} = 15V		0.01		0	0.01		0.05	
V_{OH}	Output Voltage	V_{DD} = 5V	4.1		4.1	4.57		4.1		
	Logical “1”	V_{DD} = 10V	9.1		9.1	9.58		9.1		V
	Level	V_{DD} = 15V	14.1		14.1	14.59		14.1		
V_{IL}	LOW Level	V_{DD} = 5V, V_{OUT} = 3.8V or 0.5V		1.5		2	1.5		1.5	
	Input Voltage	V_{DD} = 10V, V_{OUT} = 8.8V or 1.0V		3.0		4	3.0		3.0	V
		V_{DD} = 15V, V_{OUT} = 13.8V or 1.5V		4.0		6	4.0		4.0	
V_{IH}	HIGH Level	V_{DD} = 5V, V_{OUT} = 0.5V or 3.8V	3.5		3.5	3		3.5		
	Input Voltage	V_{DD} = 10V, V_{OUT} = 1.0V or 8.8V	7.0		7.0	6		7.0		V
		V_{DD} = 15V, V_{OUT} = 1.5V or 13.8V	11.0		11.0	9		11.0		
V_{OH}	Output	V_{DD} = 5V, I_{OH} = 0 mA	4.1		4.1	4.57		4.1		
	(Source) Drive	V_{DD} = 5V, I_{OH} = 5 mA				4.24				
	Voltage	V_{DD} = 5V, I_{OH} = 10 mA	3.9		3.9	4.12		3.5		V
		V_{DD} = 5V, I_{OH} = 15 mA				3.94				
		V_{DD} = 5V, I_{OH} = 20 mA	3.4		3.4	3.75		3.0		
		V_{DD} = 5V, I_{OH} = 25 mA				3.54				
		V_{DD} = 10V, I_{OH} = 0 mA	9.1		9.1	9.58		9.1		
		V_{DD} = 10V, I_{OH} = 5 mA				9.26				
		V_{DD} = 10V, I_{OH} = 10 mA	9.0		9.0	9.17		8.6		V
		V_{DD} = 10V, I_{OH} = 15 mA				9.04				
		V_{DD} = 10V, I_{OH} = 20 mA	8.6		8.6	8.9		8.2		
		V_{DD} = 10V, I_{OH} = 25 mA				8.75				
		V_{DD} = 15V, I_{OH} = 0 mA	14.1		14.1	9.58		14.1		
		V_{DD} = 15V, I_{OH} = 5 mA				14.27				
		V_{DD} = 15V, I_{OH} = 10 mA	14.0		14.0	14.17		13.6		V
		V_{DD} = 15V, I_{OH} = 15 mA				14.07				
		V_{DD} = 15V, I_{OH} = 20 mA	13.6		13.6	13.95		13.2		
		V_{DD} = 15V, I_{OH} = 25 mA				13.80				
I_{OL}	LOW Level	V_{DD} = 5V, V_{OL} = 0.4V	0.64		0.51	0.88		0.36		
	Output Current	V_{DD} = 10V, V_{OL} = 0.5V	1.6		1.3	2.25		0.9		mA
		V_{DD} = 15V, V_{OL} = 1.5V	4.2		3.4	8.8		2.4		
I_{IN}	Input Current	V_{DD} = 15V, V_{IN} = 0V		−0.1		-10^{-5}	−0.1		−1.0	µA
		V_{DD} = 15V, V_{IN} = 15V		0.1		10^{-5}	0.1		1.0	

AC Electrical Characteristics (Note 2)

$T_A = 25°C$ and $C_L = 50$ pF, typical temperature coefficient for all values of $V_{DD} = 0.3\%/°C$

Symbol	Parameter	Conditions	Min	Typ	Max	Units
C_{IN}	Input Capacitance	$V_{IN} = 0$		5.0	7.5	pF
t_r	Output Rise Time	$V_{DD} = 5V$		40	80	
	(Figure 1**a**)	$V_{DD} = 10V$		30	60	ns
		$V_{DD} = 15V$		25	50	
t_f	Output Fall Time	$V_{DD} = 5V$		125	250	
	(Figure 1**a**)	$V_{DD} = 10V$		75	150	ns
		$V_{DD} = 15V$		65	130	
t_{PLH}	Turn-Off Delay Time	$V_{DD} = 5V$		640	1280	
	(Data) (Figure 1**a**)	$V_{DD} = 10V$		250	500	ns
		$V_{DD} = 15V$		175	350	
t_{PHL}	Turn-On Delay Time	$V_{DD} = 5V$		720	1440	
	(Data) (Figure 1**a**)	$V_{DD} = 10V$		290	580	ns
		$V_{DD} = 15V$		195	400	
t_{PLH}	Turn-Off Delay Time	$V_{DD} = 5V$		320	640	
	(Blank) (Figure 1**a**)	$V_{DD} = 10V$		130	260	ns
		$V_{DD} = 15V$		100	200	
t_{PHL}	Turn-On Delay Time	$V_{DD} = 5V$		485	970	
	(Blank) (Figure 1**a**)	$V_{DD} = 10V$		200	400	ns
		$V_{DD} = 15V$		160	320	
t_{PLH}	Turn-Off Delay Time	$V_{DD} = 5V$		313	625	
	(Lamp Test) (Figure 1**a**)	$V_{DD} = 10V$		125	250	ns
		$V_{DD} = 15V$		90	180	
t_{PHL}	Turn-On Delay Time	$V_{DD} = 5V$		313	625	
	(Lamp Test) (Figure 1 **a**)	$V_{DD} = 10V$		125	250	ns
		$V_{DD} = 15V$		90	180	
t_{SETUP}	Setup Time	$V_{DD} = 5V$	180	90		
	(Figure 1**b**)	$V_{DD} = 10V$	76	38		ns
		$V_{DD} = 15V$	40	20		
t_{HOLD}	Hold Time	$V_{DD} = 5V$	0	–90		
	(Figure 1**b**)	$V_{DD} = 10V$	0	–38		ns
		$V_{DD} = 15V$	0	–20		
PW_{LE}	Minimum Latch Enable	$V_{DD} = 5V$	520	260		
	Pulse Width (Figure 1 **c**)	$V_{DD} = 10V$	220	110		ns
		$V_{DD} = 15V$	130	65		

Note 2: AC Parameters are guaranteed by DC correlated testing.

Switching Time Waveforms






FIGURE 1.

Typical Applications


Light Emitting Diode (LED) Readout



Gas Discharge Readout




Liquid Crystal (LC) Readout




Direct DC drive of LC's not recommended for life of LC readouts.

Incandescent Readout




Fluorescent Readout




**A filament pre-warm resistor is recommended to reduce filament thermal shock and increase the effective cold resistance of the filament.

Physical Dimensions inches (millimeters) unless otherwise noted



16-Lead Small Outline Intergrated Circuit (SOIC), JEDEC MS-013, 0.300" Wide
Package Number M16B

Physical Dimensions inches (millimeters) unless otherwise noted (Continued)



16-Lead Plastic Dual-In-Line Package (PDIP), JEDEC MS-001, 0.300" Wide
Package Number N16E

Fairchild does not assume any responsibility for use of any circuitry described, no circuit patent licenses are implied and Fairchild reserves the right at any time without notice to change said circuitry and specifications.

LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF THE PRESIDENT OF FAIRCHILD SEMICONDUCTOR CORPORATION. As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, and (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury to the user.
2. A critical component in any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

www.fairchildsemi.com

ENTEGRECİ

Bu belge www.entegreci.com üzerinden sunulmaktadır.

Elektronik komponent tedarikinde Entegreci

Entegreci, Eskişehir merkezli, Türkiye geneline satış yapan bir elektronik komponent mağazasıdır. Entegreler (IC), mikrodenetleyiciler, transistörler, diyotlar, pasif elemanlar, konnektörler, modüller ve geliştirme kartları tek adetten seri üretim adetlerine kadar satılır. Ürün sayfalarında güncel stok durumunu, fiyatı ve datasheet bağlantısını bulabilirsiniz.

Parça koduyla arama

Üretici parça numarasını yazın; stok ve fiyatı hemen görün.

www.entegreci.com

Ürün kategorileri

Entegreden kapasitöre tüm elektronik komponent kategorileri.

Kategorilere göz atın

Üreticiler

Aradığınız üreticinin ürünlerini tek sayfada inceleyin.

Üreticileri görün

Toplu alım ve teklif

Listede olmayan ya da yüksek adetli parçalar için teklif isteyin.

Teklif isteyin

www.entegreci.com | **destek@entegreci.com** | **0850 305 90 34**

Entegreci is an online electronic components store based in Türkiye. Search by manufacturer part number to see stock, prices and datasheets for integrated circuits, microcontrollers, transistors, passive components and connectors, or request a quote for parts that are not listed.

Bu sayfa Entegreci tarafından eklenmiştir. Belgenin önceki sayfaları asıl yayıncısına aittir ve içeriği değiştirilmemiştir; en güncel sürüm için belgenin yayıncısına başvurun.