UMW IPP072N10N3G


100V N-Channel MOSFET


1.Features

- $V_{DS\ (V)}$=100V
- I_D=80A
- $R_{DS(ON)}$<7.2mΩ(V_{GS}=10V)
- Ideal for high-frequency switching and synchronous rectification
- N-channel, normallevel
- Very low on-resistance $R_{DS(ON)}$
- 175 °C operating temperature
- Pb-free lead plating RoHS compliant

2.Pinning information

Pin	Symbol	Description
1	G	GATE
2	D	DRAIN
3	S	SOURCE





3.Absolute Maximum Ratings T_C= 25°C

Parameter	Symbol	Conditions	Rating	Units
Continuous drain current	I_D	T_C=25°C 2)	80	A
		T_C=100°C	70	A
Pulsed drain current 2)	$I_{D,pulse}$	T_C=25°C	320	A
Avalanche energy, single pulse	E_{AS}	I_D=80A, R_{GS}=25Ω	160	mJ
Gate source voltage	V_{GS}		±20	V
Power dissipation	P_{tot}	T_C=25°C	150	W
storage temperature	T_J,T_{STG}		-55 to 175	°C
IEC climatic cateory; DIN IEC 68-1			55/175/56	

4.Electrical Characteristic (T_C=25°C unless otherwise noted)

Parameter	Symbol	Conditions	Min	Typ	Max	Units
Thermal resistance, junction -case	R_{thJC}				1	K/W
Thermal resistance, junction -ambient	R_{thJA}	minimal footprint			62	K/W
		6 cm^2 cooling area [3])			40	K/W
Drain-source breakdown voltage	$V_{(BR)DSS}$	V_{GS}=0V, I_D=1mA	100			V
Gate threshold voltage	$V_{GS(th)}$	V_{DS}=V_{GS}, I_D=90μA	2	2.7	3.5	V
Zero gate voltage drain current	I_{DSS}	V_{DS}=100V, V_{GS}=0V, T_J=25°C		0.1	1	μA
		V_{DS}=100V, V_{GS}=0V, T_J=125°C		10	100	μA
Gate-source leakage current	I_{GSS}	V_{GS}=20V, V_{DS}=0V		1	100	nA
Drain-source on-state resistance	$R_{DS(ON)}$	V_{GS}=10V, I_D=80A		6.2	7.2	mΩ
		V_{GS}=6V, I_D=40A		7.6	12.7	mΩ
Gate resistance	R_G			1.6		Ω
Transconductance	g_{FS}	$\|V_{DS}\|>2\|I_D\|R_{DS(ON)max}$,$I_D$=80A	50	99		S
Input capacitance	C_{iss}	V_{GS}=0V, V_{DS}=50V, f=1MHz		3690	4910	pF
Output capacitance	C_{oss}			646		pF
Reverse transfer capacitance	C_{rss}			25		pF
Turn-on delay time	$t_{D(on)}$	V_{DD}=50V, V_{GS}=10V I_D=80A, R_G=3.6Ω		19		ns
Rise time	t_r			37		ns
Turn-off delay time	$t_{D(off)}$			37		ns
Fall time	t_f			9		ns
Gate to source charge	Q_{gs}	V_{DD}=50V, I_D=80A V_{GS}=0 to 10V		18		nC
Gate to drain charge	Q_{gd}			10		nC
Switching charge	Q_{SW}			16		nC
Gate charge total	Q_g			51	68	nC
Gate plateau voltage	$V_{plateau}$			4.9		V

Output charge	Q_{oss}	V_{DD}=50V, V_{GS}=0V		68	91	nC
Diode continuous forward current	I_S	T_C=25°C			80	A
Diode pulse current	$I_{S,pulse}$				320	A
Diode forward voltage	V_{SD}	V_{GS}=0V, I_F=80A, T_J=25°C		1	1.2	V
Reverse recovery time	t_{rr}	V_R=50V, I_F=I_S, di_F/dt=100A/μs		73		ns
Reverse recovery charge	Q_{rr}	V_R=50V, I_F=I_S, di_F/dt=100A/μs		139		nC

Notes:

6) See figure 16 for gate charge parameter definition.

5.1Typical characteristic

$P_{tot}=f(T_C)$




Fig 1. Power dissipation

$I_D=f(T_C)$; $V_{GS}\geq 10V$




Fig 2. Drain current

ID=f(V_{DS}); T_C=25°C; D=0, parameter: t_p




Fig 3. Safe operating area

$Z_{thJC}=f(t_p)$, parameter: $D=t_p/T$




Fig 4. Max transient thermal impedance

5.2Typical characteristic

$I_D=f(V_{DS})$; T_J=25°C, parameter: V_{GS}




Fig 5. output characteristics

$R_{DS(ON)}=f(I_D)$; T_J=25°C, parameter: V_{GS}




Fig 6. drain-source on resistance

ID=f(V_{GS}); |V_{DS}|>2| I_D |$R_{DS(ON)max}$, parameter: T_J




Fig 7. transfer characteristics

$g_{fs}=f(I_D)$; T_J=25°C




Fig 8. forward transconductance

5.3Typical characteristic

$R_{DS(ON)}=f(T_J)$; I_D=80A, V_{GS}=10V




Fig 9. Drain-source on-state resistance

$V_{GS(th)}=f(T_J)$;$V_{GS}=V_{DS}$; parameter: I_D




Fig 10. Tgate threshold voltage

C=f(V_{DS}); V_{GS}=0V; f=1MHZ




Fig 11. capacitances

$I_F=f(V_{SD})$, parameter: T_J




Fig 12. Forward characteristics of reverse diode

5.4Typical characteristic

$I_{AS}=f(t_{AV})$; $R_{GS}=25\Omega$, parameter: $T_{j(start)}$




Fig 13. Avalanche characteristics

$V_{GS}=f(Q_{gate})$; $I_D=80A$pulsed, parameter: V_{DD}




Fig 14. gate charge

$V_{BR(DSS)}=f(T_J)$; $I_D=1m$ A




Fig 15. drai source breakdown voltage





Fig 16. Gate charge waveforms

6.TO-220 Package Outline Dimensions




DIMENSIONS (mm are the original dimensions)

Symbol	A	A1	A2	A3	B	B1	C	C1	D	E	F	G
Min	9.7	8.44	1.05	4.8	15.4	12.9	4.28	1.1	0.6	3.4	2.65	5.2
Max	10.3	8.84	1.25	5.2	16.2	13.5	4.68	1.5	1.0	3.8	3.25	5.8

Symbol	H	K	L	L1	M	N	P	Q	T	DIA
Min	0.4	2.9	12.8	2.7	1.15	2.49	2.1	8.7	W:0.35	⊙1.5
Max	0.6	3.3	13.6	3.3	1.35	2.59	2.7	9.3		(deep 0.2)

7.Ordering information



yy: Year Code
ww: Week Code

Order Code	Package	Base QTY	Delivery Mode
UMW IPP072N10N3G	TO-220	1000	Tube and box

8.Disclaimer

UMW reserves the right to make changes to all products, specifications. Customers should obtain the latest version of product documentation and verify the completeness and currency of the information before placing an order.

When applying our products, please do not exceed the maximum rated values, as this may affect the reliability of the entire system. Under certain conditions, any semiconductor product may experience faults or failures. Buyers are responsible for adhering to safety standards and implementing safety measures during system design, prototyping, and manufacturing when using our products to prevent potential failure risks that could lead to personal injury or property damage.

Unless explicitly stated in writing, UMW products are not intended for use in medical, life-saving, or life-sustaining applications, nor for any other applications where product failure could result in personal injury or death. If customers use or sell the product for such applications without explicit authorization, they assume all associated risks.

When reselling, applying, or exporting, please comply with export control laws and regulations of China, the United States, the United Kingdom, the European Union, and other relevant countries, regions, and international organizations.

This document and any actions by UMW do not grant any intellectual property rights, whether express or implied, by estoppel or otherwise. The product names and marks mentioned herein may be trademarks of their respective owners.

ENTEGRECİ

Bu belge www.entegreci.com üzerinden sunulmaktadır.

Elektronik komponent tedarikinde Entegreci

Entegreci, Eskişehir merkezli, Türkiye geneline satış yapan bir elektronik komponent mağazasıdır. Entegreler (IC), mikrodenetleyiciler, transistörler, diyotlar, pasif elemanlar, konnektörler, modüller ve geliştirme kartları tek adetten seri üretim adetlerine kadar satılır. Ürün sayfalarında güncel stok durumunu, fiyatı ve datasheet bağlantısını bulabilirsiniz.

Parça koduyla arama

Üretici parça numarasını yazın; stok ve fiyatı hemen görün.

www.entegreci.com

Ürün kategorileri

Entegreden kapasitöre tüm elektronik komponent kategorileri.

Kategorilere göz atın

Üreticiler

Aradığınız üreticinin ürünlerini tek sayfada inceleyin.

Üreticileri görün

Toplu alım ve teklif

Listede olmayan ya da yüksek adetli parçalar için teklif isteyin.

Teklif isteyin

www.entegreci.com | **destek@entegreci.com** | **0850 305 90 34**

Entegreci is an online electronic components store based in Türkiye. Search by manufacturer part number to see stock, prices and datasheets for integrated circuits, microcontrollers, transistors, passive components and connectors, or request a quote for parts that are not listed.

Bu sayfa Entegreci tarafından eklenmiştir. Belgenin önceki sayfaları asıl yayıncısına aittir ve içeriği değiştirilmemiştir; en güncel sürüm için belgenin yayıncısına başvurun.