2N7002DW

60V N-Channel Enhancement Mode MOSFET

FEATURES


- $R_{DS(ON)}$, V_{GS}@10V,I_{DS}@500mA=5Ω
- $R_{DS(ON)}$, V_{GS}@4.5V,I_{DS}@75mA=7.5Ω

- Advanced Trench Process Technology
- High Density Cell Design For Ultra Low On-Resistance
- Specially Designed for Battery Operated Systems, Solid-State Relays Drivers : Relays, Displays, Lamps, Solenoids, Memories, etc.
- In compliance with EU RoHS 2002/95/EC directives

MECHANICALDATA

- Case: SOT-363 Package
- Terminals : Solderable per MIL-STD-750,Method 2026
- Marking : 702

SOT-363 Unit: inch (mm)



Maximum RATINGS and Thermal Characteristics (T_A=25°C unless otherwise noted)

PARAMETER		Symbol	Limit	Units
Drain-Source Voltage		V_{DS}	60	V
Gate-Source Voltage		V_{GS}	±20	V
Continuous Drain Current		I_D	115	mA
Pulsed Drain Current [1]		I_{DM}	800	mA
Maximum Power Dissipation	T_A=25°C T_A=75°C	P_D	200 120	mW
Operating Junction and Storage Temperature Range		T_J,T_{STG}	-55 to + 150	°C
Junction-to Ambient Thermal Resistance(PCB mounted)[2]		$R_{\theta JA}$	625	°C/W

Note: 1. Maximum DC current limited by the package
2. Surface mounted on FR4 board, t ≤ 10 sec


PAN JIT RESERVES THE RIGHT TO IMPROVE PRODUCT DESIGN,FUNCTIONS AND RELIABILITY WITHOUT NOTICE

2N7002DW


ELECTRICAL CHARACTERISTICS

Parameter	Symbol	Test Condition	Min.	Typ.	Max.	Units
Static						
Drain-Source Breakdown Voltage	BV_{DSS}	V_{GS}=0V, I_D=10uA	60	-	-	V
Gate Threshold Voltage	$V_{GS(th)}$	V_{DS}=V_{GS}, I_D=250uA	1	-	2.5	V
Drain-Source On-State Resistance	$R_{DS(on)}$	V_{GS}=4.5V, I_D=75mA	-	-	7.5	Ω
Drain-Source On-State Resistance	$R_{DS(on)}$	V_{GS}=10V, I_D=500mA	-	-	5	Ω
Zero Gate Voltage Drain Current	I_{DSS}	V_{DS}=60V, V_{GS}=0V	-	-	1	uA
Gate Body Leakage	I_{GSS}	V_{GS}=±20V, V_{DS}=0V	-	-	±100	nA
Forward Transconductance	g_{fS}	V_{DS}=15V, I_D=250mA	200	-	-	mS
Dynamic						
Total Gate Charge	Q_g	V_{DS}=15V, I_D=500mA V_{GS}=4.5V	-	0.6	0.7	nC
Gate-Source Charge	Q_{gs}		-	0.1	-	nC
Gate-Drain Charge	Q_{gd}		-	0.08	-	nC
Turn-On Delay Time	t_{on}	V_{DD}=10V , R_L=20Ω I_D=500mA , V_{GEN}=10V R_G=10Ω	-	9	15	ns
Turn-Off Delay Time	t_{off}		-	21	26	ns
Input Capacitance	C_{iss}	V_{DS}=25V, V_{GS}=0V f=1.0MH_Z	-	-	50	pF
Output Capacitance	C_{oss}		-	-	25	pF
Reverse Transfer Capacitance	C_{rss}		-	-	5	pF
Source-Drain Diode						
Max. Diode Forward Current	I_s	-	-	-	250	mA
Diode Forward Voltage	V_{SD}	I_S=250mA , V_{GS}=0V	-	0.93	1.2	V

Switching Test Circuit



Gate Charge Test Circuit



2N7002DW

Typical Characteristics Curves (T_A=25°C, unless otherwise noted)




FIG.1- Output Characteristic




FIG.2- Transfer Characteristic




FIG.3- On Resistance vs Drain Current




FIG.4- On Resistance vs Gate to Source Voltage




FIG.5- On Resistance vs Junction Temperature

2N7002DW




Fig.6 - Gate Charge Waveform




Fig.7 - Gate Charge




Fig.8 - Threshold Voltage vs Temperature




Fig.9 - Breakdown Voltage vs Junction Temperature





Fig.10 - Source-Drain Diode Forward Voltage

2N7002DW

MOUNTING PAD LAYOUT

SOT-363 Unit: inch (mm)



ORDER INFORMATION

- Packing information

  T/R - 10K per 13" plastic Reel

  T/R - 3K per 7” plastic Reel

LEGAL STATEMENT

Copyright PanJit International, Inc 2007

The information presented in this document is believed to be accurate and reliable. The specifications and information herein are subject to change without notice. Pan Jit makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose. Pan Jit products are not authorized for use in life support devices or systems. Pan Jit does not convey any license under its patent rights or rights of others.

ENTEGRECİ

Bu belge www.entegreci.com üzerinden sunulmaktadır.

Elektronik komponent tedarikinde Entegreci

Entegreci, Eskişehir merkezli, Türkiye geneline satış yapan bir elektronik komponent mağazasıdır. Entegreler (IC), mikrodenetleyiciler, transistörler, diyotlar, pasif elemanlar, konnektörler, modüller ve geliştirme kartları tek adetten seri üretim adetlerine kadar satılır. Ürün sayfalarında güncel stok durumunu, fiyatı ve datasheet bağlantısını bulabilirsiniz.

Parça koduyla arama

Üretici parça numarasını yazın; stok ve fiyatı hemen görün.

www.entegreci.com

Ürün kategorileri

Entegreden kapasitöre tüm elektronik komponent kategorileri.

Kategorilere göz atın

Üreticiler

Aradığınız üreticinin ürünlerini tek sayfada inceleyin.

Üreticileri görün

Toplu alım ve teklif

Listede olmayan ya da yüksek adetli parçalar için teklif isteyin.

Teklif isteyin

www.entegreci.com | **destek@entegreci.com** | **0850 305 90 34**

Entegreci is an online electronic components store based in Türkiye. Search by manufacturer part number to see stock, prices and datasheets for integrated circuits, microcontrollers, transistors, passive components and connectors, or request a quote for parts that are not listed.

Bu sayfa Entegreci tarafından eklenmiştir. Belgenin önceki sayfaları asıl yayıncısına aittir ve içeriği değiştirilmemiştir; en güncel sürüm için belgenin yayıncısına başvurun.