7MBR50XPA120-50


IGBT Modules

Power Module(X series)
1200V / 50A / PIM

■ Features

Low $V_{CE(sat)}$
Compact Package
P.C.Board Mount Module
Converter Diode Bridge Dynamic Brake Circuit
RoHS compliant Product

■ Typical appearance





■ Applications

Inverter for Motor Drive
AC and DC Servo Drive Amplifier
Uniterrupted Power Supply

■ Outline drawing (Unit : mm)


shows theoretical dimension.
shows reference dimension.





Weight: 200 g (typ.)

■ Equivalent circuit



■ **Maximum ratings (at T_c = 25°C unless otherwise specified)**

	Items		Symbols	Conditions		Maximum ratings	Units
Inverter	Collector-Emitter voltage		V_{CES}			1200	V
	Gate-Emitter voltage		V_{GES}			±20	V
	Collector current		I_C	Continuous	T_c=100°C	50	A
			I_C pulse	1ms		100	
	Forward current		I_F	Continuous		50	
			I_F pulse	1ms		100	
	Collector power dissipation		P_C	1 device		250	W
Brake IGBT	Collector-Emitter voltage		V_{CES}			1200	V
	Gate-Emitter voltage		V_{GES}			±20	V
	Collector current		I_C	Continuous	T_c=100°C	35	A
			I_C pulse	1ms		70	
	Collector power dissipation		P_C	1 device		200	W
Brake FWD	Forward current		I_F	Continuous		15	A
			I_{FRM}	1ms		30	
	Repetitive peak reverse voltage		V_{RRM}			1200	V
Converter	Repetitive peak reverse voltage		V_{RRM}			1600	V
	Average output current		I_O	Three-phase full wave rectified current	T_c=80°C	50	A
	Surge current (Non-Repetitive) (*1)		I_{FSM}	t=10ms, Half sine wave form	T_{vj}=25°C	630	A
					T_{vj}=150°C	520	
	I^2t (Non-Repetitive) (*1)		I^2t		T_{vj}=25°C	2000	A^2s
					T_{vj}=150°C	1350	
Junction temperature			T_{vj}	Inverter, Brake		175	°C
				Converter		150	
Operating junction temperature (under switching conditions)			T_{vjop}	Inverter, Brake		175	
				Converter		150	
Case temperature			T_c			125	
Storage temperature			T_{stg}			-40 ~ 125	
Isolation voltage	between terminals and copper base (*2)		V_{isol}	A.C. : 1min.		2500	Vrms
	between thermistor and others (*3)						
Screw torque	Mounting torque of screws to heat sink		M_5	M5		2.5～6.0	N·m

(*1) T_{vj} : Temperature at test start.

(*2) All terminals should be connected together during the test.

(*3) Two thermistor terminals should be connected together, other terminals should be connected together and shorted to base plate during the test.

■ **Electrical characteristics (at T_{vj} = 25°C unless otherwise specified)**

	Items	Symbols	Conditions		Characteristics min.	Characteristics typ.	Characteristics max.	Units
Inverter	Zero gate voltage collector current	I_{CES}	V_{GE} = 0V, V_{CE} = 1200V		-	-	50	μA
	Gate-Emitter leakage current	I_{GES}	V_{CE} = 0V V_{GE} = +20/-20V		-	-	100	nA
	Gate-Emitter threshold voltage	$V_{GE(th)}$	V_{CE} = 20V, I_C = 50mA		6.0	6.5	7.0	V
	Collector-Emitter saturation voltage	$V_{CE(sat)}$ (terminal)	V_{GE} = 15V, I_C = 50A	T_{vj}=25°C	-	1.70	2.20	V
		$V_{CE(sat)}$ (chip)		T_{vj}=25°C	-	1.50	1.95	
				T_{vj}=125°C	-	1.85	-	
				T_{vj}=150°C	-	1.95	-	
				T_{vj}=175°C	-	2.00	-	
	Internal gate resistance	r_g	-		-	0	-	Ω
	Capacitance	C_{ies}	V_{CE} = 10V, V_{GE} =0V, f = 1MHz		-	5.3	-	nF
		C_{oes}			-	0.18	-	
		C_{res}			-	0.05	-	
	Gate charge	Q_G	V_{CC} = 600V V_{GE}=-15 → +15V, I_C = 50A		-	340	-	nC
	Forward voltage	V_F (terminal)	I_F = 50A	T_{vj}=25°C	-	2.00	2.50	V
		V_F (chip)		T_{vj}=25°C	-	1.80	2.25	
				T_{vj}=125°C	-	1.85	-	
				T_{vj}=150°C	-	1.80	-	
				T_{vj}=175°C	-	1.75	-	
	Switching time (*1)	$t_{d(on)}$	V_{CC} = 600V, I_C,I_F = 50A L_s = 30nH, V_{GE} = +15/-15 V, R_G = 18 Ω	T_{vj}=25°C	-	0.09	-	μs
				T_{vj}=125°C	-	0.09	-	
				T_{vj}=150°C	-	0.09	-	
				T_{vj}=175°C	-	0.10	-	
		t_r	V_{CC} = 600V, I_C,I_F = 50A L_s = 30nH, V_{GE} = +15/-15 V, R_G = 18 Ω	T_{vj}=25°C	-	0.04	-	
				T_{vj}=125°C	-	0.04	-	
				T_{vj}=150°C	-	0.04	-	
				T_{vj}=175°C	-	0.04	-	
		$t_{d(off)}$	V_{CC} = 600V, I_C,I_F = 50A L_s = 30nH, V_{GE} = +15/-15 V, R_G = 18 Ω	T_{vj}=25°C	-	0.24	-	
				T_{vj}=125°C	-	0.27	-	
				T_{vj}=150°C	-	0.27	-	
				T_{vj}=175°C	-	0.28	-	
		t_f	V_{CC} = 600V, I_C,I_F = 50A L_s = 30nH, V_{GE} = +15/-15 V, R_G = 18 Ω	T_{vj}=25°C	-	0.11	-	
				T_{vj}=125°C	-	0.17	-	
				T_{vj}=150°C	-	0.20	-	
				T_{vj}=175°C	-	0.21	-	
	Reverse recovery time	t_{rr}	V_{CC} = 600V, I_C,I_F = 50A L_s = 30nH, V_{GE} = +15/-15 V, R_G = 18 Ω	T_{vj}=25°C	-	0.08	-	
				T_{vj}=125°C	-	0.14	-	
				T_{vj}=150°C	-	0.17	-	
				T_{vj}=175°C	-	0.19	-	

(*1) Turn on time (t_{on}) = $t_{d(on)}$ + t_r , Turn off time (t_{off}) = $t_{d(off)}$ + t_f

	Items	Symbols	Conditions		Characteristics min.	Characteristics typ.	Characteristics max.	Units
Inverter	Switching loss (per pulse)	E_{on}	V_{CC} = 600V, I_C,I_F = 50A, L_s = 30nH, V_{GE} = +15/-15 V, R_G = 18 Ω	T_{vj}=25°C	-	3.78	-	mJ
				T_{vj}=125°C	-	4.90	-	
				T_{vj}=150°C	-	5.46	-	
				T_{vj}=175°C	-	5.83	-	
		E_{off}	V_{CC} = 600V, I_C,I_F = 50A, L_s = 30nH, V_{GE} = +15/-15 V, R_G = 18 Ω	T_{vj}=25°C	-	3.36	-	
				T_{vj}=125°C	-	4.31	-	
				T_{vj}=150°C	-	4.62	-	
				T_{vj}=175°C	-	4.96	-	
		E_{rr}	V_{CC} = 600V, I_C,I_F = 50A, L_s = 30nH, V_{GE} = +15/-15 V, R_G = 18 Ω	T_{vj}=25°C	-	1.43	-	
				T_{vj}=125°C	-	2.52	-	
				T_{vj}=150°C	-	3.27	-	
				T_{vj}=175°C	-	3.72	-	
Brake	Zero gate voltage collector current	I_{CES}	V_{GE} = 0V, V_{CE} = 1200V		-	-	50	μA
	Gate-Emitter leakage current	I_{GES}	V_{CE} = 0V, V_{GE} = +20/-20V		-	-	100	nA
	Collector-Emitter saturation voltage	$V_{CE(sat)}$ (terminal)	V_{GE} = 15V, I_C = 35A	T_{vj}=25°C	-	1.65	2.10	V
		$V_{CE(sat)}$ (chip)		T_{vj}=25°C	-	1.50	1.95	
				T_{vj}=125°C	-	1.85	-	
				T_{vj}=150°C	-	1.95	-	
				T_{vj}=175°C	-	2.00	-	
	Internal gate resistance	r_g	-		-	0	-	Ω
	Switching time (*1)	$t_{d(on)}$	V_{CC} = 600V, I_C = 35A, L_s = 30nH, V_{GE} = +15/-15 V, R_G = 30 Ω	T_{vj}=25°C	-	0.10	-	μs
				T_{vj}=125°C	-	0.10	-	
				T_{vj}=150°C	-	0.11	-	
				T_{vj}=175°C	-	0.11	-	
		t_r	V_{CC} = 600V, I_C = 35A, L_s = 30nH, V_{GE} = +15/-15 V, R_G = 30 Ω	T_{vj}=25°C	-	0.04	-	
				T_{vj}=125°C	-	0.05	-	
				T_{vj}=150°C	-	0.05	-	
				T_{vj}=175°C	-	0.05	-	
		$t_{d(off)}$	V_{CC} = 600V, I_C = 35A, L_s = 30nH, V_{GE} = +15/-15 V, R_G = 30 Ω	T_{vj}=25°C	-	0.23	-	
				T_{vj}=125°C	-	0.27	-	
				T_{vj}=150°C	-	0.27	-	
				T_{vj}=175°C	-	0.27	-	
		t_f	V_{CC} = 600V, I_C = 35A, L_s = 30nH, V_{GE} = +15/-15 V, R_G = 30 Ω	T_{vj}=25°C	-	0.12	-	
				T_{vj}=125°C	-	0.18	-	
				T_{vj}=150°C	-	0.20	-	
				T_{vj}=175°C	-	0.21	-	
	Reverse current	I_{RRM}	V_R = 1200V		-	-	50	μA
	Forward voltage	V_F (terminal)	I_F = 15A	T_{vj}=25°C	-	1.95	2.40	V
		V_F (chip)	I_F = 15A	T_{vj}=25°C	-	1.80	2.25	
				T_{vj}=125°C	-	1.85	-	
				T_{vj}=150°C	-	1.80	-	
				T_{vj}=175°C	-	1.75	-	
Converter	Reverse current	I_{RRM}	V_R = 1600V		-	-	50	μA
	Forward voltage	V_{FM}	I_F = 50A	terminal	-	1.25	1.75	V
				chip	-	1.05	1.50	
Thermistor	Resistance	R	T = 25°C		-	5000	-	Ω
			T = 100°C		465	495	520	
	B value	B	T = 25/ 50°C		3305	3375	3450	K

(*1) Turn on time (t_{on}) = $t_{d(on)}$ + t_r , Turn off time (t_{off}) = $t_{d(off)}$ + t_f

NOTICE:
The external gate resistance (R_G) shown above is one of our recommended value for the purpose of minimum switching loss. However the optimum R_G depends on circuit configuration and/or environment. We recommend that the R_G has to be carefully chosen based on consideration if IGBT module matches design criteria, for example, switching loss, EMC/EMI, spike voltage, surge current and no unexpected oscillation and so on.

■Thermal resistance characteristics


Items	Symbols	Conditions	Characteristics			Units
			min.	typ.	max.	
Thermal resistance (1device)	$R_{th(j-c)}$	Inverter IGBT	-	-	0.59	°C/W
		Inverter FWD	-	-	0.71	
		Brake IGBT	-	-	0.74	
		Brake FWD	-	-	1.85	
		Converter Diode	-	-	0.72	
Contact thermal resistance (1 IGBT+1 FWD) (*1)	$R_{th(c-f)}$	with 1 W/(m·K) thermal grease	-	0.05	-	

(*1) This is the value which is defined mounting on the additional cooling fin with thermal grease.

[Inverter]

Collector current vs. Collector-Emitter voltage (typ.)


T_{vj}= 25°C / chip



[Inverter]

Collector current vs. Collector-Emitter voltage (typ.)


T_{vj}= 175°C / chip



[Inverter]

Collector current vs. Collector-Emitter voltage (typ.)


V_{GE}=15V / chip



[Inverter]

Collector-Emitter voltage vs. Gate-Emitter voltage (typ.)


T_{vj}= 25°C / chip



[Inverter]

Capacitance vs. Collector-Emitter voltage (typ.)


V_{GE}=0V, f= 1MHz, T_{vj}= 25°C



[Inverter]

Dynamic gate charge (typ.)


V_{CC}= 600V, I_C= 50A, T_{vj}= 25°C



[Inverter]

E_{on} vs. Collector current (typ.)


V_{CC}= 600V, V_{GE} = +15/-15 V, R_G= 18 Ω



[Inverter]

E_{on} vs. Gate resistance (typ.)


V_{CC}= 600V, V_{GE} = +15/-15 V, I_C= 50A



[Inverter]

E_{off} vs. Collector current (typ.)


V_{CC}= 600V, V_{GE} = +15/-15 V, R_G= 18 Ω



[Inverter]

E_{off} vs. Gate resistance (typ.)


V_{CC}= 600V, V_{GE} = +15/-15 V, I_C= 50A



[Inverter]

E_{rr} vs. Forward current (typ.)


V_{CC}= 600V, V_{GE} = +15/-15 V, R_G= 18 Ω



[Inverter]

E_{rr} vs. Gate resistance (typ.)


V_{CC}= 600V, V_{GE} = +15/-15 V, I_C= 50A



[Inverter]

Switching time vs. Collector current (typ.)


V_{CC}= 600V, R_G= 18Ω V_{GE}= +15/-15 V, T_{vj}= 25°C



[Inverter]

Switching time vs. Gate resistance (typ.)


V_{CC}= 600V, I_C= 50A, V_{GE}= +15/-15 V, T_{vj}= 25°C



[Inverter]

Switching time vs. Collector current (typ.)


V_{CC}= 600V, R_G= 18Ω V_{GE}= +15/-15 V, T_{vj}= 175°C



[Inverter]

Switching time vs. Gate resistance (typ.)


V_{CC}= 600V, I_C= 50A, V_{GE}= +15/-15 V, T_{vj}= 175°C



[Inverter]

Reverse bias safe operating area (max.)


V_{GE}= +15/-15 V, R_G>= 18Ω T_{vj}= 175°C



(Main terminals)

[Inverter]


Forward current vs. Forward voltage (typ.)



[Inverter]


Reverse recovery characteristics (typ.)

V_{CC}= 600V, V_{GE}= +15/-15 V, R_G= 18Ω




[Converter]

Forward current vs. Forward voltage (typ.)




Transient thermal resistance (max.)



n		1	2	3	4
τ_n	[sec]	0.0023	0.0301	0.0598	0.0708
r_n [°C/W]	IGBT	0.0633	0.1604	0.2267	0.1396
	FWD	0.0762	0.1931	0.2728	0.1680
	B-IGBT	0.0794	0.2012	0.2843	0.1751
	Conv	0.0772	0.1958	0.2766	0.1704

[Thermistor]


Temperature characteristic (typ.)



[Brake]

Collector current vs. Collector-Emitter voltage (typ.)


T_{vj}= 25°C / chip



[Brake]

Collector current vs. Collector-Emitter voltage (typ.)


T_{vj}= 175°C / chip



[Brake]

Collector current vs. Collector-Emitter voltage (typ.)


V_{GE}=15V / chip



[Brake]

Collector-Emitter voltage vs. Gate-Emitter voltage (typ.)


T_{vj}= 25°C / chip



[Brake]

Capacitance vs. Collector-Emitter voltage (typ.)


V_{GE}=0V, f= 1MHz, T_{vj}= 25°C



[Brake]

Dynamic gate charge (typ.)

V_{CC}= 600V, I_C= 35A, T_{vj}= 25°C



Warnings

1. This Catalog contains the product specifications, characteristics, data, materials, and structures as of 3/2023. The contents are subject to change without notice for specification changes or other reasons. When using a product listed in this Catalog, be sure to obtain the latest specifications.

2. All applications described in this Catalog exemplify the use of Fuji's products for your reference only. No right or license, either express or implied, under any patent, copyright, trade secret or other intellectual property right owned by Fuji Electric Co., Ltd. is (or shall be deemed) granted. Fuji Electric Co., Ltd. makes no representation or warranty, whether express or implied, relating to the infringement or alleged infringement of other's intellectual property rights which may arise from the use of the applications described herein.

3. Although Fuji Electric Co., Ltd. is enhancing product quality and reliability, a small percentage of semiconductor products may become faulty. When using Fuji Electric semiconductor products in your equipment, you are requested to take adequate safety measures to prevent the equipment from causing a physical injury, fire, or other problem if any of the products become faulty. It is recommended to make your design fail-safe, flame retardant, and free of malfunction.

4. The products introduced in this Catalog are intended for use in the following electronic and electrical equipment which has normal reliability requirements.
・Computers ・OA equipment ・Communications equipment (terminal devices) ・Measurement equipment
・Machine tools ・Audiovisual equipment ・Electrical home appliances ・Personal equipment ・Industrial robots etc.

5. If you need to use a product in this Catalog for equipment requiring higher reliability than normal, such as for the equipment listed below, it is imperative to contact Fuji Electric Co., Ltd. to obtain prior approval. When using these products for such equipment, take adequate measures such as a backup system to prevent the equipment from malfunctioning even if a Fuji's product incorporated in the equipment becomes faulty.
・Transportation equipment (mounted on cars and ships) ・Trunk communications equipment
・Traffic-signal control equipment ・Gas leakage detectors with an auto-shut-off feature
・Emergency equipment for responding to disasters and anti-burglary devices ・Safety devices ・Medical equipment

6. Do not use products in this Catalog for the equipment requiring strict reliability such as the following and equivalents to strategic equipment (without limitation).
・Space equipment ・Aeronautic equipment ・Nuclear control equipment ・Submarine repeater equipment

7. Copyright (c)1996-2023 by Fuji Electric Co., Ltd. All rights reserved.
No part of this Catalog may be reproduced in any form or by any means without the express permission of Fuji Electric Co., Ltd.

8. If you have any question about any portion in this Catalog, ask Fuji Electric Co., Ltd. or its sales agents before using the product. Neither Fuji Electric Co., Ltd. nor its agents shall be liable for any injury caused by any use of the products not in accordance with instructions set forth herein.

富士電機 Innovating Energy Technology

Technical Information

IGBT Modules

- Please refer to URLs below for futher information about products, application manuals and design support.
- 关于本规格书中没有记载的产品信息，应用手册，技术信息等，请参考以下链接。
- 本データシートに記載されていない製品情報，アプリケーションマニュアル，デザインサポートは以下のURLをご参照下さい。

FUJI ELECTRIC Power Semiconductor WEB site

日本	www.fujielectric.co.jp/products/semiconductor/
Global	www.fujielectric.com/products/semiconductor/
中国	www.fujielectric.com.cn/products/semiconductor/
Europe	www.fujielectric-europe.com/en/power_semiconductor/
North America	www.americas.fujielectric.com/products/semiconductors/

Information

日本

1 半導体総合カタログ	www.fujielectric.co.jp/products/semiconductor/catalog/
2 製品情報	www.fujielectric.co.jp/products/semiconductor/model/
3 アプリケーションマニュアル	www.fujielectric.co.jp/products/semiconductor/model/igbt/application/
4 デザインサポート	www.fujielectric.co.jp/products/semiconductor/model/igbt/technical/
5 マウンティングインストラクション	www.fujielectric.co.jp/products/semiconductor/model/igbt/mounting/
6 IGBT 損失シミュレーションソフト	www.fujielectric.co.jp/products/semiconductor/model/igbt/simulation/
7 富士電機技報	www.fujielectric.co.jp/products/semiconductor/journal/
8 製品のお問い合わせ	www.fujielectric.co.jp/products/semiconductor/contact/
9 改廃のお知らせ	www.fujielectric.co.jp/products/semiconductor/discontinued/

Global

1 Semiconductors General Catalog	www.fujielectric.com/products/semiconductor/catalog/
2 Product Information	www.fujielectric.com/products/semiconductor/model/
3 Application Manuals	www.fujielectric.com/products/semiconductor/model/igbt/application/
4 Design Support	www.fujielectric.com/products/semiconductor/model/igbt/technical/
5 Mounting Instructions	www.fujielectric.com/products/semiconductor/model/igbt/mounting/
6 IGBT Loss Simulation Software	www.fujielectric.com/products/semiconductor/model/igbt/simulation/
7 Fuji Electric Journal	www.fujielectric.com/products/semiconductor/journal/
8 Contact	www.fujielectric.com/contact/
9 Revised and discontinued product information	www.fujielectric.com/products/semiconductor/discontinued/

中国

1 半导体综合目录	www.fujielectric.com.cn/products/semiconductor/catalog/
2 产品信息	www.fujielectric.com.cn/products/semiconductor/model/
3 应用手册	www.fujielectric.com.cn/products/semiconductor/model/igbt/application/
4 技术信息	www.fujielectric.com.cn/products/semiconductor/model/igbt/technical/
5 安装说明书	www.fujielectric.com.cn/products/semiconductor/model/igbt/mounting/
6 IGBT 损耗模拟软件	www.fujielectric.com.cn/products/semiconductor/model/igbt/simulation/
7 富士电机技报	www.fujielectric.com.cn/products/semiconductor/journal/
8 产品咨询	www.fujielectric.com/contact/
9 产品更改和停产信息	www.fujielectric.com.cn/products/semiconductor/discontinued/

ENTEGRECİ

Bu belge www.entegreci.com üzerinden sunulmaktadır.

Elektronik komponent tedarikinde Entegreci

Entegreci, Eskişehir merkezli, Türkiye geneline satış yapan bir elektronik komponent mağazasıdır. Entegreler (IC), mikrodenetleyiciler, transistörler, diyotlar, pasif elemanlar, konnektörler, modüller ve geliştirme kartları tek adetten seri üretim adetlerine kadar satılır. Ürün sayfalarında güncel stok durumunu, fiyatı ve datasheet bağlantısını bulabilirsiniz.

Parça koduyla arama

Üretici parça numarasını yazın; stok ve fiyatı hemen görün.

www.entegreci.com

Ürün kategorileri

Entegreden kapasitöre tüm elektronik komponent kategorileri.

Kategorilere göz atın

Üreticiler

Aradığınız üreticinin ürünlerini tek sayfada inceleyin.

Üreticileri görün

Toplu alım ve teklif

Listede olmayan ya da yüksek adetli parçalar için teklif isteyin.

Teklif isteyin

www.entegreci.com | **destek@entegreci.com** | **0850 305 90 34**

Entegreci is an online electronic components store based in Türkiye. Search by manufacturer part number to see stock, prices and datasheets for integrated circuits, microcontrollers, transistors, passive components and connectors, or request a quote for parts that are not listed.

Bu sayfa Entegreci tarafından eklenmiştir. Belgenin önceki sayfaları asıl yayıncısına aittir ve içeriği değiştirilmemiştir; en güncel sürüm için belgenin yayıncısına başvurun.