UMW AO4803A

-30V Dual P-Channel MOSFET

1.Description

The AO4803A uses advanced technology to provide excellent $R_{DS(ON)}$ with low gate charge. This device is suitable for use as a load switch or in PWM applications.

2.Features

- $V_{DS\ (V)}$= -30V
- I_D=-5A
- $R_{DS(ON)}$<46mΩ(V_{GS}=-10V)
- $R_{DS(ON)}$<74mΩ(V_{GS}=-4.5V)

3.Pinning information

Pin	Symbol	Description
2,4	G1, G2	GATE
1,3	S1, S2	SOURCE
5,6,7,8	D1, D2	DRAIN

SOP-8



4.Absolute Maximum Ratings T_A=25°C unless otherwise noted

Parameter		Symbol	Rating	Units
Drain-Source Voltage		V_{DS}	-30	V
Gate-Source Voltage		V_{GS}	±20	
Continuous Drain Current	T_A=25°C	I_D	-5	A
	T_A=70°C		-4	
Pulsed Drain Current [c]		I_{DM}	-30	
Avalanche Current [c]		I_{AS}, I_{AR}	17	
Avalanche energy L=0.1mH [c]		E_{AS}, E_{AR}	14	mJ
Power Dissipation [B]	T_A=25°C	P_D	2	W
	T_A=70°C		1.3	
Junction and Storage Temperature Range		T_J, T_{STG}	-55 to 150	°C

5.Thermal Characteristics

Parameter		Symbol	Typ	Max	Units
Maximum Junction-to-Ambient [A]	t ≤ 10s	$R_{\theta JA}$	48	62.5	°C/W
Maximum Junction-to-Ambient [A D]	Steady-State		74	110	°C/W
Maximum Junction-to-Lead	Steady-State	$R_{\theta JL}$	35	40	°C/W

6.Electrical Characteristics (T_J=25°C unless otherwise noted)

Parameter	Symbol	Conditions	Min	Typ	Max	Units
Drain-Source Breakdown Voltage	BV_{DSS}	I_D=-250μA, V_{GS}=0V	-30			V
Zero Gate Voltage Drain Current	I_{DSS}	V_{DS}=-30V, V_{GS}=0V			-1	μA
		T_J=55°C			-5	μA
Gate-Body leakage current	I_{GSS}	V_{DS}=0V, V_{GS}=±20V			±100	nA
Gate Threshold Voltage	$V_{GS(th)}$	V_{DS}=V_{GS}, I_D=-250μA	-1.5	-2	-2.5	V
On state drain current	$I_{D(ON)}$	V_{GS}=-10V, V_{DS}=-5V	-30			A
Static Drain-Source On-Resistance	$R_{DS(ON)}$	V_{GS}=-10V, I_D=-5A		32	46	mΩ
		V_{GS}=-4.5V, I_D=-4A		51	74	mΩ
Forward Transconductance	g_{FS}	V_{DS}=-5V, I_D=-5A		13		S
Diode Forward Voltage	V_{SD}	I_S=-1A, V_{GS}=0V		-0.7	-1	V
Maximum Body-Diode Continuous Current	I_S				-2.5	A
Input Capacitance	C_{iss}	V_{GS}=0V, V_{DS}=-15V, f=1MHz		520		pF
Output Capacitance	C_{oss}			100		pF
Reverse Transfer Capacitance	C_{rss}			65		pF
Gate resistance	R_g	V_{GS}=0V, V_{DS}=0V, f=1MHz	3.5	7.5	11.5	Ω
Total Gate Charge	Q_g(10V)	V_{GS}=-10V, V_{DS}=-15V, I_D=-5A		9.2	11	nC
Total Gate Charge	Q_g(4.5V)			4.6	6	nC
Gate Source Charge	Q_{gs}			1.6		nC
Gate Drain Charge	Q_{gd}			2.2		nC
Turn-On DelayTime	$t_{D(on)}$	V_{GS}=-10V, V_{DS}=-15V, R_L=3Ω, R_{GEN}=3Ω		7.5		ns
Turn-On Rise Time	t_r			5.5		ns
Turn-Off DelayTime	$t_{D(off)}$			19		ns
Turn-Off Fall Time	t_f			7		ns
Body Diode Reverse Recovery Time	t_{rr}	I_F=5A, dI/dt=100A/μs		11		ns
Body Diode Reverse Recovery Charge	Q_{rr}	I_F=5A, dI/dt=100A/μs		5.3		nC

A. The value of $R_{\theta JA}$ is measured with the device mounted on 1in ^{2} FR-4 board with 2oz. Copper, in a still air environment with T_A=25°C. The value in any given application depends on the user's specific board design.

B. The power dissipation P_D is based on $T_{J(MAX)}$=150°C, using ≤ 10s junction-to-ambient thermal resistance.

C. Repetitive rating, pulse width limited by junction temperature $T_{J(MAX)}$=150°C. Ratings are based on low frequency and duty cycles to keep initial T_J=25°C.

D. The $R_{\theta JA}$ is the sum of the thermal impedence from junction to lead $R_{\theta JL}$ and lead to ambient.

E. The static characteristics in Figures 1 to 6 are obtained using <300μs pulses, duty cycle 0.5% max.

F. These curves are based on the junction-to-ambient thermal impedence which is measured with the device mounted on 1 in ^{2} FR-4 board with 2oz. Copper, assuming a maximum junction temperature of $T_{J(MAX)}$=150°C. The SOA curve provides a single pulse rating.

7.1TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS



Fig 1: On-Region Characteristics (Note E)



Figure 2: Transfer Characteristics (Note E)



Figure 3: On-Resistance vs. Drain Current and Gate Voltage (Note E)



Figure 4: On-Resistance vs. Junction Temperature (Note E)



Figure 5: On-Resistance vs. Gate-Source Voltage (Note E)



Figure 6: Body-Diode Characteristics (Note E)

7.1TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS



Figure 7: Normalized Maximum Transient Thermal Impedance (Note F)

7.2TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS



Figure 8: Gate-Charge Characteristics



Figure 9: Capacitance Characteristics



Figure 10: Single Pulse Avalanche capability (Note C)



Figure 11: Maximum Forward Biased Safe Operating Area (Note F)



Figure 12: Single Pulse Power Rating Junction-to-Ambient (Note F)

8.SOP-8 Package Outline Dimensions



DIMENSIONS (mm are the original dimensions)

Symbol	A	A1	A2	A3	b	c	D	E	E1	e	h	L
Min	-	0.05	1.30	0.60	0.39	0.20	4.70	5.80	3.80	1.24	0.30	0.50
Max	1.75	0.20	1.50	0.70	0.47	0.24	5.10	6.20	4.00	1.30	0.50	0.80

Symbol	L1	θ
Min	1.00	0°
Max	1.10	8°

9.Ordering information



yy: Year Code
ww: Week Code

Order Code	Package	Base QTY	Delivery Mode
UMW AO4803A	SOP-8	3000	Tape and reel

10.Disclaimer

UMW reserves the right to make changes to all products, specifications. Customers should obtain the latest version of product documentation and verify the completeness and currency of the information before placing an order.

When applying our products, please do not exceed the maximum rated values, as this may affect the reliability of the entire system. Under certain conditions, any semiconductor product may experience faults or failures. Buyers are responsible for adhering to safety standards and implementing safety measures during system design, prototyping, and manufacturing when using our products to prevent potential failure risks that could lead to personal injury or property damage.

Unless explicitly stated in writing, UMW products are not intended for use in medical, life-saving, or life-sustaining applications, nor for any other applications where product failure could result in personal injury or death. If customers use or sell the product for such applications without explicit authorization, they assume all associated risks.

When reselling, applying, or exporting, please comply with export control laws and regulations of China, the United States, the United Kingdom, the European Union, and other relevant countries, regions, and international organizations.

This document and any actions by UMW do not grant any intellectual property rights, whether express or implied, by estoppel or otherwise. The product names and marks mentioned herein may be trademarks of their respective owners.

ENTEGRECİ

Bu belge www.entegreci.com üzerinden sunulmaktadır.

Elektronik komponent tedarikinde Entegreci

Entegreci, Eskişehir merkezli, Türkiye geneline satış yapan bir elektronik komponent mağazasıdır. Entegreler (IC), mikrodenetleyiciler, transistörler, diyotlar, pasif elemanlar, konnektörler, modüller ve geliştirme kartları tek adetten seri üretim adetlerine kadar satılır. Ürün sayfalarında güncel stok durumunu, fiyatı ve datasheet bağlantısını bulabilirsiniz.

Parça koduyla arama

Üretici parça numarasını yazın; stok ve fiyatı hemen görün.

www.entegreci.com

Ürün kategorileri

Entegreden kapasitöre tüm elektronik komponent kategorileri.

Kategorilere göz atın

Üreticiler

Aradığınız üreticinin ürünlerini tek sayfada inceleyin.

Üreticileri görün

Toplu alım ve teklif

Listede olmayan ya da yüksek adetli parçalar için teklif isteyin.

Teklif isteyin

www.entegreci.com | **destek@entegreci.com** | **0850 305 90 34**

Entegreci is an online electronic components store based in Türkiye. Search by manufacturer part number to see stock, prices and datasheets for integrated circuits, microcontrollers, transistors, passive components and connectors, or request a quote for parts that are not listed.

Bu sayfa Entegreci tarafından eklenmiştir. Belgenin önceki sayfaları asıl yayıncısına aittir ve içeriği değiştirilmemiştir; en güncel sürüm için belgenin yayıncısına başvurun.