ALPHA & OMEGA SEMICONDUCTOR

AOT8N50/AOTF8N50

500V, 9A N-Channel MOSFET

General Description

The AOT8N50 & AOTF8N50 have been fabricated using an advanced high voltage MOSFET process that is designed to deliver high levels of performance and robustness in popular AC-DC applications.
By providing low $R_{DS(on)}$, C_{iss} and C_{rss} along with guaranteed avalanche capability these parts can be adopted quickly into new and existing offline power supply designs.

For Halogen Free add "L" suffix to part number:
AOT8N50L & AOTF8N50L

Product Summary

V_{DS}	600V@150℃
I_D (at V_{GS}=10V)	9A
$R_{DS(ON)}$ (at V_{GS}=10V)	< 0.85Ω

100% UIS Tested
100% R_g Tested

RoHS Compliant

TO-220 Top View TO-220F







Absolute Maximum Ratings T_A=25°C unless otherwise noted

Parameter		Symbol	AOT8N50	AOTF8N50	Units
Drain-Source Voltage		V_{DS}	500		V
Gate-Source Voltage		V_{GS}	±30		V
Continuous Drain Current	T_C=25°C	I_D	9	9*	A
	T_C=100°C		6	6*	
Pulsed Drain Current [C]		I_{DM}	30		
Avalanche Current [C]		I_{AR}	3.2		A
Repetitive avalanche energy [C]		E_{AR}	154		mJ
Single plused avalanche energy [G]		E_{AS}	307		mJ
Peak diode recovery dv/dt		dv/dt	5		V/ns
Power Dissipation [B]	T_C=25°C	P_D	192	38.5	W
	Derate above 25°C		1.5	0.3	W/ °C
Junction and Storage Temperature Range		T_J, T_{STG}	-55 to 150		°C
Maximum lead temperature for soldering purpose, 1/8" from case for 5 seconds		T_L	300		°C

Thermal Characteristics

Parameter	Symbol	AOT8N50	AOTF8N50	Units
Maximum Junction-to-Ambient [A,D]	$R_{\theta JA}$	65	65	°C/W
Maximum Case-to-sink [A]	$R_{\theta CS}$	0.5	--	°C/W
Maximum Junction-to-Case	$R_{\theta JC}$	0.65	3.25	°C/W

* Drain current limited by maximum junction temperature.

Electrical Characteristics (T_J=25°C unless otherwise noted)

Symbol	Parameter	Conditions	Min	Typ	Max	Units
STATIC PARAMETERS						
BV_{DSS}	Drain-Source Breakdown Voltage	I_D=250µA, V_{GS}=0V, T_J=25°C	500			V
		I_D=250µA, V_{GS}=0V, T_J=150°C		600		
BV_{DSS} /ΔTJ	Breakdown Voltage Temperature Coefficient	I_D=250µA, V_{GS}=0V		0.56		V/°C
I_{DSS}	Zero Gate Voltage Drain Current	V_{DS}=500V, V_{GS}=0V			1	µA
		V_{DS}=400V, T_J=125°C			10	
I_{GSS}	Gate-Body leakage current	V_{DS}=0V, V_{GS}=±30V			±100	nA
$V_{GS(th)}$	Gate Threshold Voltage	V_{DS}=5V I_D=250µA	3.4	4	4.5	V
$R_{DS(ON)}$	Static Drain-Source On-Resistance	V_{GS}=10V, I_D=4A		0.63	0.85	Ω
g_{FS}	Forward Transconductance	V_{DS}=40V, I_D=4A		10		S
V_{SD}	Diode Forward Voltage	I_S=1A,V_{GS}=0V		0.73	1	V
I_S	Maximum Body-Diode Continuous Current				8	A
I_{SM}	Maximum Body-Diode Pulsed Current				30	A
DYNAMIC PARAMETERS						
C_{iss}	Input Capacitance	V_{GS}=0V, V_{DS}=25V, f=1MHz	694	868	1042	pF
C_{oss}	Output Capacitance		74	93	112	pF
C_{rss}	Reverse Transfer Capacitance		6.2	7.8	9.4	pF
R_g	Gate resistance	V_{GS}=0V, V_{DS}=0V, f=1MHz	2	4	6	Ω
SWITCHING PARAMETERS						
Q_g	Total Gate Charge	V_{GS}=10V, V_{DS}=400V, I_D=8A		23.6	28	nC
Q_{gs}	Gate Source Charge			5.2	6.2	nC
Q_{gd}	Gate Drain Charge			10.6	12.7	nC
$t_{D(on)}$	Turn-On DelayTime	V_{GS}=10V, V_{DS}=250V, I_D=8A, R_G=25Ω		19.5	24	ns
t_r	Turn-On Rise Time			47	56.4	ns
$t_{D(off)}$	Turn-Off DelayTime			51.5	62	ns
t_f	Turn-Off Fall Time			38.5	46	ns
t_{rr}	Body Diode Reverse Recovery Time	I_F=8A,dI/dt=100A/µs,V_{DS}=100V		206	247	ns
Q_{rr}	Body Diode Reverse Recovery Charge	I_F=8A,dI/dt=100A/µs,V_{DS}=100V		2.1	2.6	µC

A. The value of $R_{\theta JA}$ is measured with the device in a still air environment with T_A =25°C.

B. The power dissipation P_D is based on $T_{J(MAX)}$=150°C, using junction-to-case thermal resistance, and is more useful in setting the upper dissipation limit for cases where additional heatsinking is used.

C. Repetitive rating, pulse width limited by junction temperature $T_{J(MAX)}$=150°C, Ratings are based on low frequency and duty cycles to keep initial T_J =25°C.

D. The $R_{\theta JA}$ is the sum of the thermal impedence from junction to case $R_{\theta JC}$ and case to ambient.

E. The static characteristics in Figures 1 to 6 are obtained using <300 µs pulses, duty cycle 0.5% max.

F. These curves are based on the junction-to-case thermal impedence which is measured with the device mounted to a large heatsink, assuming a maximum junction temperature of $T_{J(MAX)}$=150°C. The SOA curve provides a single pulse rating.

G. L=60mH, I_{AS}=3.2A, V_{DD}=150V, R_G=25Ω, Starting T_J=25°C

THIS PRODUCT HAS BEEN DESIGNED AND QUALIFIED FOR THE CONSUMER MARKET. APPLICATIONS OR USES AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS ARE NOT AUTHORIZED. AOS DOES NOT ASSUME ANY LIABILITY ARISING OUT OF SUCH APPLICATIONS OR USES OF ITS PRODUCTS. AOS RESERVES THE RIGHT TO IMPROVE PRODUCT DESIGN, FUNCTIONS AND RELIABILITY WITHOUT NOTICE.

TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS



Fig 1: On-Region Characteristics



Figure 2: Transfer Characteristics



Figure 3: On-Resistance vs. Drain Current and Gate Voltage



Figure 4: On-Resistance vs. Junction Temperature



Figure 5: Break Down vs. Junction Temperature



Figure 6: Body-Diode Characteristics (Note E)

TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS



Figure 7: Gate-Charge Characteristics



Figure 8: Capacitance Characteristics



Figure 9: Maximum Forward Biased Safe Operating Area for AOT8N50 (Note F)



Figure 10: Maximum Forward Biased Safe Operating Area for AOTF8N50 (Note F)



Figure 11: Current De-rating (Note B)

TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS



Figure 12: Normalized Maximum Transient Thermal Impedance for AOT8N50 (Note F)



Figure 13: Normalized Maximum Transient Thermal Impedance for AOTF8N50 (Note F)

Gate Charge Test Circuit & Waveform



Resistive Switching Test Circuit & Waveforms



Unclamped Inductive Switching (UIS) Test Circuit & Waveforms



Diode Recovery Test Circuit & Waveforms



ENTEGRECİ

Bu belge www.entegreci.com üzerinden sunulmaktadır.

Elektronik komponent tedarikinde Entegreci

Entegreci, Eskişehir merkezli, Türkiye geneline satış yapan bir elektronik komponent mağazasıdır. Entegreler (IC), mikrodenetleyiciler, transistörler, diyotlar, pasif elemanlar, konnektörler, modüller ve geliştirme kartları tek adetten seri üretim adetlerine kadar satılır. Ürün sayfalarında güncel stok durumunu, fiyatı ve datasheet bağlantısını bulabilirsiniz.

Parça koduyla arama

Üretici parça numarasını yazın; stok ve fiyatı hemen görün.

www.entegreci.com

Ürün kategorileri

Entegreden kapasitöre tüm elektronik komponent kategorileri.

Kategorilere göz atın

Üreticiler

Aradığınız üreticinin ürünlerini tek sayfada inceleyin.

Üreticileri görün

Toplu alım ve teklif

Listede olmayan ya da yüksek adetli parçalar için teklif isteyin.

Teklif isteyin

www.entegreci.com | **destek@entegreci.com** | **0850 305 90 34**

Entegreci is an online electronic components store based in Türkiye. Search by manufacturer part number to see stock, prices and datasheets for integrated circuits, microcontrollers, transistors, passive components and connectors, or request a quote for parts that are not listed.

Bu sayfa Entegreci tarafından eklenmiştir. Belgenin önceki sayfaları asıl yayıncısına aittir ve içeriği değiştirilmemiştir; en güncel sürüm için belgenin yayıncısına başvurun.