ISOTOP® Buck chopper MOSFET Power Module

V_{DSS} = 500V
R_{DSon} = 100mΩ max @ Tj = 25°C
I_D = 41A @ Tc = 25°C





ISOTOP®

Application

- AC and DC motor control
- Switched Mode Power Supplies

Features

- Power MOS 7® MOSFETs
  - Low R_{DSon}
  - Low input and Miller capacitance
  - Low gate charge
  - Fast intrinsic reverse diode
  - Avalanche energy rated
  - Very rugged
- ISOTOP® Package (SOT-227)
- Very low stray inductance
- High level of integration

Benefits

- Outstanding performance at high frequency operation
- Direct mounting to heatsink (isolated package)
- Low junction to case thermal resistance
- Very rugged
- Low profile
- RoHS Compliant

Absolute maximum ratings

Symbol	*Parameter*			*Max ratings*	*Unit*
V_{DSS}	Drain - Source Breakdown Voltage			500	V
I_D	Continuous Drain Current		T_c = 25°C	41	A
			T_c = 80°C	30	
I_{DM}	Pulsed Drain current			164	
V_{GS}	Gate - Source Voltage			±30	V
R_{DSon}	Drain - Source ON Resistance			100	mΩ
P_D	Maximum Power Dissipation		T_c = 25°C	378	W
I_{AR}	Avalanche current (repetitive and non repetitive)			41	A
E_{AR}	Repetitive Avalanche Energy			50	mJ
E_{AS}	Single Pulse Avalanche Energy			1600	
IF_{AV}	Maximum Average Forward Current	Duty cycle=0.5	Tc = 80°C	30	A
IF_{RMS}	RMS Forward Current (Square wave, 50% duty)			39	

CAUTION: These Devices are sensitive to Electrostatic Discharge. Proper Handling Procedures Should Be Followed.

All ratings @ T_j = 25°C unless otherwise specified

Electrical Characteristics

Symbol	*Characteristic*	*Test Conditions*		*Min*	*Typ*	*Max*	*Unit*
I_{DSS}	Zero Gate Voltage Drain Current	V_{GS} = 0V, V_{DS} = 500V	T_j = 25°C			100	µA
		V_{GS} = 0V, V_{DS} = 400V	T_j = 125°C			500	
$R_{DS(on)}$	Drain – Source on Resistance	V_{GS} = 10V, I_D = 23A				100	mΩ
$V_{GS(th)}$	Gate Threshold Voltage	V_{GS} = V_{DS}, I_D = 2.5mA		3		5	V
I_{GSS}	Gate – Source Leakage Current	V_{GS} = ±20 V, V_{DS} = 0V				±100	nA

Dynamic Characteristics

Symbol	*Characteristic*	*Test Conditions*	*Min*	*Typ*	*Max*	*Unit*
C_{iss}	Input Capacitance	V_{GS} = 0V V_{DS} = 25V f = 1MHz		4360		pF
C_{oss}	Output Capacitance			894		
C_{rss}	Reverse Transfer Capacitance			60		
Q_g	Total gate Charge	V_{GS} = 10V V_{Bus} = 250V I_D = 41A @ T_J=25°C		96		nC
Q_{gs}	Gate – Source Charge			24		
Q_{gd}	Gate – Drain Charge			49		
$T_{d(on)}$	Turn-on Delay Time	**Resistive switching @ 25°C** V_{GS} = 15V V_{Bus} = 250V I_D = 41A @ T_J=25°C R_G = 0.6Ω		11		ns
T_r	Rise Time			15		
$T_{d(off)}$	Turn-off Delay Time			25		
T_f	Fall Time			3		
E_{on}	Turn-on Switching Energy	**Inductive Switching @ 25°C** V_{bus} = 330V, V_{GS}=15V I_D=46A, R_G=5Ω		543		µJ
E_{off}	Turn-off Switching Energy			509		
E_{on}	Turn-on Switching Energy	**Inductive Switching @ 125°C** V_{bus} = 330V, V_{GS}=15V I_D=46A, R_G=5Ω		843		µJ
E_{off}	Turn-off Switching Energy			593		

Chopper diode ratings and characteristics

Symbol	*Characteristic*	*Test Conditions*		*Min*	*Typ*	*Max*	*Unit*
V_F	Diode Forward Voltage	I_F = 30A			1.6	1.8	V
		I_F = 60A			1.9		
		I_F = 30A	T_j = 125°C		1.4		
I_{RM}	Maximum Reverse Leakage Current	V_R = 600V	T_j = 25°C			250	µA
		V_R = 600V	T_j = 125°C			500	
C_T	Junction Capacitance	V_R = 200V			44		pF
t_{rr}	Reverse Recovery Time	I_F=1A, V_R=30V di/dt =100A/µs	T_j = 25°C		23		ns
	Reverse Recovery Time	I_F = 30A V_R = 400V di/dt =200A/µs	T_j = 25°C		85		
			T_j = 125°C		160		
I_{RRM}	Maximum Reverse Recovery Current		T_j = 25°C		4		A
			T_j = 125°C		8		
Q_{rr}	Reverse Recovery Charge		T_j = 25°C		130		nC
			T_j = 125°C		700		
t_{rr}	Reverse Recovery Time	I_F = 30A V_R = 400V di/dt =1000A/µs	T_j = 125°C		70		ns
Q_{rr}	Reverse Recovery Charge				1300		nC
I_{RRM}	Maximum Reverse Recovery Current				30		A

Thermal and package characteristics

Symbol	*Characteristic*		*Min*	*Typ*	*Max*	*Unit*
R_{thJC}	Junction to Case Thermal Resistance	MOSFET			0.33	°C/W
		Diode			1.21	
R_{thJA}	Junction to Ambient (IGBT & Diode)				20	
V_{ISOL}	RMS Isolation Voltage, any terminal to case t =1 min, 50/60Hz		2500			V
T_J,T_{STG}	Storage Temperature Range		-55		150	°C
T_L	Max Lead Temp for Soldering:0.063" from case for 10 sec				300	
Torque	Mounting torque (Mounting = 8-32 or 4mm Machine and terminals = 4mm Machine)				1.5	N.m
Wt	Package Weight			29.2		g

Typical MOSFET Performance Curve



FIGURE 1, MAXIMUM EFFECTIVE TRANSIENT THERMAL IMPEDANCE, JUNCTION-TO-CASE vs PULSE DURATION



FIGURE 2, TRANSIENT THERMAL IMPEDANCE MODEL



FIGURE 3, LOW VOLTAGE OUTPUT CHARACTERISTICS



FIGURE 4, TRANSFER CHARACTERISTICS



FIGURE 5, R_{DS}(ON) vs DRAIN CURRENT



FIGURE 6, MAXIMUM DRAIN CURRENT vs CASE TEMPERATURE



FIGURE 7, BREAKDOWN VOLTAGE vs TEMPERATURE



FIGURE 8, ON-RESISTANCE vs. TEMPERATURE



FIGURE 9, THRESHOLD VOLTAGE vs TEMPERATURE



FIGURE 10, MAXIMUM SAFE OPERATING AREA



FIGURE 11, CAPACITANCE vs DRAIN-TO-SOURCE VOLTAGE



FIGURE 12, GATE CHARGES vs GATE-TO-SOURCE VOLTAGE



FIGURE 13, SOURCE-DRAIN DIODE FORWARD VOLTAGE



FIGURE 14, DELAY TIMES vs CURRENT



FIGURE 15, RISE AND FALL TIMES vs CURRENT



FIGURE 16, SWITCHING ENERGY vs CURRENT



FIGURE 17, SWITCHING ENERGY VS. GATE RESISTANCE

Typical Diode Performance Curve



FIGURE 1a. MAXIMUM EFFECTIVE TRANSIENT THERMAL IMPEDANCE, JUNCTION-TO-CASE vs. PULSE DURATION



FIGURE 1b, TRANSIENT THERMAL IMPEDANCE MODEL



Figure 2. Forward Current *vs.* Forward Voltage



Figure 3. Reverse Recovery Time *vs.* Current Rate of Change



Figure 4. Reverse Recovery Charge *vs.* Current Rate of Change



Figure 5. Reverse Recovery Current *vs.* Current Rate of Change



Figure 6. Dynamic Parameters *vs.* Junction Temperature



Figure 7. Maximum Average Forward Current *vs.* CaseTemperature



Figure 8. Junction Capacitance *vs.* Reverse Voltage



Figure 9. Diode Test Circuit

1. I_F - Forward Conduction Current
2. di_F/dt - Rate of Diode Current Change Through Zero Crossing.
3. I_{RRM} - Maximum Reverse Recovery Current.
4. t_{rr} - Reverse Recovery Time, measured from zero crossing where diode current goes from positive to negative, to the point at which the straight line through I_{RRM} and $0.25 \bullet I_{RRM}$ passes through zero.
5. Q_{rr} - Area Under the Curve Defined by I_{RRM} and t_{rr}.



Figure 10, Diode Reverse Recovery Waveform and Definitions

SOT-227 (ISOTOP®) Package Outline



Dimensions in Millimeters and (Inches)

ISOTOP® is a registered trademark of ST Microelectronics NV

DISCLAIMER

The information contained in the document (unless it is publicly available on the Web without access restrictions) is PROPRIETARY AND CONFIDENTIAL information of Microsemi and cannot be copied, published, uploaded, posted, transmitted, distributed or disclosed or used without the express duly signed written consent of Microsemi. If the recipient of this document has entered into a disclosure agreement with Microsemi, then the terms of such Agreement will also apply. This document and the information contained herein may not be modified, by any person other than authorized personnel of Microsemi. No license under any patent, copyright, trade secret or other intellectual property right is granted to or conferred upon you by disclosure or delivery of the information, either expressly, by implication, inducement, estoppels or otherwise. Any license under such intellectual property rights must be approved by Microsemi in writing signed by an officer of Microsemi.

Microsemi reserves the right to change the configuration, functionality and performance of its products at anytime without any notice. This product has been subject to limited testing and should not be used in conjunction with life-support or other mission-critical equipment or applications. Microsemi assumes no liability whatsoever, and Microsemi disclaims any express or implied warranty, relating to sale and/or use of Microsemi products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright or other intellectual property right. Any performance specifications believed to be reliable but are not verified and customer or user must conduct and complete all performance and other testing of this product as well as any user or customers final application. User or customer shall not rely on any data and performance specifications or parameters provided by Microsemi. It is the customer's and user's responsibility to independently determine suitability of any Microsemi product and to test and verify the same. The information contained herein is provided "AS IS, WHERE IS" and with all faults, and the entire risk associated with such information is entirely with the User. Microsemi specifically disclaims any liability of any kind including for consequential, incidental and punitive damages as well as lost profit. The product is subject to other terms and conditions which can be located on the web at http://www.microsemi.com/legal/tnc.asp

Life Support Application

Seller's Products are not designed, intended, or authorized for use as components in systems intended for space, aviation, surgical implant into the body, in other applications intended to support or sustain life, or for any other application in which the failure of the Seller's Product could create a situation where personal injury, death or property damage or loss may occur (collectively "Life Support Applications").
Buyer agrees not to use Products in any Life Support Applications and to the extent it does it shall conduct extensive testing of the Product in such applications and further agrees to indemnify and hold Seller, and its officers, employees, subsidiaries, affiliates, agents, sales representatives and distributors harmless against all claims, costs, damages and expenses, and attorneys' fees and costs arising, directly or directly, out of any claims of personal injury, death, damage or otherwise associated with the use of the goods in Life Support Applications, even if such claim includes allegations that Seller was negligent regarding the design or manufacture of the goods.

Buyer must notify Seller in writing before using Seller's Products in Life Support Applications. Seller will study with Buyer alternative solutions to meet Buyer application specification based on Sellers sales conditions applicable for the new proposed specific part.

ENTEGRECİ

Bu belge www.entegreci.com üzerinden sunulmaktadır.

Elektronik komponent tedarikinde Entegreci

Entegreci, Eskişehir merkezli, Türkiye geneline satış yapan bir elektronik komponent mağazasıdır. Entegreler (IC), mikrodenetleyiciler, transistörler, diyotlar, pasif elemanlar, konnektörler, modüller ve geliştirme kartları tek adetten seri üretim adetlerine kadar satılır. Ürün sayfalarında güncel stok durumunu, fiyatı ve datasheet bağlantısını bulabilirsiniz.

Parça koduyla arama

Üretici parça numarasını yazın; stok ve fiyatı hemen görün.

www.entegreci.com

Ürün kategorileri

Entegreden kapasitöre tüm elektronik komponent kategorileri.

Kategorilere göz atın

Üreticiler

Aradığınız üreticinin ürünlerini tek sayfada inceleyin.

Üreticileri görün

Toplu alım ve teklif

Listede olmayan ya da yüksek adetli parçalar için teklif isteyin.

Teklif isteyin

www.entegreci.com | **destek@entegreci.com** | **0850 305 90 34**

Entegreci is an online electronic components store based in Türkiye. Search by manufacturer part number to see stock, prices and datasheets for integrated circuits, microcontrollers, transistors, passive components and connectors, or request a quote for parts that are not listed.

Bu sayfa Entegreci tarafından eklenmiştir. Belgenin önceki sayfaları asıl yayıncısına aittir ve içeriği değiştirilmemiştir; en güncel sürüm için belgenin yayıncısına başvurun.