CWDM305N

SURFACE MOUNT SILICON N-CHANNEL ENHANCEMENT-MODE MOSFET



SOIC-8 CASE

www.centralsemi.com

DESCRIPTION:

The CENTRAL SEMICONDUCTOR CWDM305N is a high current N-channel enhancement-mode silicon MOSFET designed for high speed pulsed amplifier and driver applications. This energy efficient MOSFET offers beneficially low $r_{DS(ON)}$, low gate charge, and low threshold voltage.

MARKING CODE: C305N

APPLICATIONS:

- Load/Power switches
- DC-DC converter circuits
- Power management

FEATURES:

- Low $r_{DS(ON)}$
- High current
- Low gate charge

MAXIMUM RATINGS: (T_A=25°C)	**SYMBOL**		**UNITS**
Drain-Source Voltage	V_{DS}	30	V
Gate-Source Voltage	V_{GS}	20	V
Continuous Drain Current (Steady State)	I_D	5.8	A
Maximum Pulsed Drain Current, tp=10μs	I_{DM}	23.2	A
Power Dissipation	P_D	2.0	W
Operating and Storage Junction Temperature	T_J, T_{stg}	-55 to +150	°C
Thermal Resistance	Θ_{JA}	62.5	°C/W

ELECTRICAL CHARACTERISTICS: (T_A=25°C unless otherwise noted)

SYMBOL	**TEST CONDITIONS**	**MIN**	**TYP**	**MAX**	**UNITS**
I_{GSSF}, I_{GSSR}	V_{GS}=20V, V_{DS}=0			100	nA
I_{DSS}	V_{DS}=30V, V_{GS}=0			1.0	μA
BV_{DSS}	V_{GS}=0, I_D=250μA	30			V
$V_{GS(th)}$	V_{GS}=V_{DS}, I_D=250μA	1.0		3.0	V
$r_{DS(ON)}$	V_{GS}=10V, I_D=2.9A		0.024	0.030	Ω
$r_{DS(ON)}$	V_{GS}=5.0V, I_D=2.9A		0.028		Ω
g_{FS}	V_{DS}=5.0V, I_D=5.8A		12		S
C_{rss}	V_{DS}=10V, V_{GS}=0, f=1.0MHz		50	58	pF
C_{iss}	V_{DS}=10V, V_{GS}=0, f=1.0MHz		500	560	pF
C_{oss}	V_{DS}=10V, V_{GS}=0, f=1.0MHz		52	90	pF
$Q_{g(tot)}$	V_{DD}=15V, V_{GS}=5.0V, I_D=5.8A		4.2	6.3	nC
Q_{gs}	V_{DD}=15V, V_{GS}=5.0V, I_D=5.8A		0.9	1.4	nC
Q_{gd}	V_{DD}=15V, V_{GS}=5.0V, I_D=5.8A		1.4	2.1	nC
t_{on}	V_{DD}=15V, I_D=5.8A, R_G=10Ω		6.5		ns
t_{off}	V_{DD}=15V, I_D=5.8A, R_G=10Ω		8.5		ns

R4 (26-April 2021)

CWDM305N

SURFACE MOUNT SILICON
N-CHANNEL
ENHANCEMENT-MODE
MOSFET

SOIC-8 CASE - MECHANICAL OUTLINE



DIMENSIONS				
	INCHES		MILLIMETERS	
SYMBOL	MIN	MAX	MIN	MAX
A	0.055	0.061	1.392	1.554
B	0.004	0.009	0.100	0.224
C	0.016	0.035	0.40	0.90
D	0.007	0.010	0.19	0.25
E	0.145	0.157	3.80	4.00
F	0.189	0.198	4.80	5.00
G	0.150		3.81	
H	0.228	0.244	5.80	6.20
J	0.013	0.020	0.33	0.51
K	0.050		1.27	

SOIC-8 (REV: R1)

PIN CONFIGURATION



LEAD CODE:

1) Source
2) Source
3) Source
4) Gate
5) Drain
6) Drain
7) Drain
8) Drain

MARKING CODE: C305N

SUGGESTED MOUNTING PADS

(Dimensions in mm)



R0

R4 (26-April 2021)

CWDM305N

SURFACE MOUNT SILICON N-CHANNEL ENHANCEMENT-MODE MOSFET

TYPICAL ELECTRICAL CHARACTERISTICS

Typical Output Characteristics



Drain Source On Resistance



Capacitance



Transfer Characteristics



Power Derating



R4 (26-April 2021)

OUTSTANDING SUPPORT AND SUPERIOR SERVICES

PRODUCT SUPPORT

Central's operations team provides the highest level of support to insure product is delivered on-time.

- Supply management (Customer portals)
- Inventory bonding
- Consolidated shipping options
- Custom bar coding for shipments
- Custom product packing

DESIGNER SUPPORT/SERVICES

Central's applications engineering team is ready to discuss your design challenges. Just ask.

- Free quick ship samples (2nd day air)
- Online technical data and parametric search
- SPICE models
- Custom electrical curves
- Environmental regulation compliance
- Customer specific screening
- Up-screening capabilities
- Special wafer diffusions
- PbSn plating options
- Package details
- Application notes
- Application and design sample kits
- Custom product and package development

REQUESTING PRODUCT PLATING

1. If requesting Tin/Lead plated devices, add the suffix " TIN/LEAD" to the part number when ordering (example: 2N2222A TIN/LEAD).
2. If requesting Lead (Pb) Free plated devices, add the suffix " PBFREE" to the part number when ordering (example: 2N2222A PBFREE).

CONTACT US

Corporate Headquarters & Customer Support Team

Central Semiconductor Corp.
145 Adams Avenue
Hauppauge, NY 11788 USA
Main Tel: (631) 435-1110
Main Fax: (631) 435-1824
Support Team Fax: (631) 435-3388
www.centralsemi.com

Worldwide Field Representatives:
www.centralsemi.com/wwreps

Worldwide Distributors:
www.centralsemi.com/wwdistributors

For the latest version of Central Semiconductor's **LIMITATIONS AND DAMAGES DISCLAIMER**, which is part of Central's Standard Terms and Conditions of sale, visit: www.centralsemi.com/terms

ENTEGRECİ

Bu belge www.entegreci.com üzerinden sunulmaktadır.

Elektronik komponent tedarikinde Entegreci

Entegreci, Eskişehir merkezli, Türkiye geneline satış yapan bir elektronik komponent mağazasıdır. Entegreler (IC), mikrodenetleyiciler, transistörler, diyotlar, pasif elemanlar, konnektörler, modüller ve geliştirme kartları tek adetten seri üretim adetlerine kadar satılır. Ürün sayfalarında güncel stok durumunu, fiyatı ve datasheet bağlantısını bulabilirsiniz.

Parça koduyla arama

Üretici parça numarasını yazın; stok ve fiyatı hemen görün.

www.entegreci.com

Ürün kategorileri

Entegreden kapasitöre tüm elektronik komponent kategorileri.

Kategorilere göz atın

Üreticiler

Aradığınız üreticinin ürünlerini tek sayfada inceleyin.

Üreticileri görün

Toplu alım ve teklif

Listede olmayan ya da yüksek adetli parçalar için teklif isteyin.

Teklif isteyin

www.entegreci.com | **destek@entegreci.com** | **0850 305 90 34**

Entegreci is an online electronic components store based in Türkiye. Search by manufacturer part number to see stock, prices and datasheets for integrated circuits, microcontrollers, transistors, passive components and connectors, or request a quote for parts that are not listed.

Bu sayfa Entegreci tarafından eklenmiştir. Belgenin önceki sayfaları asıl yayıncısına aittir ve içeriği değiştirilmemiştir; en güncel sürüm için belgenin yayıncısına başvurun.