Ordering number : ENA1418B

ECH8309

P-Channel Power MOSFET
−12V, −9.5A, 16mΩ, Single ECH8

ON Semiconductor®
http://onsemi.com

Features

- 1.8V drive
- Halogen free compliance
- Protection diode in

Specifications


Absolute Maximum Ratings at Ta=25°C

Parameter	Symbol	Conditions	Ratings	Unit
Drain-to-Source Voltage	V_{DSS}		−12	V
Gate-to-Source Voltage	V_{GSS}		±10	V
Drain Current (DC)	I_D		−9.5	A
Drain Current (Pulse)	I_{DP}	PW≤10μs, duty cycle≤1%	−40	A
Allowable Power Dissipation	P_D	When mounted on ceramic substrate (900mm²×0.8mm)	1.5	W
Channel Temperature	Tch		150	°C
Storage Temperature	Tstg		−55 to +150	°C

Stresses exceeding Maximum Ratings may damage the device. Maximum Ratings are stress ratings only. Functional operation above the Recommended Operating Conditions is not implied. Extended exposure to stresses above the Recommended Operating Conditions may affect device reliability.

Package Dimensions


unit : mm (typ)
7011A-002




Product & Package Information

- Package : ECH8
- JEITA, JEDEC : -
- Minimum Packing Quantity : 3,000 pcs./reel


Packing Type : TL



Marking



Electrical Connection




Semiconductor Components Industries, LLC, 2013

Electrical Characteristics at Ta=25°C


Parameter	Symbol	Conditions	Ratings			Unit
			min	typ	max	
Drain-to-Source Breakdown Voltage	$V_{(BR)DSS}$	I_D=−1mA, V_{GS}=0V	−12			V
Zero-Gate Voltage Drain Current	I_{DSS}	V_{DS}=−12V, V_{GS}=0V			−10	μA
Gate-to-Source Leakage Current	I_{GSS}	V_{GS}=±8V, V_{DS}=0V			±10	μA
Cutoff Voltage	V_{GS}(off)	V_{DS}=−6V, I_D=−1mA	−0.4		−1.3	V
Forward Transfer Admittance	| yfs |	V_{DS}=−6V, I_D=−4.5A	9.6	16		S
Static Drain-to-Source On-State Resistance	R_{DS}(on)1	I_D=−4.5A, V_{GS}=−4.5V		12	16	mΩ
	R_{DS}(on)2	I_D=−2A, V_{GS}=−2.5V		18	26	mΩ
	R_{DS}(on)3	I_D=−1A, V_{GS}=−1.8V		30	53	mΩ
Input Capacitance	Ciss	V_{DS}=−6V, f=1MHz		1780		pF
Output Capacitance	Coss			540		pF
Reverse Transfer Capacitance	Crss			390		pF
Turn-ON Delay Time	t_{d}(on)	See specified Test Circuit.		22		ns
Rise Time	t_r			110		ns
Turn-OFF Delay Time	t_{d}(off)			157		ns
Fall Time	t_f			123		ns
Total Gate Charge	Qg	V_{DS}=−6V, V_{GS}=−4.5V, I_D=−9.5A		18		nC
Gate-to-Source Charge	Qgs			2.8		nC
Gate-to-Drain “Miller” Charge	Qgd			4.9		nC
Diode Forward Voltage	V_{SD}	I_S=−9.5A, V_{GS}=0V		−0.8	−1.2	V


Switching Time Test Circuit





Ordering Information


Device	Package	Shipping	memo
ECH8309-TL-H	ECH8	3,000pcs./reel	Pb Free and Halogen Free



ID -- VDS
Drain Current, ID – A
Drain-to-Source Voltage, VDS – V
IT13985
–6.0V
–8.0V
–4.5V
–2.5V
–1.8V
–1.5V
VGS= –1.2V



ID -- VGS
Drain Current, ID – A
Gate-to-Source Voltage, VGS – V
IT13986
VDS= –6V
Ta=75°C
25°C
–25°C



RDS(on) -- VGS
Static Drain-to-Source On-State Resistance, RDS(on) – mΩ
Gate-to-Source Voltage, VGS – V
IT14418
Ta=25°C
ID= –1.0A
–2.0A
–4.5A



RDS(on) -- Ta
Static Drain-to-Source On-State Resistance, RDS(on) – mΩ
Ambient Temperature, Ta – °C
IT14419
VGS= –1.8V, ID= –1.0A
VGS= –2.5V, ID= –2.0A
VGS= –4.5V, ID= –4.5A



| yfs | -- ID
Forward Transfer Admittance, | yfs | – S
Drain Current, ID – A
IT13989
VDS= –6V
25°C
Ta= –25°C
75°C



IS -- VSD
Source Current, IS – A
Diode Forward Voltage, VSD – V
IT13990
VGS=0V
Ta=75°C
25°C
–25°C


SW Time -- ID
Switching Time, SW Time – ns
Drain Current, ID – A
IT13991
VDD= –6V
VGS= –4.5V
td(off)
tf
tr
td(on)


Ciss, Coss, Crss -- VDS
Ciss, Coss, Crss – pF
Drain-to-Source Voltage, VDS – V
IT13992
f=1MHz
Ciss
Coss
Crss


VGS -- Qg
VDS= −6V
ID= −9.5A
Gate-to-Source Voltage, VGS – V
Total Gate Charge, Qg – nC
IT14420


A S O
IDP= −40A
PW≤10μs
ID= −9.5A
1ms
10ms
100ms
DC operation (Ta=25°C)
Operation in this area
is limited by RDS(on).
Ta=25°C
Single pulse
When mounted on ceramic substrate (900mm2×0.8mm)
Drain Current, ID – A
Drain-to-Source Voltage, VDS – V
IT14421


PD -- Ta
When mounted on ceramic substrate
(900mm2×0.8mm)
Allowable Power Dissipation, PD – W
Ambient Temperature, Ta – °C
IT14422


Embossed Taping Specification

ECH8309-TL-H

1. Packing Format

Package Name	Carrier Tape Type	Maximum Number of devices contained (pcs)			Packing format	
		Reel	Inner box	Outer box	Inner BOX (C-1)	Outer BOX (A-7)
ECH8	CPH6	3,000	15,000	90,000	5 reels contained Dimensions:mm(external) 183×72×185	6 inner boxes contained Dimensions:mm(external) 440×195×210


Packing method



Reel label


Reel label, Inner box label

(unit:mm)



Outer box label

It is a label at the time of factory shipments. The form of a label may change in physical distribution process.




NOTE (1)

The LEAD FREE ※ description shows that the surface treatment of the terminal is lead free.


Label	JEITA Phase
LEAD FREE 3	JEITA Phase 3A
LEAD FREE 4	JEITA Phase 3

2. Taping configuration

2-1. Carrier tape size (unit:mm)




2-2. Device placement direction




Those with pin 1 index on the feed hole side·····TL

Outline Drawing

ECH8309-TL-H



Land Pattern Example



Note on usage : Since the ECH8309 is a MOSFET product, please avoid using this device in the vicinity of highly charged objects.

ON Semiconductor and the ON logo are registered trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of SCILLC's product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent-Marking.pdf. SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

ENTEGRECİ

Bu belge www.entegreci.com üzerinden sunulmaktadır.

Elektronik komponent tedarikinde Entegreci

Entegreci, Eskişehir merkezli, Türkiye geneline satış yapan bir elektronik komponent mağazasıdır. Entegreler (IC), mikrodenetleyiciler, transistörler, diyotlar, pasif elemanlar, konnektörler, modüller ve geliştirme kartları tek adetten seri üretim adetlerine kadar satılır. Ürün sayfalarında güncel stok durumunu, fiyatı ve datasheet bağlantısını bulabilirsiniz.

Parça koduyla arama

Üretici parça numarasını yazın; stok ve fiyatı hemen görün.

www.entegreci.com

Ürün kategorileri

Entegreden kapasitöre tüm elektronik komponent kategorileri.

Kategorilere göz atın

Üreticiler

Aradığınız üreticinin ürünlerini tek sayfada inceleyin.

Üreticileri görün

Toplu alım ve teklif

Listede olmayan ya da yüksek adetli parçalar için teklif isteyin.

Teklif isteyin

www.entegreci.com | **destek@entegreci.com** | **0850 305 90 34**

Entegreci is an online electronic components store based in Türkiye. Search by manufacturer part number to see stock, prices and datasheets for integrated circuits, microcontrollers, transistors, passive components and connectors, or request a quote for parts that are not listed.

Bu sayfa Entegreci tarafından eklenmiştir. Belgenin önceki sayfaları asıl yayıncısına aittir ve içeriği değiştirilmemiştir; en güncel sürüm için belgenin yayıncısına başvurun.