
EPC2035 – Enhancement Mode Power Transistor

V_{DS}, 60 V
$R_{DS(on)}$, 45 mΩ
I_D, 1.7 A



EFFICIENT POWER CONVERSION

RoHS Halogen-Free

Revised April 22, 2021

Gallium Nitride's exceptionally high electron mobility and low temperature coefficient allows very low $R_{DS(on)}$, while its lateral device structure and majority carrier diode provide exceptionally low Q_G and zero Q_{RR}. The end result is a device that can handle tasks where very high switching frequency, and low on-time are beneficial as well as those where on-state losses dominate.

Questions: Ask a GaN Expert


Maximum Ratings			
PARAMETER		**VALUE**	**UNIT**
V_{DS}	Drain-to-Source Voltage (Continuous)	60	V
	Drain-to-Source Voltage (up to 10,000 5 ms pulses at 125°C)	72	
I_D	Continuous (T_A = 25°C, $R_{\theta JA}$ = 546°C/W)	1.7	A
	Pulsed (25°C, T_{PULSE} = 300 µs)	24	
V_{GS}	Gate-to-Source Voltage	6	V
	Gate-to-Source Voltage	–4	
T_J	Operating Temperature	–40 to 150	°C
T_{STG}	Storage Temperature	–40 to 150	

Thermal Characteristics			
PARAMETER		**TYP**	**UNIT**
$R_{\theta JC}$	Thermal Resistance, Junction-to-Case	6.5	°C/W
$R_{\theta JB}$	Thermal Resistance, Junction-to-Board	65	
$R_{\theta JA}$	Thermal Resistance, Junction-to-Ambient (Note 1)	100	

Note 1: $R_{\theta JA}$ is determined with the device mounted on one square inch of copper pad, single layer 2 oz copper on FR4 board.
See https://epc-co.com/epc/documents/product-training/Appnote_Thermal_Performance_of_eGaN_FETs.pdf for details

Static Characteristics (T_J = 25°C unless otherwise stated)						
PARAMETER		**TEST CONDITIONS**	**MIN**	**TYP**	**MAX**	**UNIT**
BV_{DSS}	Drain-to-Source Voltage	V_{GS} = 0 V, I_D = 300 µA	60			V
I_{DSS}	Drain-Source Leakage	V_{GS} = 0 V, V_{DS} = 48 V		20	250	µA
I_{GSS}	Gate-to-Source Forward Leakage	V_{GS} = 5 V		0.1	1	mA
	Gate-to-Source Reverse Leakage	V_{GS} = -4 V		20	250	µA
$V_{GS(TH)}$	Gate Threshold Voltage	V_{DS} = V_{GS}, I_D = 0.8 mA	0.8	1.4	2.5	V
$R_{DS(on)}$	Drain-Source On Resistance	V_{GS} = 5 V, I_D = 1 A		35	45	mΩ
V_{SD}	Source-Drain Forward Voltage#	V_{GS} = 0 V, I_S = 0.5 A		2		V

Defined by design. Not subject to production test.
All measurements were done with substrate connected to source.



Die size: 0.9 x 0.9 mm

EPC2035 eGaN® FETs are supplied only in passivated die form with solder bumps.

Applications

- High speed DC-DC conversion
- Wireless power transfer
- High frequency hard-switching and soft-switching circuits
- Lidar/pulsed power applications

Benefits

- Ultra high efficiency
- Ultra low $R_{DS(on)}$
- Ultra low Q_G
- Ultra small footprint

Scan QR code or click link below for more information including reliability reports, device models, demo boards!

https://l.ead.me/EPC2035

Dynamic Characteristics# (T_J = 25°C unless otherwise stated)						
PARAMETER		TEST CONDITIONS	MIN	TYP	MAX	UNIT
C_{ISS}	Input Capacitance	V_{GS} = 0 V, V_{DS} = 30 V		95	115	pF
C_{RSS}	Reverse Transfer Capacitance			2	3	
C_{OSS}	Output Capacitance			60	90	
R_G	Gate Resistance			0.5		Ω
Q_G	Total Gate Charge	V_{GS} = 5 V, V_{DS} = 30 V, I_D = 1A		880	1150	pC
Q_{GS}	Gate-to-Source Charge	V_{DS} = 30 V, I_D = 1 A		250		
Q_{GD}	Gate-to-Drain Charge			160	270	
$Q_{G(TH)}$	Gate Charge at Threshold			170		
Q_{OSS}	Output Charge	V_{GS} = 0 V, V_{DS} = 30 V		2600	3900	
Q_{RR}	Source-Drain Recovery Charge			0		

Defined by design. Not subject to production test.
All measurements were done with substrate connected to source.
Note 2: $C_{OSS(ER)}$ is a fixed capacitance that gives the same stored energy as C_{OSS} while V_{DS} is rising from 0 to 50% BV_{DSS}.
Note 3: $C_{OSS(TR)}$ is a fixed capacitance that gives the same charging time as C_{OSS} while V_{DS} is rising from 0 to 50% BV_{DSS}.

Figure 1: Typical Output Characteristics 25°C




Figure 2: Typical Transfer Characteristics




Figure 3: Typical $R_{DS(on)}$ vs. V_{GS} for Various Drain Currents




Figure 4: Typical $R_{DS(on)}$ vs. V_{GS} for Various Temperatures




Figure 5a: Typical Capacitance (Linear Scale)




Figure 5b: Typical Capacitance (Log Scale)




Figure 6: Typical Gate Charge





Figure 7: Typical Reverse Drain-Source Characteristics



Note: Negative gate drive voltage increases the reverse drain-source voltage. EPC recommends 0 V for OFF.

Figure 8: Typical Normalized On Resistance vs. Temperature




Figure 9: Typical Normalized Threshold Voltage vs. Temp.




Figure 10: Typical Gate Leakage Current





Figure 11: Typical Transient Thermal Response Curves








Figure 12: Safe Operating Area



T_J = Max Rated, T_C = +25°C, Single Pulse

TAPE AND REEL CONFIGURATION


4mm pitch, 8mm wide tape on 7″ reel



	EPC2035 (note 1)		
Dimension (mm)	target	min	max
a	8.00	7.90	8.30
b	1.75	1.65	1.85
c (see note)	3.50	3.45	3.55
d	4.00	3.90	4.10
e	4.00	3.90	4.10
f (see note)	2.00	1.95	2.05
g	1.5	1.5	1.6

Note 1: MSL 1 (moisture sensitivity level 1) classified according to IPC/JEDEC industry standard.
Note 2: Pocket position is relative to the sprocket hole measured as true position of the pocket, not the pocket hole.


DIE MARKINGS




Part Number	Laser Markings	
	Part # Marking Line 1	Lot_Date Code Marking line 2
EPC2035	AA	YYY

DIE OUTLINE

Solder Bump View




Side View



DIM	Micrometers		
	MIN	Nominal	MAX
A	870	900	930
B	870	900	930
c	450	450	450
d	450	450	450
e	210	225	240
f	210	225	240
g	187	208	229

RECOMMENDED LAND PATTERN

(measurements in µm)



* minimum 190

The land pattern is solder mask defined.


Pads 1 is Gate;

Pad 3 is Drain;

Pads 2, 4 are Source

RECOMMENDED STENCIL DRAWING

(measurements in µm)



Recommended stencil should be 4mil (100 µm) thick, must be laser cut, openings per drawing.

Intended for use with SAC305 Type 4 solder, reference 88.5% metals content.

Additional assembly resources available at https://epc-co.com/epc/design-support

Efficient Power Conversion Corporation (EPC) reserves the right to make changes without further notice to any products herein to improve reliability, function or design. EPC does not assume any liability arising out of the application or use of any product or circuit described herein; neither does it convey any license under its patent rights, nor the rights of others.

eGaN® is a registered trademark of Efficient Power Conversion Corporation.

EPC Patent Listing: https://epc-co.com/epc/about-epc/patents

Information subject to change without notice.

ENTEGRECİ

Bu belge www.entegreci.com üzerinden sunulmaktadır.

Elektronik komponent tedarikinde Entegreci

Entegreci, Eskişehir merkezli, Türkiye geneline satış yapan bir elektronik komponent mağazasıdır. Entegreler (IC), mikrodenetleyiciler, transistörler, diyotlar, pasif elemanlar, konnektörler, modüller ve geliştirme kartları tek adetten seri üretim adetlerine kadar satılır. Ürün sayfalarında güncel stok durumunu, fiyatı ve datasheet bağlantısını bulabilirsiniz.

Parça koduyla arama

Üretici parça numarasını yazın; stok ve fiyatı hemen görün.

www.entegreci.com

Ürün kategorileri

Entegreden kapasitöre tüm elektronik komponent kategorileri.

Kategorilere göz atın

Üreticiler

Aradığınız üreticinin ürünlerini tek sayfada inceleyin.

Üreticileri görün

Toplu alım ve teklif

Listede olmayan ya da yüksek adetli parçalar için teklif isteyin.

Teklif isteyin

www.entegreci.com | **destek@entegreci.com** | **0850 305 90 34**

Entegreci is an online electronic components store based in Türkiye. Search by manufacturer part number to see stock, prices and datasheets for integrated circuits, microcontrollers, transistors, passive components and connectors, or request a quote for parts that are not listed.

Bu sayfa Entegreci tarafından eklenmiştir. Belgenin önceki sayfaları asıl yayıncısına aittir ve içeriği değiştirilmemiştir; en güncel sürüm için belgenin yayıncısına başvurun.