EPC2070 – Enhancement Mode Power Transistor

V_{DS} , 100 V
Max $R_{DS(on)}$, 23 mΩ
I_D , 1.7 A



EFFICIENT POWER CONVERSION

RoHS Halogen-Free

Revised July 28, 2022

Gallium Nitride's exceptionally high electron mobility and low temperature coefficient allows very low $R_{DS(on)}$, while its lateral device structure and majority carrier diode provide exceptionally low Q_G and zero Q_{RR}. The end result is a device that can handle tasks where very high switching frequency, and low on-time are beneficial as well as those where on-state losses dominate.

Questions: Ask a GaN Expert

Maximum Ratings			
PARAMETER		VALUE	UNIT
V_{DS}	Drain-to-Source Voltage (Continuous)	100	V
	Drain-to-Source Voltage (up to 10,000 5 ms pulses at 150°C)	120	
I_D	Continuous (T_A = 25°C)	1.7	A
	Pulsed (25°C, T_{PULSE} = 300 µs)	34	
V_{GS}	Gate-to-Source Voltage	6	V
	Gate-to-Source Voltage	-4	
T_J	Operating Temperature	-40 to 150	°C
T_{STG}	Storage Temperature	-40 to 150	

Thermal Characteristics			
PARAMETER		TYP	UNIT
$R_{\theta JC}$	Thermal Resistance, Junction-to-Case	3.4	°C/W
$R_{\theta JB}$	Thermal Resistance, Junction-to-Board	16	
$R_{\theta JA}$	Thermal Resistance, Junction-to-Ambient (Note 1)	92	

Note 1: $R_{\theta JA}$ is determined with the device mounted on one square inch of copper pad, single layer 2 oz copper on FR4 board.
See https://epc-co.com/epc/documents/product-training/Appnote_Thermal_Performance_of_eGaN_FETs.pdf for details.

Static Characteristics (T_J = 25°C unless otherwise stated)						
PARAMETER		TEST CONDITIONS	MIN	TYP	MAX	UNIT
BV_{DSS}	Drain-to-Source Voltage	V_{GS} = 0 V, I_D = 0.11 mA	100			V
I_{DSS}	Drain-Source Leakage	V_{GS} = 0 V, V_{DS} = 80 V		0.0001	0.1	mA
I_{GSS}	Gate-to-Source Forward Leakage	V_{GS} = 5 V		0.004	0.5	
	Gate-to-Source Forward Leakage#	V_{GS} = 5 V, T_J = 125°C		0.1	1	
	Gate-to-Source Reverse Leakage	V_{GS} = -4 V		0.001	0.1	
$V_{GS(TH)}$	Gate Threshold Voltage	V_{DS} = V_{GS}, I_D = 1.5 mA	0.8	1.3	2.5	V
$R_{DS(on)}$	Drain-Source On Resistance	V_{GS} = 5 V, I_D = 3 A		18	23	mΩ
V_{SD}	Source-Drain Forward Voltage#	I_S = 0.5 A, V_{GS} = 0 V		1.6		V

Defined by design. Not subject to production test.



Die Size: 1.3 x 0.85 mm

EPC2070 eGaN® FETs are supplied in passivated die form with copper pillars.

Applications

- High frequency DC-DC from 48 V–60 V input
- ToF module using Vcsel laser for camera modules, laptops and smart phones
- Open rack server architectures
- Lidar/pulsed power applications
- Power supplies
- Class D audio
- LED lighting
- Low inductance motor drive

Benefits

- Ultra high efficiency
- No reverse recovery
- Ultra low Q_G
- Ultra small footprint

Scan QR code or click link below for more information including reliability reports, device models, demo boards!

https://l.ead.me/EPC2070

Dynamic Characteristics# (T_J = 25°C unless otherwise stated)						
PARAMETER		TEST CONDITIONS	MIN	TYP	MAX	UNIT
C_{ISS}	Input Capacitance	V_{DS} = 50 V , V_{GS} = 0 V		257	386	pF
C_{RSS}	Reverse Transfer Capacitance			0.5		
C_{OSS}	Output Capacitance			82	123	
$C_{OSS(ER)}$	Effective Output Capacitance, Energy Related (Note 2)	V_{DS} = 0 to 50 V, V_{GS} = 0 V		105		
$C_{OSS(TR)}$	Effective Output Capacitance, Time Related (Note 3)			139		
R_G	Gate Resistance			1		Ω
Q_G	Total Gate Charge	V_{DS} = 50 V, V_{GS} = 5 V, I_D = 3 A		1.9	2.5	nC
Q_{GS}	Gate to Source Charge	V_{DS} = 50 V, I_D = 3 A		0.6		
Q_{GD}	Gate to Drain Charge			0.2		
$Q_{G(TH)}$	Gate Charge at Threshold			0.5		
Q_{OSS}	Output Charge	V_{GS} = 0 V, V_{DS} = 50 V		6	9	
Q_{RR}	Source-Drain Recovery Charge			0		

Defined by design. Not subject to production test.
All measurements were done with substrate connected to source.
Note 2: $C_{OSS(ER)}$ is a fixed capacitance that gives the same stored energy as C_{OSS} while V_{DS} is rising from 0 to 50% BV_{DSS}.
Note 3: $C_{OSS(TR)}$ is a fixed capacitance that gives the same charging time as C_{OSS} while V_{DS} is rising from 0 to 50% BV_{DSS}.

Figure 1: Typical Output Characteristics at 25°C



Figure 2: Typical Transfer Characteristics



Figure 3: Typical $R_{DS(on)}$ vs. V_{GS} for Various Currents



Figure 4: Typical $R_{DS(on)}$ vs. V_{GS} for Various Temperatures



Figure 5a: Typical Capacitance (Linear Scale)



Figure 5b: Typical Capacitance (Log Scale)



Figure 6: Typical Output Charge and C_{OSS} Stored Energy



Figure 7: Typical Gate Charge



Figure 8: Typical Reverse Drain-Source Characteristics



Figure 9: Typical Normalized On-State Resistance vs. Temp.



Note: Negative gate drive voltage increases the reverse drain-source voltage. EPC recommends 0 V for OFF.

Figure 10: Typical Normalized Threshold Voltage vs. Temp.



Figure 11: Typical Transient Thermal Response Curves





Figure 12: Safe Operating Area



TAPE AND REEL CONFIGURATION

4mm pitch, 8mm wide tape on 7" reel



	Dimension (mm)		
EPC2070 (Note 1)	Target	MIN	MAX
a	8.00	7.90	8.30
b	1.75	1.65	1.85
c (Note 2)	3.50	3.45	3.55
d	4.00	3.90	4.10
e	4.00	3.90	4.10
f (Note 2)	2.00	1.95	2.05
g	1.50	1.50	1.60

Note 1: MSL 1 (moisture sensitivity level 1) classified according to IPC/JEDEC industry standard.

Note 2: Pocket position is relative to the sprocket hole measured as true position of the pocket, not the pocket hole.

DIE MARKINGS



Part Number	Laser Markings		
	Part # Marking Line 1	Lot_Date Code Marking Line 2	Lot_Date Code Marking Line 3
EPC2070	2070	XXXX	YYYY

DIE OUTLINE

Solder Bar View
(looking at the Cu pillars)



DIM	MICROMETERS		
	MIN	Nominal	MAX
A	1270	1300	1330
B	820	850	880
c		450	
d		150	
e	185	200	215
f	185	200	215

Side View



Pad 1 is Gate;
Pads 2, 5, 6 are Source;
Pads 3 & 4 are Drain

RECOMMENDED LAND PATTERN

(units in µm)



Pad 1 is Gate;
Pads 2, 5, 6 are Source;
Pads 3 & 4 are Drain

RECOMMENDED STENCIL DRAWING

(measurements in µm)



Preliminary Solder Flux Recommendation:
EPC uses Kester NP505-HR Type 4 Solder Paste. This solder uses ROL0 type flux. It is intended that the solder completely wets the sides of the Cu Pilar. This is different from traditional Cu Pillar assembly techniques.

Additional assembly resources available at
https://epc-co.com/epc/design-support

Efficient Power Conversion Corporation (EPC) reserves the right to make changes without further notice to any products herein to improve reliability, function or design. EPC does not assume any liability arising out of the application or use of any product or circuit described herein; neither does it convey any license under its patent rights, nor the rights of others.

eGaN® is a registered trademark of Efficient Power Conversion Corporation.
EPC Patent Listing: https://epc-co.com/epc/about-epc/patents

Information subject to change without notice.

ENTEGRECİ

Bu belge www.entegreci.com üzerinden sunulmaktadır.

Elektronik komponent tedarikinde Entegreci

Entegreci, Eskişehir merkezli, Türkiye geneline satış yapan bir elektronik komponent mağazasıdır. Entegreler (IC), mikrodenetleyiciler, transistörler, diyotlar, pasif elemanlar, konnektörler, modüller ve geliştirme kartları tek adetten seri üretim adetlerine kadar satılır. Ürün sayfalarında güncel stok durumunu, fiyatı ve datasheet bağlantısını bulabilirsiniz.

Parça koduyla arama

Üretici parça numarasını yazın; stok ve fiyatı hemen görün.

www.entegreci.com

Ürün kategorileri

Entegreden kapasitöre tüm elektronik komponent kategorileri.

Kategorilere göz atın

Üreticiler

Aradığınız üreticinin ürünlerini tek sayfada inceleyin.

Üreticileri görün

Toplu alım ve teklif

Listede olmayan ya da yüksek adetli parçalar için teklif isteyin.

Teklif isteyin

www.entegreci.com | **destek@entegreci.com** | **0850 305 90 34**

Entegreci is an online electronic components store based in Türkiye. Search by manufacturer part number to see stock, prices and datasheets for integrated circuits, microcontrollers, transistors, passive components and connectors, or request a quote for parts that are not listed.

Bu sayfa Entegreci tarafından eklenmiştir. Belgenin önceki sayfaları asıl yayıncısına aittir ve içeriği değiştirilmemiştir; en güncel sürüm için belgenin yayıncısına başvurun.