V_{DSS}	650 V
I_D	20 A
$R_{DS(ON)}$	0.35 Ω

FEATURES

- 650V,20A
- $R_{DS(ON)}$ = 0.35Ω (Typ.) @ V_{GS} = 10V, I_D =10A
- Fast Switching
- Improved dv/dt Capability
- 100% Avalanche Tested



ITO-220AB

GK XXX
20N65F

APPLICATION

- Switch Mode Power Supply(SMPS)
- Uninterruptible Power Supply(UPS)
- Power Factor Correction (PFC)





MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

ABSOLUTE MAXIMUM RATINGS (T_C = 25°C unless otherwise specified)

Parameter		Symbol	20N65F		Units
Drain-Source Voltage		V_{DSS}	650		V
Gate-Source Voltage		V_{GSS}	±30		V
Continuous Drain Current	T_C = 25℃	I_D	20		A
	T_C = 100℃		13		A
Pulsed Drain Current note1		I_{DM}	80		A
Single Pulsed Avalanche Energy note2		E_{AS}	1350		mJ
Power Dissipation	T_C = 25℃	P_D	167	416	W
Thermal Resistance, Junction to Case		$R_{\theta JC}$	0.75	0.3	℃/W
Thermal Resistance, Junction to Ambient		$R_{\theta JA}$	60	60	℃/W
Operating and Storage Temperature Range		T_J, T_{STG}	-55 to +150		℃

Electrical Characteristics (T_C=25℃ unless otherwise specified)

Symbol	Parameter	Test Condition	Min.	Typ.	Max.	Units
Off Characteristic						
$V_{(BR)DSS}$	Drain-Source Breakdown Voltage	V_{GS}=0V,I_D=250μA	650	-	-	V
I_{DSS}	Zero Gate Voltage Drain Current	V_{DS} = 650V, V_{GS} = 0V, T_J= 25℃	-	-	1	μA
I_{GSS}	Gate to Body Leakage Current	V_{DS} =0V, V_{GS} = ±30V	-	-	±100	nA
On Characteristics						
$V_{GS(th)}$	Gate Threshold Voltage	V_{DS}= V_{GS}, I_D=250μA	2	3	4	V
$R_{DS(on)}$	Static Drain-Source on-Resistance note3	V_{GS} =10V, I_D =10A	-	0.35	0.45	Ω
Dynamic Characteristics						
C_{iss}	Input Capacitance	V_{DS} = 25V, V_{GS} = 0V, f = 1.0MHz	-	2978	-	pF
C_{oss}	Output Capacitance		-	291	-	pF
C_{rss}	Reverse Transfer Capacitance		-	40	-	pF
Q_g	Total Gate Charge	V_{DD} = 520V, I_D = 20A, V_{GS} = 10V	-	80	-	nC
Q_{gs}	Gate-Source Charge		-	12	-	nC
Q_{gd}	Gate-Drain(“Miller”) Charge		-	34	-	nC
Switching Characteristics						
$t_{d(on)}$	Turn-on Delay Time	V_{DD} = 325V, I_D =20A, R_G = 25Ω	-	37	-	ns
t_r	Turn-on Rise Time		-	66	-	ns
$t_{d(off)}$	Turn-off Delay Time		-	175	-	ns
t_f	Turn-off Fall Time		-	84	-	ns
Drain-Source Diode Characteristics and Maximum Ratings						
I_S	Maximum Continuous Drain to Source Diode Forward Current		-	-	20	A
I_{SM}	Maximum Pulsed Drain to Source Diode Forward Current		-	-	80	A
V_{SD}	Drain to Source Diode Forward Voltage	V_{GS} = 0V, I_{SD} = 20A	-	-	1.4	V
t_{rr}	Reverse Recovery Time	V_{GS} =0V, I_S=20A, di/dt=100A/μs	-	450	-	ns
Q_{rr}	Reverse Recovery Charge		-	7.1	-	μC

Notes:1. Repetitive Rating: Pulse Width Limited by Maximum Junction Temperature

2. I_{AS} =16A, V_{DD} = 50V, R_G = 25 Ω, Starting T_J = 25°C

3. Pulse Test: Pulse Width≤350μs, Duty Cycle≤1%

RATING AND CHARACTERISTIC CURVES

Figure1: Output Characteristics



Figure 2: Typical Transfer Characteristics



Figure 3: On-resistance vs. Drain Current



Figure 4: Body Diode Characteristics



Figure 5: Gate Charge Characteristics



Figure 6: Capacitance Characteristics



RATING AND CHARACTERISTIC CURVES

Figure 7: Normalized Breakdown Voltage vs. Junction Temperature



Figure 8: Normalized on Resistance vs. Junction Temperature



Figure 9: Maximum Safe Operating Area



Figure 10: Maximum Continuous Drain Current vs. Case Temperature



Figure.11: Maximum Effective Transient Thermal Impedance, Junction-to-Case (TO-220F)



Figure.12: Maximum Effective Transient Thermal Impedance, Junction-to-Case (TO-247,TO-3P)



Soldering parameters

Reflow Condition		Pb-Free assembly (see as bellow)
Pre Heat	-Temperature Min ($T_{s(min)}$)	+150℃
	-Temperature Max($T_{s(max)}$)	+200℃
	-Time (Min to Max) (ts)	60-180 secs.
Average ramp up rate (Liquid us Temp (T_L) to peak)		3℃/sec. Max
$T_{s(max)}$ to T_L - Ramp-up Rate		3℃/sec. Max
Reflow	-Temperature(T_L)(Liquid us)	+217℃
	-Temperature(t_L)	60-150 secs.
Peak Temp (T_p)		+260(+0/-5)℃
Time within 5℃ of actual Peak Temp (t_p)		30 secs. Max
Ramp-down Rate		6℃/sec. Max
Time 25℃ to Peak Temp (T_P)		8 min. Max
Do not exceed		+260℃

FIG5: Reflow condition



Package Dimensions & Suggested Pad Layout

ITO-220AB(FULLYINSULATED)



Dimensions in inches and (millimeters)

ENTEGRECİ

Bu belge www.entegreci.com üzerinden sunulmaktadır.

Elektronik komponent tedarikinde Entegreci

Entegreci, Eskişehir merkezli, Türkiye geneline satış yapan bir elektronik komponent mağazasıdır. Entegreler (IC), mikrodenetleyiciler, transistörler, diyotlar, pasif elemanlar, konnektörler, modüller ve geliştirme kartları tek adetten seri üretim adetlerine kadar satılır. Ürün sayfalarında güncel stok durumunu, fiyatı ve datasheet bağlantısını bulabilirsiniz.

Parça koduyla arama

Üretici parça numarasını yazın; stok ve fiyatı hemen görün.

www.entegreci.com

Ürün kategorileri

Entegreden kapasitöre tüm elektronik komponent kategorileri.

Kategorilere göz atın

Üreticiler

Aradığınız üreticinin ürünlerini tek sayfada inceleyin.

Üreticileri görün

Toplu alım ve teklif

Listede olmayan ya da yüksek adetli parçalar için teklif isteyin.

Teklif isteyin

www.entegreci.com | **destek@entegreci.com** | **0850 305 90 34**

Entegreci is an online electronic components store based in Türkiye. Search by manufacturer part number to see stock, prices and datasheets for integrated circuits, microcontrollers, transistors, passive components and connectors, or request a quote for parts that are not listed.

Bu sayfa Entegreci tarafından eklenmiştir. Belgenin önceki sayfaları asıl yayıncısına aittir ve içeriği değiştirilmemiştir; en güncel sürüm için belgenin yayıncısına başvurun.