## Features

- Trench Power LV MOSFET Technology
- Excellent Package For Heat Dissipation
- High Density Cell Design For Low $R_{DS(on)}$
- Moisture Sensitivity Level 1
- Halogen Free. “Green” Device (Note 1)
- Epoxy Meets UL 94 V-0 Flammability Rating
- Lead Free Finish/RoHS Compliant ("P" Suffix Designates RoHS Compliant. See Ordering Information)

# N-CHANNEL MOSFET

## Maximum Ratings

- Operating Junction Temperature Range : -55°C to +175°C
- Storage Temperature Range: -55°C to +175°C
- Thermal Resistance:60°C/W Junction to Ambient(Note2)
- Thermal Resistance: 5°C/W Junction to Case

| Parameter | | Symbol | Rating | Unit |
|---|---|---|---|---|
| Drain-Source Voltage | | $V_{DS}$ | 30 | V |
| Gate-Source Volltage | | $V_{GS}$ | ±20 | V |
| Continuous Drain Current | $T_C$=25°C | $I_D$ | 50 | A |
| | $T_C$=100°C | | 35 | |
| Pulsed Drain Current (Note 3) | | $I_{DM}$ | 200 | A |
| Total Power Dissipation (Note 4) | | $P_D$ | 30 | W |
| Single Pulse Avalanche Energy(Note5) | | $E_{AS}$ | 112 | mJ |

Note:

1. Halogen free "Green” products are defined as those which contain <900ppm bromine, <900ppm chlorine (<1500ppm total Br + Cl) and <1000ppm antimony compounds.
2. The value of RthJA is measured with the device mounted on 1 in2 FR-4 board with 2oz. copper, in a still air environment with $T_A$=25°C
3. Repetitive rating; pulse width limited by max. junction temperature.
4. $P_D$ is based on max. junction temperature, using junction-case thermal resistance.
5. $T_J$=25°C, $V_{DD}$=25V, $V_{GS}$=10V, L=1mH

## Internal Structure and Marking Code







pin1

DFN3333




| DIMENSIONS | | | | | |
|---|---|---|---|---|---|
| DIM | INCHES | | MM | | NOTE |
| | MIN | MAX | MIN | MAX | |
| A | 0.126 | 0.130 | 3.20 | 3.30 | |
| B | 0.126 | 0.130 | 3.20 | 3.30 | |
| C | 0.030 | 0.033 | 0.75 | 0.85 | |
| C1 | 0.007 | 0.009 | 0.18 | 0.22 | |
| C2 | --- | 0.002 | --- | 0.05 | |
| D | 0.071 | 0.079 | 1.80 | 2.00 | |
| E | 0.087 | 0.098 | 2.20 | 2.50 | |
| F | 0.016 | 0.020 | 0.40 | 0.50 | |
| G | 0.010 | 0.014 | 0.25 | 0.35 | |
| H | 0.012 | 0.016 | 0.30 | 0.40 | |
| e | 0.024 | 0.028 | 0.60 | 0.70 | |

## Electrical Characteristics @ 25°C (Unless Otherwise Specified)

| Parameter | Symbol | Test Conditions | Min | Typ | Max | Unit |
|---|---|---|---|---|---|---|
| **Static Characteristics** | | | | | | |
| Drain-Source Breakdown Voltage | $V_{(BR)DSS}$ | $V_{GS}$=0V, $I_D$=250μA | 30 | | | V |
| Gate-Source Leakage Current | $I_{GSS}$ | $V_{DS}$=0V, $V_{GS}$ =±20V | | | ±100 | nA |
| Zero Gate Voltage Drain Current | $I_{DSS}$ | $V_{DS}$=30V, $V_{GS}$=0V | | | 1 | μA |
| Gate-Threshold Voltage | $V_{GS(th)}$ | $V_{DS}$=$V_{GS}$, $I_D$=250μA | 1 | 1.5 | 2.5 | V |
| Drain-Source On-Resistance | $R_{DS(on)}$ | $V_{GS}$=10V, $I_D$=15A | | 4.9 | 6 | mΩ |
| | | $V_{GS}$=4.5V, $I_D$=15A | | 6.3 | 8 | |
| Gate Resistance | $R_g$ | f=1MHz, Open drain | | 2.5 | | Ω |
| **Diode Characteristics** | | | | | | |
| Diode Forward Voltage | $I_S$ | | | | 50 | A |
| Continuous Body Diode Current | $V_{SD}$ | $V_{GS}$=0V, $I_S$=20A | | | 1.2 | V |
| Reverse Recovery Chrage | $Q_{rr}$ | $I_S$=25A, $dI_F/dt$=100A/μs | | 101 | | ns |
| Reverse Recovery Time | $t_{rr}$ | | | 103 | | nC |
| **Dynamic Characteristics** | | | | | | |
| Input Capacitance | $C_{iss}$ | $V_{DS}$=15V,$V_{GS}$=0V,f=1MHz | | 2150 | | pF |
| Output Capacitance | $C_{oss}$ | | | 270 | | |
| Reverse Transfer Capacitance | $C_{rss}$ | | | 250 | | |
| Total Gate Charge | $Q_g$ | $V_{DS}$=15V,$V_{GS}$=10V,$I_D$=20A | | 43 | | nC |
| Gate-Source Charge | $Q_{gs}$ | | | 6 | | |
| Gate-Drain Charge | $Q_{gd}$ | | | 12 | | |
| Turn-On Delay Time | $t_{d(on)}$ | $V_{GS}$=10V, $V_{DD}$=20V, $I_D$=4A,$R_L$=2.2Ω | | 9 | | ns |
| Turn-On Rise Time | $t_r$ | | | 29 | | |
| Turn-Off Delay Time | $t_{d(off)}$ | | | 33 | | |
| Turn-Off Fall Time | $t_f$ | | | 5 | | |

## Curve Characteristics

**Fig.1 - Typical Output Characteristics**




**Fig.2 - Transfer Characteristic**




**Fig.3 - $R_{DS(ON)}$ - $V_{GS}$**




**Fig.4 - $R_{DS(ON)}$ - $I_D$**




**Fig.5 - Capacitance Characteristics**




**Fig.6 - Gate Charge**



## Curve Characteristics

**Fig.7 - Normalized Threshold Voltage**




**Fig.8 - Normalized On Resistance Characteristics**




**Fig.9 - $I_S$ - $V_{SD}$**




**Fig.10 - Drain Current**




**Fig.11 - PD Dissipation**



## Curve Characteristics

**Fig.12 - Safe Operation Area**




**Fig.13 - Normalized Transient Thermal Impedance**



## Ordering Information

| Device | Packing |
|---|---|
| Part Number-TP | Tape&Reel: 5Kpcs/Reel |


*****IMPORTANT NOTICE*****

***Micro Commercial Components Corp***. reserves the right to make changes without further notice to any product herein to make corrections, modifications , enhancements , improvements , or other changes . ***Micro Commercial Components Corp*** . does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights ,nor the rights of others . The user of products in such applications shall assume all risks of such use and will agree to hold ***Micro Commercial Components Corp*** . and all the companies whose products are represented on our website, harmless against all damages. ***Micro Commercial Components Corp***. products are sold subject to the general terms and conditions of commercial sale, as published at
**https://www.mccsemi.com/Home/TermsAndConditions.**

*****LIFE SUPPORT*****

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

*****CUSTOMER AWARENESS*****

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. **MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources**. MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.

ENTEGRECİ

Bu belge www.entegreci.com üzerinden sunulmaktadır.

# Elektronik komponent tedarikinde Entegreci

Entegreci, Eskişehir merkezli, Türkiye geneline satış yapan bir elektronik komponent mağazasıdır. Entegreler (IC), mikrodenetleyiciler, transistörler, diyotlar, pasif elemanlar, konnektörler, modüller ve geliştirme kartları tek adetten seri üretim adetlerine kadar satılır. Ürün sayfalarında güncel stok durumunu, fiyatı ve datasheet bağlantısını bulabilirsiniz.

### Parça koduyla arama

Üretici parça numarasını yazın; stok ve fiyatı hemen görün.

**www.entegreci.com**

### Ürün kategorileri

Entegreden kapasitöre tüm elektronik komponent kategorileri.

**Kategorilere göz atın**

### Üreticiler

Aradığınız üreticinin ürünlerini tek sayfada inceleyin.

**Üreticileri görün**

### Toplu alım ve teklif

Listede olmayan ya da yüksek adetli parçalar için teklif isteyin.

**Teklif isteyin**

**www.entegreci.com** | **destek@entegreci.com** | **0850 305 90 34**

Entegreci is an online electronic components store based in Türkiye. Search by manufacturer part number to see stock, prices and datasheets for integrated circuits, microcontrollers, transistors, passive components and connectors, or request a quote for parts that are not listed.

Bu sayfa Entegreci tarafından eklenmiştir. Belgenin önceki sayfaları asıl yayıncısına aittir ve içeriği değiştirilmemiştir; en güncel sürüm için belgenin yayıncısına başvurun.