	E502650

IGBT Modules
1200V 75A


Features


- Low Switching Losses
- Low $V_{ce(sat)}$ with Positive Temperature Coefficient
- Including Fast & Soft Recovery Anti-parallel FWD
- Low Inductance Case
- High Short Circuit Capability(10μs)
- Maximum Junction Temperature 175°C
- Epoxy Meets UL 94 V-0 Flammability Rating
- Lead Free Finish/RoHS Compliant ("P" Suffix Designates RoHS Compliant. See Ordering Information)

Applications


- Motor Drivers
- AC and DC Servo Drive Amplifier
- UPS (Uninterruptible Power Supplies)


Circuit Diagram





E2A





● IGBT- Inverter

Maximum Ratings

Parameter	Symbol	Test Conditions	Rating	Unit
Collector-Emitter Voltage	V_{CES}	V_{GE}=0V, I_C=1mA, T_{vj}=25°C	1200	V
Continuous Collector Current	I_C	T_C=80°C, T_{vjmax}=175°C	75	A
Repetitive Peak Collector Current	I_{CRM}	t_p=1ms	150	A
Gate-Emitter Voltage	V_{GES}	T_{vj}=25°C	±20	V
Total Power Dissipation	P_{tot}	T_C=25°C, T_{vjmax}=175°C	470	W

Electrical Characteristics

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Gate-Emitter Threshold Voltage	$V_{GE(th)}$	V_{GE}=V_{CE}, I_C=3.3mA,T_{vj}=25°C	5	5.8	6.5	V
Collector-Emitter Cut-off Current	I_{CES}	V_{CE}=1200V,V_{GE}=0V, Tvj=25°C			1	mA
Collector-Emitter Saturation Voltage	$V_{CE(sat)}$	I_C=75A,V_{GE}=15V, T_{vj}=25°C		1.95		V
		I_C=75A,V_{GE}=15V, T_{vj}=125°C		2.20		V
		I_C=75A,V_{GE}=15V, T_{vj}=150°C		2.30		V
Gate Charge	Q_g			0.85		μC
Input Capacitance	C_{ies}	V_{CE}=25V,V_{GE}=0V,f=1MHz		4.2		nF
Reverse Transfer Capacitance	C_{res}			0.32		
Internal Gate Resistance	R_{gint}			10		Ω
Gate-Emitter leakage current	I_{GES}	V_{CE}=0V, V_{GE}=20V, T_{vj}=25°C			400	nA
Turn-On Delay Time	$t_{d(on)}$	V_{CE}=600V, I_C=75A, V_{GE}=± 15V, R_G=2.2Ω, T_{vj}=25°C		75		ns
Rise Time	t_r			40		
Turn-Off Delay Time	$t_{d(off)}$			163		
Fall Time	t_f			235		
Turn-On Energy	E_{on}			4.71		mJ
Turn-Off Energy	E_{off}			5.45		
Turn-On Delay Time	$t_{d(on)}$	V_{CE}=600V, I_C=75A, V_{GE}=± 15V, R_G=2.2Ω, T_{vj}=150°C		77		ns
Rise Time	t_r			47		
Turn-Off Delay Time	$t_{d(off)}$			173		
Fall Time	t_f			309		
Turn-On Energy	E_{on}			6.73		mJ
Turn-Off Energy	E_{off}			6.24		
SC Data	I_{SC}	T_p≤10μs,V_{GE}=15V,T_{vj}=150℃, V_{CC}=900V,V_{CEM}≤1200V		300		A

● Diode- Inverter

Maximum Ratings

Parameter	Symbol	Test Conditions	Rating	Unit
Repetitive Peak Reverse Voltage	V_{RRM}	T_{vj}=25°C	1200	V
Continuous DC Forward Current	I_F		75	A
Repetitive Peak Forward Current	I_{FRM}	t_p=1ms	150	A
I^2t-value	I^2t	V_R=0,t_p=10ms,T_{vj}=125°C	810	A^2s
		V_R=0,t_p=10ms,T_{vj}=150°C	690	

Electrical Characteristics

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Forward Voltage	V_F	I_F=75A, T_{vj}=25°C		1.95	2.60	V
		I_F=75A, T_{vj}=125°C		1.78		V
		I_F=75A, T_{vj}=150°C		1.70		V
Recovered Charge	Q_{rr}	I_F=75A, V_R=600V, -di_F/dt=1700A/μs, T_{vj}=25°C		2.1		μC
Peak Reverse Recovery Current	I_{rr}			53		A
Reverse Recovery Energy	E_{rec}			0.35		mJ
Recovered Charge	Q_{rr}	I_F=75A, V_R=600V, -di_F/dt=1700A/μs, T_{vj}=150°C		5.8		μC
Peak Reverse Recovery Current	I_{rr}			56		A
Reverse Recovery Energy	E_{rec}			1.67		mJ

● IGBT- Brake-chopper

Maximum Ratings

Parameter	Symbol	Test Conditions	Rating	Unit
Collector-Emitter Voltage	V_{CES}	V_{GE}=0V, I_C=1mA, T_{vj}=25°C	1200	V
Continuous Collector Current	I_C	T_C=100°C, T_{vjmax}=175°C	50	A
Repetitive Peak Collector Current	I_{CRM}	t_p=1ms	100	A
Gate-Emitter Voltage	V_{GES}	T_{vj}=25°C	±20	V
Total Power Dissipation	P_{tot}	T_C=25°C, T_{vjmax}=175°C	442	W

Electrical Characteristics

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Gate-Emitter Threshold Voltage	$V_{GE(th)}$	V_{GE}=V_{CE}, I_C=1.7mA,T_{vj}=25°C	5.0	5.7	6.5	V
Collector-Emitter Cut-off Current	I_{CES}	V_{CE}=1200V,V_{GE}=0V, T_{vj}=25°C			1	mA
Collector-Emitter Saturation Voltage	$V_{CE(sat)}$	I_C=50A,V_{GE}=15V, T_{vj}=25°C		1.9		V
		I_C=50A,V_{GE}=15V, T_{vj}=125°C		2.25		V
		I_C=50A,V_{GE}=15V, T_{vj}=150°C		2.32		V
Gate Charge	Q_g			0.35		µC
Input Capacitance	C_{ies}	V_{CE}=25V,V_{GE}=0V,f=1MHz		2.60		nF
Reverse Transfer Capacitance	C_{res}			0.10		
Gate-Emitter leakage current	I_{GES}	V_{CE}=0V, V_{GE}=20V, T_{vj}=25°C			400	nA
Turn-On Delay Time	$t_{d(on)}$	V_{CE}=600V, I_C=50A, V_{GE}=± 15V, R_G=20Ω, T_{vj}=25°C		41		ns
Rise Time	t_r			48		
Turn-Off Delay Time	$t_{d(off)}$			160		
Fall Time	t_f			244		
Turn-On Energy	E_{on}			5.92		mJ
Turn-Off Energy	E_{off}			3.39		
Turn-On Delay Time	$t_{d(on)}$	V_{CE}=600V, I_C=50A, V_{GE}=± 15V, R_G=20Ω, T_{vj}=150°C		45		ns
Rise Time	t_r			50		
Turn-Off Delay Time	$t_{d(off)}$			169		
Fall Time	t_f			302		
Turn-On Energy	E_{on}			6.87		mJ
Turn-Off Energy	E_{off}			3.73		
SC Data	I_{SC}	T_p≤10µs,V_{GE}=15V,T_{vj}=150°C, V_{CC}=900V,V_{CEM}≤1200V		200		A

● Diode- Brake-chopper

Maximum Ratings

Parameter	Symbol	Test Conditions	Rating	Unit
Repetitive Peak Reverse Voltage	V_{RRM}	T_{vj}=25°C	1200	V
Continuous DC Forward Current	I_F		35	A
Repetitive Peak Forward Current	I_{FRM}	t_p=1ms	70	A
I^2t-value	I^2t	V_R=0,t_p=10ms,T_{vj}=125°C	240	A^2s
		V_R=0,t_p=10ms,T_{vj}=150°C	220	

Electrical Characteristics

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Forward Voltage	V_F	I_F=35A, T_{vj}=25°C		1.95		V
		I_F=35A, T_{vj}=125°C		1.78		V
		I_F=35A, T_{vj}=150°C		1.69		V
Recovered Charge	Q_{rr}	I_F=35A, V_R=600V, -di_F/dt=1600A/µs, T_{vj}=25°C		2.35		µC
Peak Reverse Recovery Current	I_{rr}			21		A
Reverse Recovery Energy	E_{rec}			0.67		mJ
Recovered Charge	Q_{rr}	I_F=35A, V_R=600V, -di_F/dt=1600A/µs, T_{vj}=150°C		3.81		µC
Peak Reverse Recovery Current	I_{rr}			25		A
Reverse Recovery Energy	E_{rec}			1.13		mJ

● Diode- Rectifier

Maximum Ratings

Parameter	Symbol	Test Conditions	Rating	Unit
Repetitive Peak Reverse Voltage	V_{RRM}	T_j=25°C	1600	V
Average On-state Current 50/60Hz, sine wave	$I_{F(AV)}$	T_C=100°C	80	A
Maximum RMS Current at Rectifier Output	I_{RMSM}	T_C=100°C	120	A
Surge Forward Current	I_{FSM}	V_R=0,t_p=10ms,T_{vj}=25°C	1200	A
		V_R=0,t_p=10ms,T_{vj}=150°C	1000	A
I^2t-value	I^2t	V_R=0,t_p=10ms,T_{vj}=25°C	7200	A^2s
		V_R=0,t_p=10ms,T_{vj}=150°C	5000	A^2s

Electrical Characteristics

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Diode Forward Voltage	V_F	I_F=50A,T_j=125°C		0.98		V
Reverse Current	I_r	T_{vj}=125°C,V_R=1600V			2	mA

● NTC-Thermistor

Electrical Characteristics

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Rated Resistance	R_{25}			5		kΩ
Deviation of R100	ΔR/R	T_C=100,R_{100}=493.3Ω	-5		5	%
Power Dissipation	P_{25}				20	mW
B-value	$B_{25/50}$	$R_2=R_{25}\exp[B_{25/50}(1/T_2-1/(298.15K))]$		3375		K

● Module Characteristics(T_C=25°C unless otherwise specified)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Isolation voltage	V_{isol}	t=1min,f=50Hz	2500			V
Maximum Junction Temperature	T_{jmax}				175	°C
Operating Junction Temperature	$T_{vj\ op}$		-40		150	°C
Operating Junction Temperature	T_{stg}		-40		125	°C
Stray Inductance	L_{CE}			60		nH
Module Lead Resistance , Terminal to Chip	$R_{cc'+EE'}$	T_C=25°C, per switch		4		mΩ
	$R_{AA'+CC'}$			3		
Thermal Resistance Junction to Case	$R_{\theta jc}$	per IGBT-inverter		0.315		K/W
		per Diode-inverter		0.619		
		per IGBT-brake-chopper		0.5		
		per Diode-chopper		1.266		
		per Diode-rectifier		0.635		
Thermal Resistance Case to Sink	$R_{\theta CS}$	per IGBT-inverter		0.121		K/W
		per Diode-inverter		0.221		
		per IGBT-brake-chopper		0.18		
		per Diode-chopper		0.452		
		per Diode-rectifier		0.227		
		per Module		0.009		
Module-to-Sink Torque	M_S		3		6	N·m
Weight of Module	G			300		g

Curve Characteristics

Fig1.IGBT Output Characteristics




Fig2.IGBT Transfer Characteristics




Fig3.IGBT Switching Loss vs.Ic





Fig4.IGBT Switching Loss vs.Rg



Curve Characteristics

Fig5. RBSOA




Fig 6. IGBT Transient Thermal Impedance




Fig7.Diode Foward Characteristics





Fig8.Diode Switching Loss vs.I_F



Curve Characteristics

Fig9.Diode Switching Loss vs.Rg




Fig10.Diode Transient Thermal Impedance




Fig 11. NTC Temperature Characteristic






Fig12. IGBT-brake-chopper Output Characteristics




Curve Characteristics

Fig13. Diode-brake-chopper Forward Characteristics




Circuit Diagram



Package Dimensions

Dimensions in mm

E2A



Ordering Information

Device	Packing
Part Number-BP	Bulk: 6pcs/Box ; 36pcs/Ctn

*****IMPORTANT NOTICE*****

Micro Commercial Components Corp. reserves the right to make changes without further notice to any product herein to make corrections, modifications , enhancements , improvements , or other changes . ***Micro Commercial Components Corp*** . does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights ,nor the rights of others . The user of products in such applications shall assume all risks of such use and will agree to hold ***Micro Commercial Components Corp*** . and all the companies whose products are represented on our website, harmless against all damages. ***Micro Commercial Components Corp***. products are sold subject to the general terms and conditions of commercial sale, as published at
https://www.mccsemi.com/Home/TermsAndConditions.

*****LIFE SUPPORT*****

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

*****CUSTOMER AWARENESS*****

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. **MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources**. MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.

ENTEGRECİ

Bu belge www.entegreci.com üzerinden sunulmaktadır.

Elektronik komponent tedarikinde Entegreci

Entegreci, Eskişehir merkezli, Türkiye geneline satış yapan bir elektronik komponent mağazasıdır. Entegreler (IC), mikrodenetleyiciler, transistörler, diyotlar, pasif elemanlar, konnektörler, modüller ve geliştirme kartları tek adetten seri üretim adetlerine kadar satılır. Ürün sayfalarında güncel stok durumunu, fiyatı ve datasheet bağlantısını bulabilirsiniz.

Parça koduyla arama

Üretici parça numarasını yazın; stok ve fiyatı hemen görün.

www.entegreci.com

Ürün kategorileri

Entegreden kapasitöre tüm elektronik komponent kategorileri.

Kategorilere göz atın

Üreticiler

Aradığınız üreticinin ürünlerini tek sayfada inceleyin.

Üreticileri görün

Toplu alım ve teklif

Listede olmayan ya da yüksek adetli parçalar için teklif isteyin.

Teklif isteyin

www.entegreci.com | **destek@entegreci.com** | **0850 305 90 34**

Entegreci is an online electronic components store based in Türkiye. Search by manufacturer part number to see stock, prices and datasheets for integrated circuits, microcontrollers, transistors, passive components and connectors, or request a quote for parts that are not listed.

Bu sayfa Entegreci tarafından eklenmiştir. Belgenin önceki sayfaları asıl yayıncısına aittir ve içeriği değiştirilmemiştir; en güncel sürüm için belgenin yayıncısına başvurun.