
NIKO-SEM


P-Channel Enhancement Mode Field Effect Transistor

PD517BA
TO-252
Halogen-Free & Lead-Free

PRODUCT SUMMARY

$V_{(BR)DSS}$	$R_{DS(ON)}$	I_D
-30V	12mΩ	-55A





1. GATE
2. DRAIN
3. SOURCE

RoHS Compliant

ABSOLUTE MAXIMUM RATINGS (T_A = 25 °C Unless Otherwise Noted)

PARAMETERS/TEST CONDITIONS		SYMBOL	LIMITS	UNITS
Drain-Source Voltage		V_{DS}	-30	V
Gate-Source Voltage		V_{GS}	±20	V
Continuous Drain Current[2]	T_C = 25 °C	I_D	-55	A
	T_C = 100 °C		-35	
Pulsed Drain Current[1]		I_{DM}	-150	
Avalanche Current		I_{AS}	-38	
Avalanche Energy	L = 0.1mH	E_{AS}	72	mJ
Power Dissipation	T_C = 25 °C	P_D	62	W
	T_C = 100 °C		25	
Junction & Storage Temperature Range		T_J, T_{stg}	-55 to 150	°C

THERMAL RESISTANCE RATINGS

THERMAL RESISTANCE	SYMBOL	TYPICAL	MAXIMUM	UNITS
Junction-to-Case	$R_{\theta JC}$		2	°C / W
Junction-to-Ambient	$R_{\theta JA}$		62.5	

[1]Pulse width limited by maximum junction temperature.
[2]Package limitation current is -40A.


ELECTRICAL CHARACTERISTICS (T_J = 25 °C, Unless Otherwise Noted)

PARAMETER	SYMBOL	TEST CONDITIONS	LIMITS			UNIT
			MIN	TYP	MAX	
STATIC						
Drain-Source Breakdown Voltage	$V_{(BR)DSS}$	V_{GS} = 0V, I_D = -250μA	-30			V
Gate Threshold Voltage	$V_{GS(th)}$	V_{DS} = V_{GS}, I_D = -250μA	-1	-1.7	-3	
Gate-Body Leakage	I_{GSS}	V_{DS} = 0V, V_{GS} = ±20V			±100	nA
Zero Gate Voltage Drain Current	I_{DSS}	V_{DS} = -24V, V_{GS} = 0V			-1	μA
		V_{DS} = -20V, V_{GS} = 0V, T_J = 125 °C			-10	


Drain-Source On-State Resistance[1]	$R_{DS(ON)}$	V_{GS} = -4.5V, I_D = -9A		15.4	19	mΩ
		V_{GS} = -10V, I_D = -12A		9.8	12	
Forward Transconductance[1]	g_{fs}	V_{DS} = -5V, I_D = -12A		31		S
DYNAMIC						
Input Capacitance	C_{iss}	V_{GS} = 0V, V_{DS} = -15V, f = 1MHz		2740		pF
Output Capacitance	C_{oss}			376		
Reverse Transfer Capacitance	C_{rss}			321		
Gate Resistance	R_g	V_{GS} =0V, V_{DS} = 0V, f = 1MHz		2.6		Ω
Total Gate Charge[2]	$Q_{g\ (V_{GS}=-10V)}$	V_{DS} = -15V , V_{GS} = -10V, I_D = -12A		55		nC
	$Q_{g(V_{GS}=-4.5V)}$			28		
Gate-Source Charge[2]	Q_{gs}			8.7		
Gate-Drain Charge[2]	Q_{gd}			13		
Turn-On Delay Time[2]	$t_{d(on)}$	V_{DS} = -15V , $I_D \cong$ -12A, V_{GS} = -10V, R_{GEN} =6Ω		15		nS
Rise Time[2]	t_r			18		
Turn-Off Delay Time[2]	$t_{d(off)}$			38		
Fall Time[2]	t_f			22		
SOURCE-DRAIN DIODE RATINGS AND CHARACTERISTICS (T_J = 25 °C)						
Continuous Current[3]	I_S				-51	A
Forward Voltage[1]	V_{SD}	I_F = -12A, V_{GS} = 0V			-1.2	V
Reverse Recovery Time	t_{rr}	I_F = -12A, dI_F/dt = 100A / μS		20		nS
Reverse Recovery Charge	Q_{rr}			12		nC

[1]Pulse test : Pulse Width ≤ 300 μsec, Duty Cycle ≤ 2%.
[2]Independent of operating temperature.
[3]Package limitation current is -40A.


Output Characteristics




Transfer Characteristics




On-Resistance VS Temperature




Capacitance Characteristic




Gate charge Characteristics




Source-Drain Diode Forward Voltage




Safe Operating Area



Single Pulse Maximum Power Dissipation



Transient Thermal Response Curve



ENTEGRECİ

Bu belge www.entegreci.com üzerinden sunulmaktadır.

Elektronik komponent tedarikinde Entegreci

Entegreci, Eskişehir merkezli, Türkiye geneline satış yapan bir elektronik komponent mağazasıdır. Entegreler (IC), mikrodenetleyiciler, transistörler, diyotlar, pasif elemanlar, konnektörler, modüller ve geliştirme kartları tek adetten seri üretim adetlerine kadar satılır. Ürün sayfalarında güncel stok durumunu, fiyatı ve datasheet bağlantısını bulabilirsiniz.

Parça koduyla arama

Üretici parça numarasını yazın; stok ve fiyatı hemen görün.

www.entegreci.com

Ürün kategorileri

Entegreden kapasitöre tüm elektronik komponent kategorileri.

Kategorilere göz atın

Üreticiler

Aradığınız üreticinin ürünlerini tek sayfada inceleyin.

Üreticileri görün

Toplu alım ve teklif

Listede olmayan ya da yüksek adetli parçalar için teklif isteyin.

Teklif isteyin

www.entegreci.com | **destek@entegreci.com** | **0850 305 90 34**

Entegreci is an online electronic components store based in Türkiye. Search by manufacturer part number to see stock, prices and datasheets for integrated circuits, microcontrollers, transistors, passive components and connectors, or request a quote for parts that are not listed.

Bu sayfa Entegreci tarafından eklenmiştir. Belgenin önceki sayfaları asıl yayıncısına aittir ve içeriği değiştirilmemiştir; en güncel sürüm için belgenin yayıncısına başvurun.