PJQ1916

20V N-Channel Enhancement Mode MOSFET

Voltage 20 V **Current** 950mA

DFN1006-3L





Features

- Advanced Trench Process Technology
- ESD Protected
- Specially Designed for Switch Load, PWM Application, etc
- Lead free in compliance with EU RoHS 2.0
- Green molding compound as per IEC 61249 standard

Mechanical Data

- Case : DFN1006-3L Package
- Terminals : Solderable per MIL-STD-750, Method 2026
- Approx. Weight : 0.00002 ounces, 0.0007 grams

Maximum Ratings and Thermal Characteristics (T_A=25°C unless otherwise noted)

PARAMETER		SYMBOL	LIMIT	UNITS
Drain-Source Voltage		V_{DS}	20	V
Gate-Source Voltage		V_{GS}	±8	
Continuous Drain Current(Note 4)		I_D	950	mA
Pulsed Drain Current(Note 1)		I_{DM}	1900	
Power Dissipation	T_A=25°C	P_D	500	mW
	Derate above 25°C		4	mW/°C
Operating Junction and Storage Temperature Range		T_J,T_{STG}	-55~150	°C
Typical Thermal Resistance - Junction to Ambient(Note 5)		$R_{\theta JA}$	250	°C/W

PJQ1916

Electrical Characteristics (T_A=25°C unless otherwise noted)

PARAMETER	SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNITS
Static						
Drain-Source Breakdown Voltage	BV_{DSS}	V_{GS}=0V, I_D=250uA	20	-	-	V
Gate Threshold Voltage	$V_{GS(th)}$	V_{DS}=V_{GS}, I_D=250uA	0.3	0.5	1	
Drain-Source On-State Resistance	$R_{DS(on)}$	V_{GS}=4.5V, I_D=500mA	-	220	300	mΩ
		V_{GS}=2.5V, I_D=400mA	-	250	400	
		V_{GS}=1.8V, I_D=200mA	-	300	550	
		V_{GS}=1.5V, I_D=100mA	-	340	800	
		V_{GS}=1.2V, I_D=10mA	-	480	1500	
Zero Gate Voltage Drain Current	I_{DSS}	V_{DS}=20V, V_{GS}=0V	-	-	1	uA
Gate-Source Leakage Current	I_{GSS}	V_{GS}=±8V, V_{DS}=0V	-	-	±10	
Dynamic(Note 6)						
Total Gate Charge	Q_g	V_{DS}=10V, I_D=500mA, V_{GS}=4.5V(Note 2,3)	-	1.1	-	nC
Gate-Source Charge	Q_{gs}		-	0.16	-	
Gate-Drain Charge	Q_{gd}		-	0.12	-	
Input Capacitance	Ciss	V_{DS}=10V, V_{GS}=0V, f=1MHZ	-	46	-	pF
Output Capacitance	Coss		-	15	-	
Reverse Transfer Capacitance	Crss		-	13	-	
Turn-On Delay Time	$td_{(on)}$	V_{DS}=10V, I_D=500mA, V_{GS}=4.5V, R_G=10Ω (Note 2,3)	-	5.3	-	ns
Turn-On Rise Time	t_r		-	22	-	
Turn-Off Delay Time	$td_{(off)}$		-	43	-	
Turn-Off Fall Time	t_f		-	31	-	
Drain-Source Diode						
Diode Forward Current	I_S	---	-	-	500	mA
Diode Forward Voltage	V_{SD}	I_S=500mA,V_{GS}=0V	-	0.7	1	V

Notes：

1.Pulse width<300us, Duty cycle<2%.

2.Essentially independent of operating temperature typical characteristics.

3.Repetitive rating, pulse width limited by junction temperature T_J(MAX)=150℃.Ratings are based on low frequency and duty cycles to keep initial T_J =25℃.

4.The maximum current rating is package limited.

5.$R_{\theta JA}$ is the sum of the junction-to-case and case-to-ambient thermal resistance where the case thermal reference is defined as the solder mounting surface of the drain pins. Mounted on a 1 inch^2 with 2oz.square pad of copper.

6.Guaranteed by design, not subject to production testing.

PJQ1916

TYPICAL CHARACTERISTIC CURVES



Fig.1 Output Characteristics



Fig.2 Transfer Characteristics



Fig.3 On-Resistance vs. Drain Current



Fig.4 On-Resistance vs. Junction temperature



Fig.5 On-Resistance Variation with V_{GS}



Fig.6 Source-Drain Diode Forward Voltage

PJQ1916

TYPICAL CHARACTERISTIC CURVES



Fig.7 Gate-Charge Characteristics



Fig.8 Breakdown Voltage Variation vs. Temperature



Fig.9 Threshold Voltage Variation with Temperature



Fig.10 Capacitance vs. Drain-Source Voltage

PJQ1916

Product and Packing Information

Part No.	Package Type	Packing Type	Marking
PJQ1916	DFN1006-3L	10K pcs / 7” reel	G

Packaging Information & Mounting Pad Layout

DFN1006-3L Dimension — Unit: inch(mm)



DFN1006-3L Pad Layout — Unit: inch(mm)



PJQ1916

Disclaimer

- Reproducing and modifying information of the document is prohibited without permission from Panjit International Inc..
- Panjit International Inc. reserves the rights to make changes of the content herein the document anytime without notification. Please refer to our website for the latest document.
- Panjit International Inc. disclaims any and all liability arising out of the application or use of any product including damages incidentally and consequentially occurred.
- Panjit International Inc. does not assume any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.
- Applications shown on the herein document are examples of standard use and operation. Customers are responsible in comprehending the suitable use in particular applications. Panjit International Inc. makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.
- The products shown herein are not designed and authorized for equipments requiring high level of reliability or relating to human life and for any applications concerning life-saving or life-sustaining, such as medical instruments, transportation equipment, aerospace machinery et cetera. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Panjit International Inc. for any damages resulting from such improper use or sale.
- Since Panjit uses lot number as the tracking base, please provide the lot number for tracking when complaining.

ENTEGRECİ

Bu belge www.entegreci.com üzerinden sunulmaktadır.

Elektronik komponent tedarikinde Entegreci

Entegreci, Eskişehir merkezli, Türkiye geneline satış yapan bir elektronik komponent mağazasıdır. Entegreler (IC), mikrodenetleyiciler, transistörler, diyotlar, pasif elemanlar, konnektörler, modüller ve geliştirme kartları tek adetten seri üretim adetlerine kadar satılır. Ürün sayfalarında güncel stok durumunu, fiyatı ve datasheet bağlantısını bulabilirsiniz.

Parça koduyla arama

Üretici parça numarasını yazın; stok ve fiyatı hemen görün.

www.entegreci.com

Ürün kategorileri

Entegreden kapasitöre tüm elektronik komponent kategorileri.

Kategorilere göz atın

Üreticiler

Aradığınız üreticinin ürünlerini tek sayfada inceleyin.

Üreticileri görün

Toplu alım ve teklif

Listede olmayan ya da yüksek adetli parçalar için teklif isteyin.

Teklif isteyin

www.entegreci.com | **destek@entegreci.com** | **0850 305 90 34**

Entegreci is an online electronic components store based in Türkiye. Search by manufacturer part number to see stock, prices and datasheets for integrated circuits, microcontrollers, transistors, passive components and connectors, or request a quote for parts that are not listed.

Bu sayfa Entegreci tarafından eklenmiştir. Belgenin önceki sayfaları asıl yayıncısına aittir ve içeriği değiştirilmemiştir; en güncel sürüm için belgenin yayıncısına başvurun.