PTD4080B

40V/60A N-Channel Advanced Power MOSFET

Features

- $R_{DS(on)}$ (Typical 5.5mΩ)@V_{GS}=10V
- Improved dv/dt Capability, High Ruggedness
- 100% Avalanche Tested
- Maximum Junction Temperature Range (150°C)





TO-252

Absolute Maximum Ratings

Stresses exceeding Maximum Ratings may damage the device. Maximum Ratings are stress ratings only. Functional operation above the Recommended Operating Conditions is not implied. Extended exposure to stresses above the Recommended Operating Conditions may affect device reliability.

Symbol	Parameter		Rating	Unit
Common Ratings (T_J=25°C Unless Otherwise Noted)				
V_{GS}	Gate-Source Voltage		±20	V
$V_{(BR)DSS}$	Drain-Source Breakdown Voltage		40	V
T_J	Maximum Junction Temperature		-50 to 175	°C
T_{STG}	Storage Temperature Range		–50 to 175	°C
I_S	Diode Continuous Forward Current		60	A
Mounted on Large Heat Sink (T_J=25°C Unless Otherwise Noted)				
I_{DM}	Pulse Drain Current Tested (Sillicon Limit) (Note1)		240	A
I_D	Continuous Drain current@V_{GS}=10V	T_C=25°C	60	A
P_D	Maximum Power Dissipation	T_C=25°C	47	W
E_{AS}	Sing Pulsed Avalanche Energy (Note2)		81	mJ
$R_{\theta JC}$	Thermal Resistance Junction−to−Case		3.2	°C/W

Symbol	Parameter	Condition	Min.	Typ.	Max.	Unit
Static Electrical Characteristics @ T_J= 25°C (unless otherwise stated)						
$V_{(BR)DSS}$	Drain-Source Breakdown Voltage	VGS=0V ID=250μA	40	--	--	V
I_{DSS}	Zero Gate Voltage Drain current(Tc=25℃)	VDS=40V,VGS=0V	--	--	1	μA
I_{GSS}	Gate-Body Leakage Current	VGS=±20V,VDS=0V	--	--	±100	nA
$V_{GS(TH)}$	Gate Threshold Voltage	VDS=VGS,ID=250μA	1	--	2.5	V
$R_{DS(ON)}$	Drain-Source On-State Resistance (Note3)	VGS=10V,ID=20A	--	5.5	7	mΩ
$R_{DS(ON)}$	Drain-Source On-State Resistance (Note3)	VGS=4.5V,ID=20A	--	9	12.5	mΩ
Dynamic Electrical Characteristics @ T_J = 25°C (unless otherwise stated)						
C_{iss}	Input Capacitance	VDS=20V,VGS=0V, f=1MHz	--	2400	--	pF
C_{oss}	Output Capacitance		--	192	--	pF
C_{rss}	Reverse Transfer Capacitance		--	165	--	pF
Q_g	Total Gate Charge	VDS=20V,ID=30A VGS=10V	--	37	--	nC
Q_{gs}	Gate-Source Charge		--	6	--	nC
Q_{gd}	Gate-Drain Charge		--	7	--	nC
Switching Characteristics note B						
$t_{d(on)}$	Turn-on Delay Time	VDD=20V ID=30A, RGEN=3Ω, RL=1Ω, VGS=10V	--	12	--	nS
t_r	Turn-on Rise Time		--	12	--	nS
$t_{d(off)}$	Turn-Off Delay Time		--	38	--	nS
t_f	Turn-Off Fall Time		--	9	--	nS
Source- Drain Diode Characteristics@ TJ = 25°C (unless otherwise stated)						
V_{SD}	Forward on voltage	IS=20A,VGS=0V	--	--	1.2	V

Note :
1. Repetitive Rating: Pulse Width Limited by Maximum Junction Temperature
2. EAS condition: TJ=25℃ , VDD=20V, VG=10V,RG=25Ω L=0.5mH, IAS=18A
3. Pulse Test: Pulse Width≤300μs, Duty Cycle≤0.5%

Typical characteristic curve:

Figure1: Output Characteristics



Figure 2: Typical Transfer Characteristics



Figure 3: On-resistance vs. Drain Current



Figure 4: Body Diode Characteristics



Figure 5: Gate Charge Characteristics



Figure 6: Capacitance Characteristics



Figure 7: Normalized Breakdown Voltage vs. Junction Temperature



Figure 8: Normalized on Resistance vs. Junction Temperature



Figure 9: Maximum Safe Operating Area



Figure 10: Maximum Continuous Drain Current vs. Case Temperature



Figure.11: Maximum Effective Transient Thermal Impedance, Junction-to-Case



Test Circuit and Waveform



Figure1:Gate Charge Test Circuit & Waveform



Figure 2: Resistive Switching Test Circuit & Waveforms



Figure 3:Unclamped Inductive Switching Test Circuit & Waveforms

ENTEGRECİ

Bu belge www.entegreci.com üzerinden sunulmaktadır.

Elektronik komponent tedarikinde Entegreci

Entegreci, Eskişehir merkezli, Türkiye geneline satış yapan bir elektronik komponent mağazasıdır. Entegreler (IC), mikrodenetleyiciler, transistörler, diyotlar, pasif elemanlar, konnektörler, modüller ve geliştirme kartları tek adetten seri üretim adetlerine kadar satılır. Ürün sayfalarında güncel stok durumunu, fiyatı ve datasheet bağlantısını bulabilirsiniz.

Parça koduyla arama

Üretici parça numarasını yazın; stok ve fiyatı hemen görün.

www.entegreci.com

Ürün kategorileri

Entegreden kapasitöre tüm elektronik komponent kategorileri.

Kategorilere göz atın

Üreticiler

Aradığınız üreticinin ürünlerini tek sayfada inceleyin.

Üreticileri görün

Toplu alım ve teklif

Listede olmayan ya da yüksek adetli parçalar için teklif isteyin.

Teklif isteyin

www.entegreci.com | **destek@entegreci.com** | **0850 305 90 34**

Entegreci is an online electronic components store based in Türkiye. Search by manufacturer part number to see stock, prices and datasheets for integrated circuits, microcontrollers, transistors, passive components and connectors, or request a quote for parts that are not listed.

Bu sayfa Entegreci tarafından eklenmiştir. Belgenin önceki sayfaları asıl yayıncısına aittir ve içeriği değiştirilmemiştir; en güncel sürüm için belgenin yayıncısına başvurun.