SK3402

N-Channel Enhancement Mode MOSFET

Feature

30V/4.2A $R_{DS(ON)}$ = 50mΩ(MAX) @V_{GS} = 10V.

$R_{DS(ON)}$ =60mΩ(MAX) @V_{GS} = 4.5V.

Super High dense cell design for extremely low $R_{DS(ON)}$.

Reliable and Rugged.

SC-59 for Surface Mount Package.



SC-59



Marking: A2PA

Applications

- Power Management

  Portable Equipment and Battery Powered Systems.

Absolute Maximum Ratings

T_A=25℃Unless Otherwise noted

Parameter	Symbol	Limit	Units
Drain-Source Voltage	V_{DS}	30	V
Gate-Source Voltage	V_{GS}	±12	V
Drain Current-Continuous	I_D	4.2	A

Electrical Characteristics

T_A=25℃Unless Otherwise noted

Parameter	Symbol	Test Conditions	Min	Typ.	Max	Units
Off Characteristics						
Drain to Source Breakdown Voltage	BVDSS	VGS=0V, ID=250μA	30	-	-	V
Zero-Gate Voltage Drain Current	IDSS	VDS=30V, VGS=0V	-	-	1	μA
Gate Body Leakage Current, Forward	IGSSF	VGS=12V, VDS=0V	-	-	100	nA
Gate Body Leakage Current, Reverse	IGSSR	VGS=-12V, VDS=0V	-	-	-100	nA
On Characteristics						
Gate Threshold Voltage	VGS(th)	VGS= VDS, ID=250μA	0.6	-	2.5	V
Static Drain-source On-Resistance	RDS(ON)	VGS =10V, ID =4A	-	48	50	mΩ
		VGS =4.5V, ID =3A	-	55	60	mΩ
		VGS =2.5V, ID =2A	-	60	65	mΩ
Drain-Source Diode Characteristics and Maximum Ratings						
Drain-Source Diode Forward Voltage	VSD	VGS =0V, IS=1.25A			1.2	V

Dynamic						
Q_g	Total Gate Charge	V_{DS}=15V,V_{GS}=10V,I_D=2A		8.5	12	nC
Q_{gs}	Gate-Source Charge			1.1		
Q_{gd}	Gate-Drain Charge			1.8		
t_{on}	Turn-on Time	V_{DD}=15V,I_D=2A,V_{GS}=10V,R_G=6Ω			40	ns
$t_{d(ON)}$	Turn-on Delay time			11		
t_r	Turn-on Rise Time			17		
$T_{d(off)}$	Turn-off Delay Time			37		
t_f	Turn-off Fall Time			20		
t_{off}	Turn-off Time				60	

Typical Characteristics





Figure 1．Output Characteristics

Figure 2．Transfer Characteristics

Typical Characteristics





Figure 3．Gate Threshold Variation with Temperature

Figure 4．On-Resistance Variation with Temperature



Figure 5 . On-Resistance vs. Gate-to-Source Voltage



Figure 6 . Source-Drain Diode Forward Voltage

Package Outline Dimensions (UNIT: mm)



ENTEGRECİ

Bu belge www.entegreci.com üzerinden sunulmaktadır.

Elektronik komponent tedarikinde Entegreci

Entegreci, Eskişehir merkezli, Türkiye geneline satış yapan bir elektronik komponent mağazasıdır. Entegreler (IC), mikrodenetleyiciler, transistörler, diyotlar, pasif elemanlar, konnektörler, modüller ve geliştirme kartları tek adetten seri üretim adetlerine kadar satılır. Ürün sayfalarında güncel stok durumunu, fiyatı ve datasheet bağlantısını bulabilirsiniz.

Parça koduyla arama

Üretici parça numarasını yazın; stok ve fiyatı hemen görün.

www.entegreci.com

Ürün kategorileri

Entegreden kapasitöre tüm elektronik komponent kategorileri.

Kategorilere göz atın

Üreticiler

Aradığınız üreticinin ürünlerini tek sayfada inceleyin.

Üreticileri görün

Toplu alım ve teklif

Listede olmayan ya da yüksek adetli parçalar için teklif isteyin.

Teklif isteyin

www.entegreci.com | **destek@entegreci.com** | **0850 305 90 34**

Entegreci is an online electronic components store based in Türkiye. Search by manufacturer part number to see stock, prices and datasheets for integrated circuits, microcontrollers, transistors, passive components and connectors, or request a quote for parts that are not listed.

Bu sayfa Entegreci tarafından eklenmiştir. Belgenin önceki sayfaları asıl yayıncısına aittir ve içeriği değiştirilmemiştir; en güncel sürüm için belgenin yayıncısına başvurun.