60V N-CHANNEL SELF PROTECTED ENHANCEMENT MODE INTELLIFET MOSFET WITH PROGRAMMABLE CURRENT LIMIT

Product Summary

- Continuous Drain Source Voltage V_{DS} = 60V
- On-State Resistance: 500mΩ
- Nominal Load Current (V_{IN} = 5V): 1.4A
- Clamping Energy: 550mJ

Description

The ZXMS6003G is a self-protected low-side IntelliFET™ MOSFET. It features monolithic overtemperature, overcurrent, overvoltage (active clamp), and ESD protected logic level functionality. It is intended as a general purpose switch with status indication and programmable current limit.

Applications

- Especially Suited for Loads with a High In-Rush Current Such as Lamps and Motors
- All Types of Resistive, Inductive, and Capacitive Loads in Switching Applications
- µC Compatible Power Switch for 12V and 24V DC Applications
- Replaces Electromechanical Relays and Discrete Circuits
- Linear Mode Capability - The current-limiting protection circuitry is designed to deactivate at low V_{DS} in order not to compromise the load current during normal operation. The design max. DC operating current is therefore determined by the thermal capability of the package/board combination rather than by the protection circuitry.
  Note: This does not compromise the product's ability to self-protect during short-circuit load conditions.
- Current Limit is Programmable via an External Resistor R_{PROG} Connected Between Status and IN pins
- Status Pin Voltage Reflects the Gate Drive Applied Internally to the Power MOSFET
- With V_{IN} = 5V and R_{PROG} = 24kΩ:
  - Status Voltage: 5V Indicates Normal Operation
  - Status Voltage: 2V to 3V Indicates the Device is in Current-Limiting Mode
  - Status Voltage <1V Indicates the Device is in Thermal Shutdown

Features and Benefits

- Current Limit Programmable via External Resistor
- Status Pin (Analog Status Indication)
- Logic Level Input
- Short-Circuit Protection with Auto Restart
- Overvoltage Protection (Active Clamp)
- Thermal Shutdown with Auto Restart
- Overcurrent Protection
- Input Protection (ESD)
- Load Dump Protection (Actively Protects Load)
- High Continuous Current Rating
- **Lead-Free Finish; RoHS Compliant (Notes 1 & 2)**
- **Halogen and Antimony Free. "Green" Device (Note 3)**

Mechanical Data

- Case: SOT223 (Type DN)
- Case Material: Molded Plastic, "Green" Molding Compound. UL Flammability Classification Rating 94V-0
- Moisture Sensitivity: Level 1 per J-STD-020
- Terminals: Matte Tin Finish (e3)
- Weight: 0.112 grams (Approximate)

SOT223 (Type DN)



Top View

Note: R_{PROG} must be connected between the Status and IN pins.



Top view

Notes:
1. EU Directive 2002/95/EC (RoHS), 2011/65/EU (RoHS 2) & 2015/863/EU (RoHS 3) compliant. All applicable RoHS exemptions applied.
2. See https://www.diodes.com/quality/lead-free/ for more information about Diodes Incorporated's definitions of Halogen- and Antimony-free, "Green" and Lead-free.
3. Halogen- and Antimony-free "Green" products are defined as those which contain <900ppm bromine, <900ppm chlorine (<1500ppm total Br + Cl) and <1000ppm antimony compounds.

IntelliFET is a trademark of Diodes Incorporated.

© Diodes Incorporated

Ordering Information (Note 4)

Part Number	Marking	Reel Size (inches)	Tape Width (mm)	Quantity per Reel
ZXMS6003GTA	ZXMS6003	7	12	1000 Units

Note: 4. For packaging details, go to our website at https://www.diodes.com/design/support/packaging/diodes-packaging/.

Marking Information



ZXMS6003 = Product Type Marking Code
YWW = Date Code Marking
Y or $\overline{Y}$ = Last Digit of Year (ex: 8 = 2018)
WW or $\overline{WW}$ = Week Code (01 to 53)

Functional Block Diagram



© Diodes Incorporated

Absolute Maximum Ratings (@T_A = +25°C, unless otherwise stated.)

Parameter	Symbol	Limit	Unit
Continuous Drain-Source Voltage	V_{DS}	60	V
Drain-Source Voltage for Short-Circuit Protection V_{IN} = 5V (Note 5)	$V_{DS(SC)}$	36	V
Drain-Source Voltage for Short-Circuit Protection V_{IN} = 10V (Note 5)	$V_{DS(SC)}$	20	V
Continuous Input Voltage	V_{IN}	-0.2 to +10	V
Peak Input Voltage	V_{IN}	-0.2 to +20	V
Operating Temperature Range	T_J	-40 to +150	°C
Storage Temperature Range	T_{STG}	-55 to +150	°C
Power Dissipation at @T_A = +25°C (Note 6)	P_D	2.5	W
Continuous Drain Current @V_{IN} = 10V; T_A = +25°C (Note 6)	I_D	1.6	A
Continuous Drain Current @V_{IN} = 5V; T_A = +25°C (Note 6)	I_D	1.4	A
Continuous Source Current (Body Diode) (Note 6)	I_S	3	A
Pulsed Source Current (Body Diode) (Note 7)	I_S	8	A
Unclamped Single Pulse Inductive Energy	E_{AS}	550	mJ
Load Dump Protection	$V_{LOADDUMP}$	80	V
Electrostatic Discharge (Human Body Model)	V_{ESD}	4000	V
DIN Humidity Category, DIN 40 040	—	E	—
IEC Climatic Category, DIN IEC 68-1	—	40/150/56	—

Thermal Resistance (@T_A = +25°C, unless otherwise stated.)

Parameter	Symbol	Value	Unit
Junction to Ambient (Note 6)	$R_{\Theta JA}$	50	°C/W
Junction to Ambient (Note 7)	$R_{\Theta JA}$	28	°C/W

Notes: 5. For $I_{D(LIM)}$ < 1.2A (see safe operating area curve).
6. For a device surface mounted on 50mm × 50mm × 1.6mm FR-4 board with a high coverage of single sided 2oz weight copper.
7. For a device surface mounted on FR-4 board and measured at t < = 10s.

© Diodes Incorporated

Thermal Characteristics



Safe Operating Area



Safe Operating Area



Transient Thermal Impedance



Pulse Power Dissipation



Derating Curve

© Diodes Incorporated

Electrical Characteristics (@T_A = +25°C, unless otherwise stated.)

Parameter	Symbol	Min	Typ	Max	Unit	Conditions
Static Characteristics						
Drain-Source Clamp Voltage	$V_{DS(AZ)}$	60	70	75	V	I_D = 10mA
Off State Drain Current	I_{DSS}	—	0.1	3	µA	V_{DS} = 12V, V_{IN} = 0V
Off State Drain Current	I_{DSS}	—	3	15	µA	V_{DS} = 32V, V_{IN} = 0V
Input Threshold Voltage (Note 8)	$V_{IN(TH)}$	1	2.1	—	V	V_{DS} = V_{GS}, I_D = 1mA
Input Current	I_{IN}	—	0.7	1.2	mA	V_{IN} = 5V
Input Current	I_{IN}	—	1.5	2.7	mA	V_{IN} = 7V
Input Current	I_{IN}	—	4	7	mA	V_{IN} = 10V
Static Drain-Source On-State Resistance	$R_{DS(ON)}$	—	520	675	mΩ	V_{IN} = 5V, I_D = 0.2A
Static Drain-Source On-State Resistance	$R_{DS(ON)}$	—	385	500	mΩ	V_{IN} = 10V, I_D = 0.5A
Current Limit (Note 9)	$I_{D(LIM)}$	0.2	0.3	0.4	A	V_{IN} = 5V, V_{DS} = 10V, R_{PROG} = 20k
Current Limit (Note 9)	$I_{D(LIM)}$	0.7	0.9	1.2	A	V_{IN} = 10V, V_{DS} = 10V, R_{PROG} = 20k
Dynamic Characteristics						
Turn-On Time (V_{IN} to 90% I_D)	t_{ON}	—	3	—	µs	R_{PROG} = 20k, R_L = 22Ω, V_{IN} = 0 to 10V, V_{DD} = 12V
Turn-Off Time (V_{IN} to 90% I_D)	t_{OFF}	—	13	—	µs	R_{PROG} = 20k, R_L = 22Ω, V_{IN} = 10V to 0V, V_{DD} = 12V
Slew Rate On (70 to 50% V_{DD})	dV_{DS}/dt_{ON}	—	8	—	V/µs	R_{PROG}= 20k, R_L = 22Ω, V_{IN} = 0 to 10V, V_{DD} = 12V
Slew Rate Off (50 to 70% V_{DD})	dV_{DS}/dt_{ON}	—	3.2	—	V/µs	R_{PROG} = 20k, R_L = 22Ω, V_{IN} = 10V to 0V, V_{DD} = 12V
Protection Functions (Note 10)						
Required Input Voltage for Over-Temperature Protection	V_{PROT}	4.5	—	—	V	—
Thermal Overload Trip Temperature	T_{JT}	+150	+175	—	°C	—
Thermal Hysteresis	—	—	+1	—	°C	—
Unclamped Single Pulse Inductive Energy T_J = +25°C	E_{AS}	550	—	—	mJ	$I_{D(ISO)}$ = 0.7A, V_{DD} = 32V
Unclamped Single Pulse Inductive Energy T_J = +150°C	E_{AS}	200	—	—	mJ	$I_{D(ISO)}$ = 0.7A, V_{DD} = 32V
Status Flag						
Normal Operation	V_{STATUS}	—	4.95	—	V	V_{IN} = 5V
Current Limit Operating	V_{STATUS}	—	2.5	—	V	V_{IN} = 5V
Thermal Shutdown Activated	V_{STATUS}	—	0.2	1	V	V_{IN} = 5V
Normal Operation	V_{STATUS}	—	8	—	V	V_{IN} = 10V
Current Limit Operation	V_{STATUS}	—	3	—	V	V_{IN} = 10V
Thermal Shutdown Activated	V_{STATUS}	—	0.35	1	V	V_{IN} = 10V
Inverse Diode						
Source Drain Voltage	V_{SD}	—	—	1	V	V_{IN} = 0V, -I_D = 1.4A

Notes:
8. Protection features may operate outside spec for V_{IN} < 4.5V.
9. The drain current is limited to a reduced value when V_{DS} exceeds a safe level.
10. Integrated protection functions are designed to prevent IC destruction under fault conditions described in the datasheet. Fault conditions are considered as “outside” normal operating range. Protection functions are not designed for continuous, repetitive operation.

© Diodes Incorporated

Typical Characteristics



Typical Output Characteristic



On-state Resistance vs Temperature



On-Resistance vs Input Voltage



Threshold Voltage vs Temperature



Source-Drain Diode Forward Voltage



Switching Speed

© Diodes Incorporated

Typical Characteristics (cont.)

Current Limiting and Over Temp Shutdown Status Indication at Vin=5V



Current Limiting and Over Temp Shutdown Status Indication at Vin=10V





VStatus vs Rprog @ Vin=5V



VStatus vs Rprog @ Vin=10V



Current Limit vs Rprog



VStatus vs Vin

© Diodes Incorporated

Package Outline Dimensions

Please see http://www.diodes.com/package-outlines.html for the latest version.

SOT223 (Type DN)



SOT223 (Type DN)			
Dim	**Min**	**Max**	**Typ**
A	--	1.70	--
A1	0.01	0.15	--
A2	1.50	1.68	1.60
b	0.60	0.80	0.70
b2	2.90	3.10	--
c	0.20	0.32	--
D	6.30	6.70	--
E	6.70	7.30	--
E1	3.30	3.70	--
e	--	--	2.30
e1	--	--	4.60
L	0.85	--	--
All Dimensions in mm			

Suggested Pad Layout

Please see http://www.diodes.com/package-outlines.html for the latest version.

SOT223 (Type DN)



Dimensions	Value (in mm)
C	2.30
C1	6.40
X	1.20
X1	3.30
Y	1.60
Y1	1.60
Y2	8.00

© Diodes Incorporated

IMPORTANT NOTICE

DIODES INCORPORATED MAKES NO WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, WITH REGARDS TO THIS DOCUMENT, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE (AND THEIR EQUIVALENTS UNDER THE LAWS OF ANY JURISDICTION).

Diodes Incorporated and its subsidiaries reserve the right to make modifications, enhancements, improvements, corrections or other changes without further notice to this document and any product described herein. Diodes Incorporated does not assume any liability arising out of the application or use of this document or any product described herein; neither does Diodes Incorporated convey any license under its patent or trademark rights, nor the rights of others. Any Customer or user of this document or products described herein in such applications shall assume all risks of such use and will agree to hold Diodes Incorporated and all the companies whose products are represented on Diodes Incorporated website, harmless against all damages.

Diodes Incorporated does not warrant or accept any liability whatsoever in respect of any products purchased through unauthorized sales channel. Should Customers purchase or use Diodes Incorporated products for any unintended or unauthorized application, Customers shall indemnify and hold Diodes Incorporated and its representatives harmless against all claims, damages, expenses, and attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized application.

Products described herein may be covered by one or more United States, international or foreign patents pending. Product names and markings noted herein may also be covered by one or more United States, international or foreign trademarks.

This document is written in English but may be translated into multiple languages for reference. Only the English version of this document is the final and determinative format released by Diodes Incorporated.

LIFE SUPPORT

Diodes Incorporated products are specifically not authorized for use as critical components in life support devices or systems without the express written approval of the Chief Executive Officer of Diodes Incorporated. As used herein:

A. Life support devices or systems are devices or systems which:

1. are intended to implant into the body, or

2. support or sustain life and whose failure to perform when properly used in accordance with instructions for use provided in the labeling can be reasonably expected to result in significant injury to the user.

B. A critical component is any component in a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or to affect its safety or effectiveness.

Customers represent that they have all necessary expertise in the safety and regulatory ramifications of their life support devices or systems, and acknowledge and agree that they are solely responsible for all legal, regulatory and safety-related requirements concerning their products and any use of Diodes Incorporated products in such safety-critical, life support devices or systems, notwithstanding any devices- or systems-related information or support that may be provided by Diodes Incorporated. Further, Customers must fully indemnify Diodes Incorporated and its representatives against any damages arising out of the use of Diodes Incorporated products in such safety-critical, life support devices or systems.

Copyright © 2019, Diodes Incorporated

www.diodes.com

ENTEGRECİ

Bu belge www.entegreci.com üzerinden sunulmaktadır.

Elektronik komponent tedarikinde Entegreci

Entegreci, Eskişehir merkezli, Türkiye geneline satış yapan bir elektronik komponent mağazasıdır. Entegreler (IC), mikrodenetleyiciler, transistörler, diyotlar, pasif elemanlar, konnektörler, modüller ve geliştirme kartları tek adetten seri üretim adetlerine kadar satılır. Ürün sayfalarında güncel stok durumunu, fiyatı ve datasheet bağlantısını bulabilirsiniz.

Parça koduyla arama

Üretici parça numarasını yazın; stok ve fiyatı hemen görün.

www.entegreci.com

Ürün kategorileri

Entegreden kapasitöre tüm elektronik komponent kategorileri.

Kategorilere göz atın

Üreticiler

Aradığınız üreticinin ürünlerini tek sayfada inceleyin.

Üreticileri görün

Toplu alım ve teklif

Listede olmayan ya da yüksek adetli parçalar için teklif isteyin.

Teklif isteyin

www.entegreci.com | **destek@entegreci.com** | **0850 305 90 34**

Entegreci is an online electronic components store based in Türkiye. Search by manufacturer part number to see stock, prices and datasheets for integrated circuits, microcontrollers, transistors, passive components and connectors, or request a quote for parts that are not listed.

Bu sayfa Entegreci tarafından eklenmiştir. Belgenin önceki sayfaları asıl yayıncısına aittir ve içeriği değiştirilmemiştir; en güncel sürüm için belgenin yayıncısına başvurun.