Three Level NPC Q2Pack Module

NXH400N100L4Q2F2SG, NXH400N100L4Q2F2PG

The NXH400N100L4Q2 is a power module containing a I−type neutral point clamped three−level inverter. The integrated field stop trench IGBTs and FRDs provide lower conduction losses and switching losses, enabling designers to achieve high efficiency and superior reliability.

Features

- Neutral Point Clamped Three−level Inverter Module
- Extreme Efficient Trench with Field Stop Technology
- Low Inductive Layout
- Low Package Height
- Thermistor

Typical Applications

- Solar Inverters
- Energy Storage System
- Uninterruptable Power Supplies Systems



Figure 1. NXH400N100L4Q2F2 Schematic Diagram



Q2PACK PRESS FIT PINS
PIM48, 93x47
CASE 180CR



Q2PACK SOLDER PINS
PIM48, 93x47
CASE 180BL

MARKING DIAGRAM



NXH400N100L4Q2F2xG	= Specific Device Code
x	= P or S
G	= Pb−Free Package
AT	= Assembly & Test Site Code
YYWW	= Year and Work Week Code

PIN CONNECTIONS



ORDERING INFORMATION

See detailed ordering and shipping information on page 5 of this data sheet.

© Semiconductor Components Industries, LLC, 2022

Table 1. ABSOLUTE MAXIMUM RATINGS (T_J = 25°C unless otherwise noted) (Note 1)

Rating	Symbol	Value	Unit
IGBT (T1, T2, T3, T4)			
Collector-Emitter Voltage	V_{CES}	1000	V
Gate-Emitter Voltage Positive Transient Gate−Emitter Voltage (T_{pulse} = 5 μs, D < 0.10)	V_{GE}	±20 30	V
Continuous Collector Current @ T_C = 80°C	I_C	360	A
Pulsed Peak Collector Current @ T_C = 80°C (T_J = 175°C)	$I_{C(Pulse)}$	1080	A
Maximum Power Dissipation (T_J = 175°C)	P_{tot}	980	W
Minimum Operating Junction Temperature	T_{JMIN}	−40	°C
Maximum Operating Junction Temperature (Note 2)	T_{JMAX}	175	°C
IGBT INVERSE DIODE (D1, D2, D3, D4)			
Peak Repetitive Reverse Voltage	V_{RRM}	1000	V
Continuous Forward Current @ T_C = 80°C	I_F	276	A
Repetitive Peak Forward Current (T_J = 175°C)	I_{FRM}	828	A
Maximum Power Dissipation (T_J = 175°C)	P_{tot}	680	W
Minimum Operating Junction Temperature	T_{JMIN}	−40	°C
Maximum Operating Junction Temperature	T_{JMAX}	175	°C
NEUTRAL POINT DIODE (D5, D6)			
Peak Repetitive Reverse Voltage	V_{RRM}	1000	V
Continuous Forward Current @ T_C = 80°C	I_F	291	A
Repetitive Peak Forward Current (T_J = 175°C)	I_{FRM}	873	A
Maximum Power Dissipation (T_J = 175°C)	P_{tot}	734	W
Minimum Operating Junction Temperature	T_{JMIN}	−40	°C
Maximum Operating Junction Temperature	T_{JMAX}	175	°C

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

Table 2. THERMAL AND INSULATION PROPERTIES (T_J = 25°C unless otherwise noted) (Note 1)

Rating	Symbol	Value	Unit
THERMAL PROPERTIES			
Operating Temperature under Switching Condition	T_{VJOP}	−40 to 150	°C
Storage Temperature Range	T_{stg}	−40 to 125	°C
INSULATION PROPERTIES			
Isolation Test Voltage, t = 1 s, 50 Hz (Note 2)	V_{is}	4000	V_{RMS}
Creepage Distance		12.7	mm
Comparative Tracking Index	CTI	>600	

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

1. Refer to ELECTRICAL CHARACTERISTICS, RECOMMENDED OPERATING RANGES and/or APPLICATION INFORMATION for Safe Operating parameters.
2. 4000 VAC_{RMS} for 1 second duration is equivalent to 3333 VAC_{RMS} for 1 minute duration.

Share Feedback
Your Opinion Matters

ELECTRICAL CHARACTERISTICS (T_J = 25°C unless otherwise noted)

Characteristic	Symbol	Test Conditions	Min	Typ	Max	Unit
OUTER IGBT (T1, T4) CHARACTERISTICS						
Collector-Emitter Cutoff Current	I_{CES}	V_{GE} = 0 V, V_{CE} = 1000 V	–	–	25	μA
Collector-Emitter Saturation Voltage	$V_{CE(sat)}$	V_{GE} = 15 V, I_C = 400 A, T_J = 25°C	–	1.65	2.2	V
		V_{GE} = 15 V, I_C = 400 A, T_J = 150°C	–	2.1	–	
Gate-Emitter Threshold Voltage	$V_{GE(TH)}$	V_{GE} = V_{CE}, I_C = 400 mA	3.6	4.9	6.2	V
Gate Leakage Current	I_{GES}	V_{GE} = ±20 V, V_{CE} = 0 V	–	–	±1.0	μA
Turn-on Delay Time	$t_{d(on)}$	T_J = 25°C V_{CE} = 600 V, I_C = 200 A V_{GE} = −9 V, 15 V, R_{Gon} = 9 Ω, R_{Goff} = 19 Ω	–	170.46	–	ns
Rise Time	t_r		–	54.38	–	
Turn-off Delay Time	$t_{d(off)}$		–	696.63	–	
Fall Time	t_f		–	12.91	–	
Turn-on Switching Loss per Pulse	E_{on}		–	8.96	–	mJ
Turn-off Switching Loss per Pulse	E_{off}		–	6	–	
Turn-on Delay Time	$t_{d(on)}$	T_J = 125°C V_{CE} = 600 V, I_C = 200 A V_{GE} = −9 V, 15 V, R_{Gon} = 9 Ω, R_{Goff} = 19 Ω	–	163.09	–	ns
Rise Time	t_r		–	61.38	–	
Turn-off Delay Time	$t_{d(off)}$		–	771.31	–	
Fall Time	t_f		–	18.23	–	
Turn-on Switching Loss per Pulse	E_{on}		–	14.54	–	mJ
Turn-off Switching Loss per Pulse	E_{off}		–	9.8	–	
Input Capacitance	C_{ies}	V_{CE} = 20 V, V_{GE} = 0 V, f = 1 MHz	–	26060	–	pF
Output Capacitance	C_{oes}		–	1182	–	
Reverse Transfer Capacitance	C_{res}		–	146	–	
Total Gate Charge	Q_g	V_{CE} = 600 V, I_C = 300 A, V_{GE} = −15 V~15 V	–	1410	–	nC
Thermal Resistance – Chip-to-Heatsink	R_{thJH}	Thermal grease, Thickness = 100 μm ±2% λ = 2.9 W/mK	–	0.17	–	K/W
Thermal Resistance – Chip-to-Case	R_{thJC}		–	0.0969	–	K/W
NEUTRAL POINT DIODE (D5, D6) CHARACTERISTICS						
Diode Forward Voltage	V_F	I_F = 225 A, T_J = 25°C	–	2.1	2.7	V
		I_F = 225 A, T_J = 150°C	–	1.9	–	
Reverse Recovery Time	t_{rr}	T_J = 25°C V_{CE} = 600 V, I_C = 200 A V_{GE} = −9 V, 15 V, R_G = 9 Ω	–	91.65	–	ns
Reverse Recovery Charge	Q_{rr}		–	5109	–	nC
Peak Reverse Recovery Current	I_{RRM}		–	117.19	–	A
Peak Rate of Fall of Recovery Current	di/dt		–	3.02	–	A/ns
Reverse Recovery Energy	E_{rr}		–	1504	–	μJ
Reverse Recovery Time	t_{rr}	T_J = 125°C V_{CE} = 600 V, I_C = 200 A V_{GE} = −9 V, 15 V, R_G = 9 Ω	–	168.8	–	ns
Reverse Recovery Charge	Q_{rr}		–	15979	–	nC
Peak Reverse Recovery Current	I_{RRM}		–	183.14	–	A
Peak Rate of Fall of Recovery Current	di/dt		–	2.64	–	A/ns
Reverse Recovery Energy	E_{rr}		–	5463	–	μJ
Thermal Resistance – Chip-to-Heatsink	R_{thJH}	Thermal grease, Thickness = 100 μm ±2% λ = 2.9 W/mK	–	0.21	–	K/W
Thermal Resistance – Chip-to-Case	R_{thJC}		–	0.1295	–	K/W

Share Feedback
Your Opinion Matters

ELECTRICAL CHARACTERISTICS (T_J = 25°C unless otherwise noted) (continued)

Characteristic	Symbol	Test Conditions	Min	Typ	Max	Unit
INNER IGBT (T2, T3) CHARACTERISTICS						
Collector−Emitter Cutoff Current	I_{CES}	V_{GE} = 0 V, V_{CE} = 1000 V	–	–	25	μA
Collector−Emitter Saturation Voltage	$V_{CE(sat)}$	V_{GE} = 15 V, I_C = 400 A, T_J = 25 °C	–	1.65	2.2	V
		V_{GE} = 15 V, I_C = 400 A, T_J = 150 °C	–	1.9	–	
Gate−Emitter Threshold Voltage	$V_{GE(TH)}$	V_{GE} = V_{CE}, I_C = 400mA	3.9	4.6	5.8	V
Gate Leakage Current	I_{GES}	V_{GE} = ±20 V, V_{CE} = 0 V	–	–	±1.0	μA
Turn−on Delay Time	$t_{d(on)}$	T_J = 25°C V_{CE} = 600 V, I_C = 200 A, V_{GE} = −9 V, 15 V, R_{Gon} = 9 Ω, R_{Goff} = 28 Ω	–	171.27	–	ns
Rise Time	t_r		–	52.54	–	
Turn−off Delay Time	$t_{d(off)}$		–	1153.7	–	
Fall Time	t_f		–	34.88	–	
Turn−on Switching Loss per Pulse	E_{on}		–	8.16	–	mJ
Turn off Switching Loss per Pulse	E_{off}		–	10.25	–	
Turn−on Delay Time	$t_{d(on)}$	T_J = 125°C V_{CE} = 600 V, I_C = 200 A, V_{GE} = −9 V, 15 V, R_{Gon} = 9 Ω, R_{Goff} = 28 Ω	–	160.21	–	ns
Rise Time	t_r		–	59.83	–	
Turn−off Delay Time	$t_{d(off)}$		–	1274.8	–	
Fall Time	t_f		–	26.46	–	
Turn−on Switching Loss per Pulse	E_{on}		–	12.37	–	mJ
Turn off Switching Loss per Pulse	E_{off}		–	13.42	–	
Input Capacitance	C_{ies}	V_{CE} = 20 V, V_{GE} = 0 V, f = 1 MHz	–	26060	–	pF
Output Capacitance	C_{oes}		–	1182	–	
Reverse Transfer Capacitance	C_{res}		–	146	–	
Total Gate Charge	Q_g	V_{CE} = 600 V, I_C = 300 A, V_{GE} = −15 V~15 V	–	1410	–	nC
Thermal Resistance − Chip−to−heatsink	R_{thJH}	Thermal grease, Thickness = 100 μm ±2% λ = 2.9 W/mK	–	0.17	–	K/W
Thermal Resistance − Chip−to−case	R_{thJC}		–	0.0969	–	K/W
IGBT INVERSE DIODE (D1, D2, D3, D4) CHARACTERISTICS						
Diode Forward Voltage	V_F	I_F = 225 A, T_J = 25°C	–	2.1	2.7	V
		I_F = 225 A, T_J = 150°C	–	1.9	–	
Reverse Recovery Time	t_{rr}	T_J = 25°C V_{CE} = 600 V, I_C = 200 A V_{GE} = −9 V, 15 V, R_G = 9 Ω	–	90.31	–	ns
Reverse Recovery Charge	Q_{rr}		–	5653	–	nC
Peak Reverse Recovery Current	I_{RRM}		–	123.4	–	A
Peak Rate of Fall of Recovery Current	di/dt		–	3.178	–	A/ns
Reverse Recovery Energy	E_{rr}		–	1860	–	μJ
Reverse Recovery Time	t_{rr}	T_J = 125°C V_{CE} = 600 V, I_C = 200 A V_{GE} = −9 V, 15 V, R_G = 9 Ω	–	167.18	–	ns
Reverse Recovery Charge	Q_{rr}		–	16627	–	nC
Peak Reverse Recovery Current	I_{RRM}		–	182.8	–	A
Peak Rate of Fall of Recovery Current	di/dt		–	2.734	–	A/ns
Reverse Recovery Energy	E_{rr}		–	6512	–	μJ
Thermal Resistance − Chip-to-Heatsink	R_{thJH}	Thermal grease, Thickness = 100 μm ±2% λ = 2.9 W/mK	–	0.22	–	K/W
Thermal Resistance − Chip-to-Case	R_{thJC}		–	0.1397	–	K/W
THERMISTOR CHARACTERISTICS						
Nominal Resistance	R_{25}	T = 25°C	–	5	–	kΩ
Nominal Resistance	R_{100}	T = 100°C	–	490.6	–	Ω

Share Feedback
Your Opinion Matters

ELECTRICAL CHARACTERISTICS (T_J = 25°C unless otherwise noted) (continued)

Characteristic	Symbol	Test Conditions	Min	Typ	Max	Unit
THERMISTOR CHARACTERISTICS						
Deviation of R25	ΔR/R		−1	–	1	%
Power Dissipation	P_D		–	5	–	mW
Power Dissipation Constant			–	1.3	–	mW/K
B-value		B (25/85), tolerance ±1%	–	3435	–	K

Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

ORDERING INFORMATION

Part Number	Marking	Package	Shipping
NXH400N100L4Q2F2PG	NXH400N100L4Q2F2PG	Q2PACK PRESS FIT PINS PIM48, 93x47 (Pb−Free and Halide−Free)	12 Units / Blister Tray
NXH400N100L4Q2F2SG	NXH400N100L4Q2F2SG	Q2PACK SOLDER PIN PIM48, 93x47 (Pb−Free and Halide−Free)	12 Units / Blister Tray

Share Feedback
Your Opinion Matters

TYPICAL CHARACTERISTICS – IGBT, INVERSE DIODE AND NEUTRAL POINT DIODE



Figure 2. Typical Output Characteristics – IGBT



Figure 3. Typical Output Characteristics – IGBT



Figure 4. Transfer Characteristics – IGBT



Figure 5. Saturation Voltage Characteristics



Figure 6. Inverse Diode Forward Characteristics



Figure 7. Buck Diode Forward Characteristics

Share Feedback
Your Opinion Matters

TYPICAL CHARACTERISTICS – OUTER IGBT (T1, T4)



Figure 8. Typical Turn ON Loss vs. IC



Figure 9. Typical Turn OFF Loss vs. IC



Figure 10. Typical Turn ON Loss vs. RG



Figure 11. Typical Turn OFF Loss vs. RG



Figure 12. Typical Turn−Off Switching Time vs. IC



Figure 13. Typical Turn−On Switching Time vs. IC

Share Feedback
Your Opinion Matters

TYPICAL CHARACTERISTICS – OUTER IGBT (T1,T4) (continued)



Figure 14. Typical Turn−Off Switching Time vs. RG



Figure 15. Typical Turn−On Switching Time vs. RG

Share Feedback
Your Opinion Matters

TYPICAL CHARACTERISTICS – INNER IGBT (T2, T3)



Figure 16. Typical Turn ON Loss vs. IC



Figure 17. Typical Turn OFF Loss vs. IC



Figure 18. Typical Turn ON Loss vs. RG



Figure 19. Typical Turn OFF Loss vs. RG



Figure 20. Typical Turn−Off Switching Time vs. IC



Figure 21. Typical Turn−On Switching Time vs. IC

Share Feedback
Your Opinion Matters

TYPICAL CHARACTERISTICS – INNER IGBT (T2, T3) (continued)



Figure 22. Typical Turn−Off Switching Time vs. RG



Figure 23. Typical Turn−On Switching Time vs. RG

Share Feedback
Your Opinion Matters

TYPICAL SWITCHING CHARACTERISTICS – NEUTRAL POINT DIODE



Figure 24. Typical Reverse Recovery Energy Loss vs. IC



Figure 25. Typical Reverse Recovery Energy Loss vs. Rg



Figure 26. Typical Reverse Recovery Time vs. IC



Figure 27. Typical Reverse Recovery Time vs. Rg



Figure 28. Typical Reverse Recovery Charge vs. IC



Figure 29. Typical Reverse Recovery Charge vs. Rg

Share Feedback
Your Opinion Matters

TYPICAL SWITCHING CHARACTERISTICS – NEUTRAL POINT DIODE (continued)



Figure 30. Typical Reverse Recovery Peak Current vs. IC



Figure 31. Typical Reverse Recovery Peak Current vs. Rg



Figure 32. Typical di/dt vs. IC



Figure 33. Typical di/dt vs. Rg

Share Feedback
Your Opinion Matters

TYPICAL CHARACTERISTICS – INVERSE DIODE



Figure 34. Typical Reverse Recovery Energy Loss vs. IC



Figure 35. Typical Reverse Recovery Energy Loss vs. Rg



Figure 36. Typical Reverse Recovery Time vs. IC



Figure 37. Typical Reverse Recovery Time vs. Rg



Figure 38. Typical Reverse Recovery Charge vs. IC



Figure 39. Typical Reverse Recovery Charge vs. Rg

Share Feedback
Your Opinion Matters

TYPICAL CHARACTERISTICS – INVERSE DIODE (continued)



Figure 40. Typical Reverse Recovery Peak Current vs. IC



Figure 41. Typical Reverse Recovery Peak Current vs. Rg



Figure 42. Typical di/dt vs. IC



Figure 43. Typical di/dt vs. Rg

Share Feedback
Your Opinion Matters

TYPICAL CHARACTERISTICS – IGBT, INVERSE DIODE AND NEUTRAL POINT DIODE



Figure 44. FBSOA – Outer IGBT



Figure 45. RBSOA – Outer IGBT



Figure 46. FBSOA – Inner IGBT



Figure 47. RBSOA – Inner IGBT



Figure 48. Gate Voltage vs. Gate Charge



Figure 49. Capacitance Charge

Share Feedback
Your Opinion Matters

TYPICAL CHARACTERISTICS – IGBT, INVERSE DIODE AND NEUTRAL POINT DIODE (continued)



Figure 50. Thermistor Characteristics



Figure 51. Transient Thermal Impedance – IGBT



Figure 52. Transient Thermal Impedance – Inverse Diode

Share Feedback
Your Opinion Matters

TYPICAL CHARACTERISTICS – IGBT, INVERSE DIODE AND NEUTRAL POINT DIODE (continued)



Figure 53. Transient Thermal Impedance – Neutral Point Diode

Share Feedback
Your Opinion Matters



PIM48, 93x47 (SOLDER PIN)
CASE 180BL
ISSUE A

DATE 08 DEC 2022



SIDE VIEW



TOP VIEW



END VIEW

NOTES:

1. DIMENSIONING AND TOLERANCING PER ASME Y14.5M, 2009
2. CONTROLLING DIMENSION : MILLIMETERS
3. DIMENSIONS b AND b1 APPLY TO THE PLATED TERMINALS AND ARE MEASURED AT DIMENSION A1
4. PIN POSITION TOLERANCE IS ± 0.4mm
5. PACKAGE MARKING IS LOCATED AS SHOWN ON THE SIDE OPPOSITE THE PACKAGE ORIENTATION FEATURES

	MILLIMETERS		
DIM	MIN.	NOM.	MAX.
A	16.80	17.20	17.60
A2	11.70	12.00	12.30
A3	4.40	4.70	5.00
A4	16.40	16.70	17.00
b	0.95	1.00	1.05
D	92.90	93.00	93.10
D1	104.45	104.75	105.05
D2	81.80	82.00	82.20
D3	106.90	107.20	107.50
E	46.70	47.00	47.30
E1	44.10	44.40	44.70
E2	38.80	39.00	39.20
P	5.40	5.50	5.60
P1	10.60	10.70	10.80
P2	1.80	2.00	2.20

S Pin position

Pin table				Pin table			
Pin	X	Y	Function	Pin	X	Y	Function
1	11.9	36.9	Phase1	25	70.9	0	DC-
2	14.9	36.9	Phase1	26	68.1	0	DC-
3	17.9	36.9	Phase1	27	65.3	0	DC-
4	20.9	36.9	Phase1	28	62.5	0	DC-
5	23.9	36.9	Phase1	29	56.9	0	DC-
6	26.9	36.9	Phase1	30	54.1	0	DC-
7	29.9	36.9	Phase1	31	51.3	0	DC-
8	32.9	36.9	Phase1	32	43.6	0	N2
9	38	36.9	Phase2	33	40.8	0	N2
10	41	36.9	Phase2	34	38	0	N2
11	44	36.9	Phase2	35	32.9	0	N1
12	47	36.9	Phase2	36	30	0	N1
13	50	36.9	Phase2	37	27.1	0	N1
14	53	36.9	Phase2	38	24.2	0	N1
15	56	36.9	Phase2	39	17.4	0	DC+
16	23.95	34.1	E2	40	14.5	0	DC+
17	20.15	33.9	G2	41	11.6	0	DC+
18	47	23.65	G3	42	8.7	0	DC+
19	47	20.65	E3	43	5.8	0	DC+
20	48.4	15.95	N	44	2.9	0	DC+
21	70.9	23.2	TH1	45	0	0	DC+
22	70.9	20.2	TH2	46	14.2	16	P
23	59.7	4.85	G4	47	14.2	13	E1
24	59.7	1.75	E4	48	11.2	13	G1

onsemi and onsemi are trademarks of Semiconductor Components Industries, LLC dba **onsemi** or its subsidiaries in the United States and/or other countries. **onsemi** reserves the right to make changes without further notice to any products herein. **onsemi** makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. **onsemi** does not convey any license under its patent rights nor the rights of others.

© Semiconductor Components Industries, LLC, 2022

PIM48, 93x47 (SOLDER PIN)
CASE 180BL
ISSUE A

DATE 08 DEC 2022



RECOMMENDED
MOUNTING PATTERN

* For additional Information on our Pb−Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

GENERIC
MARKING DIAGRAM*



FRONTSIDE MARKING

BACKSIDE MARKING

XXXXX = Specific Device Code
AT = Assembly & Test Site Code
YYWW = Year and Work Week Code

*This information is generic. Please refer to device data sheet for actual part marking. Pb−Free indicator, “G” or microdot “▪”, may or may not be present. Some products may not follow the Generic Marking.

DOCUMENT NUMBER:	**98AON47737H**	Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped “CONTROLLED COPY” in red.	
DESCRIPTION:	**PIM48, 93x47 (SOLDER PIN)**		**PAGE 2 OF 2**

onsemi and ONSEMI are trademarks of Semiconductor Components Industries, LLC dba **onsemi** or its subsidiaries in the United States and/or other countries. **onsemi** reserves the right to make changes without further notice to any products herein. **onsemi** makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. **onsemi** does not convey any license under its patent rights nor the rights of others.

© Semiconductor Components Industries, LLC, 2022



PIM48, 93x47 (PRESS−FIT PIN)
CASE 180CR
ISSUE A

DATE 08 DEC 2022



SIDE VIEW



TOP VIEW

END VIEW

NOTES:

1. DIMENSIONING AND TOLERANCING PER ASME Y14.5M, 2009
2. CONTROLLING DIMENSION : MILLIMETERS
3. DIMENSIONS b AND b1 APPLY TO THE PLATED TERMINALS AND ARE MEASURED AT DIMENSION A1
4. PIN POSITION TOLERANCE IS ± 0.4mm
5. PACKAGE MARKING IS LOCATED AS SHOWN ON THE SIDE OPPOSITE THE PACKAGE ORIENTATION FEATURES

	MILLIMETERS		
DIM	MIN.	NOM.	MAX.
A	16.90	17.30	17.70
A1	13.97	14.18	14.39
A2	11.70	12.00	12.30
A3	4.40	4.70	5.00
A4	16.40	16.70	17.00
b	1.61	1.66	1.71
b1	0.75	0.80	0.85
D	92.90	93.00	93.10
D1	104.45	104.75	105.05
D2	81.80	82.00	82.20
D3	106.90	107.20	107.50
E	46.70	47.00	47.30
E1	44.10	44.40	44.70
E2	38.80	39.00	39.20
P	5.40	5.50	5.60
P1	10.60	10.70	10.80
P2	1.80	2.00	2.20

S Pin position

Pin table				Pin table			
Pin	X	Y	Function	Pin	X	Y	Function
1	11.9	36.9	Phase1	25	70.9	0	DC-
2	14.9	36.9	Phase1	26	68.1	0	DC-
3	17.9	36.9	Phase1	27	65.3	0	DC-
4	20.9	36.9	Phase1	28	62.5	0	DC-
5	23.9	36.9	Phase1	29	56.9	0	DC-
6	26.9	36.9	Phase1	30	54.1	0	DC-
7	29.9	36.9	Phase1	31	51.3	0	DC-
8	32.9	36.9	Phase1	32	43.6	0	N2
9	38	36.9	Phase2	33	40.8	0	N2
10	41	36.9	Phase2	34	38	0	N2
11	44	36.9	Phase2	35	32.9	0	N1
12	47	36.9	Phase2	36	30	0	N1
13	50	36.9	Phase2	37	27.1	0	N1
14	53	36.9	Phase2	38	24.2	0	N1
15	56	36.9	Phase2	39	17.4	0	DC+
16	23.95	34.1	E2	40	14.5	0	DC+
17	20.15	33.9	G2	41	11.6	0	DC+
18	47	23.65	G3	42	8.7	0	DC+
19	47	20.65	E3	43	5.8	0	DC+
20	48.4	15.95	N	44	2.9	0	DC+
21	70.9	23.2	TH1	45	0	0	DC+
22	70.9	20.2	TH2	46	14.2	16	P
23	59.7	4.85	G4	47	14.2	13	E1
24	59.7	1.75	E4	48	11.2	13	G1

onsemi and ONSEMI are trademarks of Semiconductor Components Industries, LLC dba **onsemi** or its subsidiaries in the United States and/or other countries. **onsemi** reserves the right to make changes without further notice to any products herein. **onsemi** makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. **onsemi** does not convey any license under its patent rights nor the rights of others.

© Semiconductor Components Industries, LLC, 2022

PIM48, 93x47 (PRESS−FIT PIN)
CASE 180CR
ISSUE A

DATE 08 DEC 2022



RECOMMENDED
MOUNTING PATTERN

* For additional Information on our Pb−Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

GENERIC
MARKING DIAGRAM*



FRONTSIDE MARKING

BACKSIDE MARKING

XXXXX = Specific Device Code
AT = Assembly & Test Site Code
YYWW = Year and Work Week Code

*This information is generic. Please refer to device data sheet for actual part marking. Pb−Free indicator, “G” or microdot “▪”, may or may not be present. Some products may not follow the Generic Marking.

DOCUMENT NUMBER:	**98AON47745H**	Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped “CONTROLLED COPY” in red.	
DESCRIPTION:	**PIM48, 93x47 (PRESS−FIT PIN)**		**PAGE 2 OF 2**

onsemi and ONSEMI are trademarks of Semiconductor Components Industries, LLC dba **onsemi** or its subsidiaries in the United States and/or other countries. **onsemi** reserves the right to make changes without further notice to any products herein. **onsemi** makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. **onsemi** does not convey any license under its patent rights nor the rights of others.

© Semiconductor Components Industries, LLC, 2022

onsemi, , and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "**onsemi**" or its affiliates and/or subsidiaries in the United States and/or other countries. **onsemi** owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of **onsemi**'s product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent−Marking.pdf. **onsemi** reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as−is" and **onsemi** makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using **onsemi** products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by **onsemi**. "Typical" parameters which may be provided in **onsemi** data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. **onsemi** does not convey any license under any of its intellectual property rights nor the rights of others. **onsemi** products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use **onsemi** products for any such unintended or unauthorized application, Buyer shall indemnify and hold **onsemi** and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that **onsemi** was negligent regarding the design or manufacture of the part. **onsemi** is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

ADDITIONAL INFORMATION

TECHNICAL PUBLICATIONS:
Technical Library: www.onsemi.com/design/resources/technical−documentation
onsemi Website: www.onsemi.com

ONLINE SUPPORT: www.onsemi.com/support
For additional information, please contact your local Sales Representative at www.onsemi.com/support/sales

ENTEGRECİ

Bu belge www.entegreci.com üzerinden sunulmaktadır.

Elektronik komponent tedarikinde Entegreci

Entegreci, Eskişehir merkezli, Türkiye geneline satış yapan bir elektronik komponent mağazasıdır. Entegreler (IC), mikrodenetleyiciler, transistörler, diyotlar, pasif elemanlar, konnektörler, modüller ve geliştirme kartları tek adetten seri üretim adetlerine kadar satılır. Ürün sayfalarında güncel stok durumunu, fiyatı ve datasheet bağlantısını bulabilirsiniz.

Parça koduyla arama

Üretici parça numarasını yazın; stok ve fiyatı hemen görün.

www.entegreci.com

Ürün kategorileri

Entegreden kapasitöre tüm elektronik komponent kategorileri.

Kategorilere göz atın

Üreticiler

Aradığınız üreticinin ürünlerini tek sayfada inceleyin.

Üreticileri görün

Toplu alım ve teklif

Listede olmayan ya da yüksek adetli parçalar için teklif isteyin.

Teklif isteyin

www.entegreci.com | **destek@entegreci.com** | **0850 305 90 34**

Entegreci is an online electronic components store based in Türkiye. Search by manufacturer part number to see stock, prices and datasheets for integrated circuits, microcontrollers, transistors, passive components and connectors, or request a quote for parts that are not listed.

Bu sayfa Entegreci tarafından eklenmiştir. Belgenin önceki sayfaları asıl yayıncısına aittir ve içeriği değiştirilmemiştir; en güncel sürüm için belgenin yayıncısına başvurun.