Q1 3-Phase TNPC Module

NXH40T120L3Q1

The NXH40T120L2Q1 is a power module containing a three channel T−type neutral−point clamped (TNPC) circuit. Each channel has two 1200 V, 40 A IGBTs with inverse diodes and two 650 V, 25 A IGBTs with inverse diodes. The module contains an NTC thermistor.

Features

- Low Package Height
- Compact 82.5 mm x 37.4 mm x 12 mm Package
- Options with Press−fit Pins and Solder Pins
- Options with Pre−applied Thermal Interface Material (TIM) and without Pre−applied TIM
- Thermistor
- This Device is Pb−Free and is RoHS Compliant

Applications

- Solar Inverters
- UPS
- Energy Storage Systems



Figure 1. NXH40T120L3Q1 Schematic Diagram



Q1 3−TNPC
CASE 180AS
Solder pins follow similar pattern

MARKING DIAGRAM



NXH40T120L3Q1x	= Device Code
A	= Assembly Site Code
T	= Test Site Code
YYWW	= Year and Work Week Code
G	= Pb−Free Package

PIN CONNECTIONS



ORDERING INFORMATION

See detailed ordering and shipping information on page 5 of this data sheet.

© Semiconductor Components Industries, LLC, 2017

MAXIMUM RATINGS (Note 1)

Rating	Symbol	Value	Unit
IGBT (Q1, Q4, Q5, Q8, Q9, Q12)			
Collector – Emitter Voltage	V_{CES}	1200	V
Gate – Emitter Voltage	V_{GE}	±20	V
Continuous Collector Current @ T_C = 80°C (T_J = 175°C)	I_C	40	A
Pulsed Collector Current (T_J = 175°C)	I_{Cpulse}	120	A
Maximum Power Dissipation (T_J = 175°C)	P_{tot}	145	W
Minimum Operating Junction Temperature	T_{JMIN}	–40	°C
Maximum Operating Junction Temperature	T_{JMAX}	175	°C
DIODE (D1, D4, D5, D8, D9, D12)			
Peak Repetitive Reverse Voltage	V_{RRM}	1200	V
Continuous Forward Current @ T_C = 80°C (T_J = 175°C)	I_F	25	A
Repetitive Peak Forward Current (T_J = 175°C)	I_{FRM}	75	A
Maximum Power Dissipation (T_J = 175°C)	P_{tot}	55	W
Minimum Operating Junction Temperature	T_{JMIN}	– 40	°C
Maximum Operating Junction Temperature	T_{JMAX}	175	°C
IGBT+DIODE (Q2+D2, Q3+D3, Q6+D6, Q7+D7, Q10+D10, Q11+D11)			
Collector – Emitter Voltage	V_{CES}	650	V
Gate – Emitter Voltage	V_{GE}	±20	V
Continuous Collector Current @ T_C = 80°C (T_J = 175°C)	I_C	42	A
Pulsed Collector Current (T_J = 175°C)	I_{Cpulse}	126	A
Maximum Power Dissipation (T_J = 175°C)	P_{tot}	146	W
Minimum Operating Junction Temperature	T_{JMIN}	–40	°C
Maximum Operating Junction Temperature	T_{JMAX}	175	°C
THERMAL PROPERTIES			
Storage Temperature range	T_{stg}	– 40 to 150	°C
INSULATION PROPERTIES			
Isolation Test Voltage, t = 1 sec, 60 Hz	V_{is}	3000	V_{RMS}
Creepage Distance		12.7	mm

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

1. Refer to ELECTRICAL CHARACTERISTICS, RECOMMENDED OPERATING RANGES and/or APPLICATION INFORMATION for Safe Operating parameters.

RECOMMENDED OPERATING CONDITIONS

Rating	Symbol	Min	Max	Unit
Module Operating Junction Temperature	T_J	–40	150	°C

Functional operation above the stresses listed in the Recommended Operating Ranges is not implied. Extended exposure to stresses beyond the Recommended Operating Ranges limits may affect device reliability.

ELECTRICAL CHARACTERISTICS (T_J = 25°C Unless Otherwise Noted)

Parameter	Test Conditions	Symbol	Min.	Typ.	Max.	Unit
IGBT CHARACTERISTICS (Q1, Q4, Q5, Q8, Q9, Q12)						
Collector−Emitter Cutoff Current	V_{GE} = 0 V, V_{CE} = 1200 V	I_{CES}	–	–	400	μA
Collector−Emitter Saturation Voltage	V_{GE} = 15 V, I_C = 40 A, T_J = 25°C	$V_{CE(sat)}$	–	1.85	2.20	V
	V_{GE} = 15 V, I_C = 40 A , T_J = 150°C		–	2.25	–	
Gate−Emitter Threshold Voltage	V_{GE} = V_{CE}, I_C = 1.5 mA	$V_{GE(TH)}$	4.50	–	6.50	V
Gate Leakage Current	V_{GE} = 20 V, V_{CE} = 0 V	I_{GES}	–	–	800	nA
Turn−on Delay Time	T_J = 25°C V_{CE} = 350 V, I_C = 28 A, V_{GE} = ±15 V, R_G = 8 Ω	$t_{d(on)}$	–	63	–	ns
Rise Time		t_r	–	22	–	
Turn−off Delay Time		$t_{d(off)}$	–	199	–	
Fall Time		t_f	–	23	–	
Turn−on Switching Loss per Pulse		E_{on}	–	560	–	μJ
Turn off Switching Loss per Pulse		E_{off}	–	338	–	
Turn−on Delay Time	T_J = 125°C V_{CE} = 350 V, I_C = 28 A, V_{GE} = ±15 V, R_G = 8 Ω	$t_{d(on)}$	–	59	–	ns
Rise Time		t_r	–	24	–	
Turn−off Delay Time		$t_{d(off)}$	–	225	–	
Fall Time		t_f	–	80	–	
Turn − on Switching Loss per Pulse		E_{on}	–	757	–	μJ
Turn off Switching Loss per Pulse		E_{off}	–	910	–	
Input Capacitance	V_{CE} = 20 V V_{GE} = 0 V, f = 1 MHz	C_{ies}	–	7753	–	pF
Output Capacitance		C_{oes}	–	227	–	
Reverse Transfer Capacitance		C_{res}	–	127	–	
Total Gate Charge	V_{CE} = 350 V, I_C = 40 A, V_{GE} = ±15 V	Q_g	–	536	–	nC
Thermal Resistance − chip−to−heatsink	Thermal grease, Thickness ≤ 2.25 Mil, λ = 2.9 W/mK	R_{thJH}	–	1.01	–	°C/W
DIODE CHARACTERISTICS (D1, D4, D5, D8, D9, D12)						
Diode Forward Voltage	I_F = 20 A, T_J = 25°C	V_F	–	2.4	2.7	V
	I_F = 20 A, T_J = 150°C		–	1.7	–	
Reverse Recovery Time	T_J = 25°C V_{CE} = 350 V, I_C = 28 A, V_{GE} = ±15 V, R_G = 16 Ω	t_{rr}	–	43	–	ns
Reverse Recovery Charge		Q_{rr}	–	756	–	μC
Peak Reverse Recovery Current		I_{RRM}	–	35	–	A
Peak Rate of Fall of Recovery Current		di/dt	–	750	–	A/μs
Reverse Recovery Energy		E_{rr}	–	104	–	μJ
Reverse Recovery Time	T_J = 125°C V_{CE} = 350 V, I_C = 28 A, V_{GE} = ±15 V, R_G = 16 Ω	t_{rr}	–	129	–	ns
Reverse Recovery Charge		Q_{rr}	–	2702	–	μC
Peak Reverse Recovery Current		I_{RRM}	–	45	–	A
Peak Rate of Fall of Recovery Current		di/dt	–	407	–	A/μs
Reverse Recovery Energy		E_{rr}	–	428	–	μJ
Thermal Resistance − chip−to−heatsink	Thermal grease, Thickness ≤ 2.25 Mil, λ = 2.9 W/mK	R_{thJH}	–	1.63	–	°C/W

ELECTRICAL CHARACTERISTICS (T_J = 25°C Unless Otherwise Noted) (continued)

Parameter	Test Conditions	Symbol	Min.	Typ.	Max.	Unit
IGBT CHARACTERISTICS (Q2, Q3, Q6, Q7, Q10, Q11)						
Collector−Emitter Cutoff Current	V_{GE} = 0 V, V_{CE} = 650 V	I_{CES}	–	–	250	μA
Collector−Emitter Saturation Voltage	V_{GE} = 15 V, I_C = 50 A, T_J = 25°C	$V_{CE(sat)}$	–	1.50	–	V
	V_{GE} = 15 V, I_C = 50 A , T_J = 150°C		–	1.53	–	
Gate−Emitter Threshold Voltage	V_{GE} = V_{CE}, I_C = 1.65 mA	$V_{GE(TH)}$	2.60	4.40	6.40	V
Gate Leakage Current	V_{GE} = 20 V, V_{CE} = 0 V	I_{GES}	–	–	400	nA
Turn−on Delay Time	T_J = 25°C V_{CE} = 350 V, I_C = 28 A, V_{GE} = ±15 V, R_G = 16 Ω	$t_{d(on)}$	–	54	–	ns
Rise Time		t_r	–	15	–	
Turn−off Delay Time		$t_{d(off)}$	–	157	–	
Fall Time		t_f	–	12	–	
Turn−on Switching Loss per Pulse		E_{on}	–	416	–	μJ
Turn off Switching Loss per Pulse		E_{off}	–	321	–	
Turn−on Delay Time	T_J = 125°C V_{CE} = 350 V, I_C = 28 A, V_{GE} = ±15 V, R_G = 16 Ω	$t_{d(on)}$	–	52	–	ns
Rise Time		t_r	–	16	–	
Turn−off Delay Time		$t_{d(off)}$	–	178	–	
Fall Time		t_f	–	18	–	
Turn − on Switching Loss per Pulse		E_{on}	–	671	–	μJ
Turn off Switching Loss per Pulse		E_{off}	–	444	–	
Input Capacitance	V_{CE} = 20 V V_{GE} = 0 V, f = 1 MHz	C_{ies}	–	3137	–	pF
Output Capacitance		C_{oes}	–	146	–	
Reverse Transfer Capacitance		C_{res}	–	17	–	
Total Gate Charge	V_{CE} = 350 V, I_C = 40 A, V_{GE} = ±15 V	Q_g	–	180	–	nC
Thermal Resistance − chip−to−heatsink	Thermal grease, Thickness ≤ 2.25 Mil, λ = 2.9 W/mK	R_{thJH}	–	0.995	–	°C/W
DIODE CHARACTERISTICS (D2, D3, D6, D7, D10, D11)						
Diode Forward Voltage	I_F = 20 A, T_J = 25°C	V_F	–	1.28	–	V
	I_F = 20 A, T_J = 150°C		–	1.18	–	
Combined IGBT + Diode Voltage Drop	I_F = 20 A, T_J = 25°C	V_F	–	3.05	3.4	V
Reverse Recovery Time	T_J = 25°C V_{CE} = 350 V, I_C = 28 A, V_{GE} = ±15 V, R_G = 8 Ω	t_{rr}	–	69	–	ns
Reverse Recovery Charge		Q_{rr}	–	1267	–	μC
Peak Reverse Recovery Current		I_{RRM}	–	41	–	A
Peak Rate of Fall of Recovery Current		di/dt	–	1599	–	A/μs
Reverse Recovery Energy		E_{rr}	–	244	–	μJ
Reverse Recovery Time	T_J = 125°C V_{CE} = 350 V, I_C = 28 A, V_{GE} = ±15 V, R_G = 8 Ω	t_{rr}	–	111	–	ns
Reverse Recovery Charge		Q_{rr}	–	2323	–	μC
Peak Reverse Recovery Current		I_{RRM}	–	40	–	A
Peak Rate of Fall of Recovery Current		di/dt	–	470	–	A/μs
Reverse Recovery Energy		E_{rr}	–	510	–	μJ

ELECTRICAL CHARACTERISTICS (T_J = 25°C Unless Otherwise Noted) (continued)

Parameter	Test Conditions	Symbol	Min.	Typ.	Max.	Unit
THERMISTOR CHARACTERISTICS						
Nominal resistance	T = 25°C	R_{25}		22		kΩ
Nominal resistance	T = 100°C	R_{100}		1468		Ω
Deviation of R25		R/R	−5		5	%
Power dissipation		P_D		200		mW
Power dissipation constant				2		mW/K
B−value	B(25/50), tolerance ±3%			3950		K
B−value	B(25/100), tolerance ±3%			3998		K

Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

ORDERING INFORMATION

Orderable Part Number	Marking	Package	Shipping
NXH40T120L3Q1PG	NXH40T120L3Q1PG	Q1 3−Phase TNPC − Case 180AS Press−fit Pins (Pb−Free)	21 Units / Blister Tray
NXH40T120L3Q1SG	NXH40T120L3Q1SG	Q1 3−Phase TNPC − Case 180BN Solder Pins (Pb−Free)	21 Units / Blister Tray
NXH40T120L3Q1PTG	NXH40T120L3Q1PTG	Q1 3−Phase TNPC − Case 180AS Press−fit Pins (Pb−Free)	21 Units / Blister Tray

TYPICAL CHARACTERISTICS – HALF BRIDGE IGBT (Q1, Q4, Q5, Q8, Q9, Q12) AND DIODE (D1, D4, D5, D8, D9, D12)



Figure 2. Typical Output Characteristics



Figure 3. Typical Output Characteristics



Figure 4. Typical Transfer Characteristics



Figure 5. Diode Forward Characteristics

TYPICAL CHARACTERISTICS – HALF BRIDGE IGBT (Q1, Q4, Q5, Q8, Q9, Q12) AND DIODE (D1, D4, D5, D8, D9, D12)



Figure 6. Transient Thermal Impedance (Half Bridge IGBT)



Figure 7. Transient Thermal Impedance (Half Bridge Diode)

TYPICAL CHARACTERISTICS – HALF BRIDGE IGBT (Q1, Q4, Q5, Q8, Q9, Q12) AND DIODE (D1, D4, D5, D8, D9, D12)



Figure 8. FBSOA



Figure 9. RBSOA



Figure 10. Gate Voltage vs. Gate Charge

TYPICAL CHARACTERISTICS – NP IGBT + DIODE
(Q2+D2, Q3+D3, Q6+D6, Q7+D7, Q10+D10, Q11+D11)



Figure 11. Typical Output Characteristics (I_C versus V_{DT})



Figure 12. Typical Output Characteristics (I_C versus V_{DT})



Figure 13. Typical Transfer Characteristics

TYPICAL CHARACTERISTICS – NP IGBT + DIODE
(Q2+D2, Q3+D3, Q6+D6, Q7+D7, Q10+D10, Q11+D11)



Figure 14. Transient Thermal Impedance (Neutral Point IGBT + Diode)



Figure 15. FBSOA (NP IGBT + Diode)



Figure 16. RBSOA (NP IGBT + Diode)



Figure 17. Gate Voltage vs. Gate Charge

TYPICAL CHARACTERISTICS – HALF BRIDGE IGBT COMMUTATES NEUTRAL POINT DIODE



Figure 18. Typical Switching Loss E_{ON} vs. I_C



Figure 19. Typical Switching Loss E_{OFF} vs. I_C



Figure 20. Typical Switching Loss E_{ON} vs. R_G



Figure 21. Typical Switching Loss E_{OFF} vs. R_G



Figure 22. Typical Switching Time T_{DOFF} vs. I_C



Figure 23. Typical Switching Time T_{DON} vs. I_C

TYPICAL CHARACTERISTICS – HALF BRIDGE IGBT COMMUTATES NEUTRAL POINT DIODE



Figure 24. Typical Switching Time T_{DOFF} vs. R_G



Figure 25. Typical Switching Time T_{DON} vs. R_G



Figure 26. Typical Reverse Recovery Energy Loss vs. I_C



Figure 27. Typical Reverse Recovery Energy Loss vs. R_G



Figure 28. Typical Reverse Recovery Time vs. R_G



Figure 29. Typical Reverse Recovery Charge vs. R_G

TYPICAL CHARACTERISTICS – HALF BRIDGE IGBT COMMUTATES NEUTRAL POINT DIODE



Figure 30. Typical Reverse Recovery Peak Current vs. R_G



Figure 31. Typical di/dt vs. R_G



Figure 32. Typical Reverse Recovery Time vs. I_C



Figure 33. Typical Reverse Recovery Charge vs. I_C



Figure 34. Typical Reverse Recovery Current vs. I_C



Figure 35. Typical di/dt Current Slope vs. I_C

TYPICAL CHARACTERISTICS – NEUTRAL POINT IGBT COMMUTATES HALF BRIDGE DIODE



Figure 36. Typical Turn ON Loss vs. I_C



Figure 37. Typical Turn OFF Loss vs. I_C



Figure 38. Typical Turn ON Loss vs. R_G



Figure 39. Typical Turn OFF Loss vs. R_G



Figure 40. Typical Turn−Off Switching Time vs. I_C



Figure 41. Typical Turn−On Switching Time vs. I_C

TYPICAL CHARACTERISTICS – NEUTRAL POINT IGBT COMMUTATES HALF BRIDGE DIODE



Figure 42. Typical Turn−Off Switching Time vs. R_G



Figure 43. Typical Turn−On Switching Time vs. R_G



Figure 44. Typical Reverse Recovery Energy Loss vs. I_C



Figure 45. Typical Reverse Recovery Energy Loss vs. R_G



Figure 46. Typical Reverse Recovery Time vs. R_G



Figure 47. Typical Reverse Recovery Charge vs. R_G

TYPICAL CHARACTERISTICS – NEUTRAL POINT IGBT COMMUTATES HALF BRIDGE DIODE



Figure 48. Typical Reverse Recovery Peak Current vs. R_G



Figure 49. Typical di/dt vs. R_G



Figure 50. Typical Reverse Recovery Time vs. I_C



Figure 51. Typical Reverse Recovery Charge vs. I_C



Figure 52. Typical Reverse Recovery Current vs. I_C



Figure 53. Typical di/dt Current Slope vs. I_C

PIM44, 71x37.4 (PRESSFIT PINS)
CASE 180AS
ISSUE O

DATE 25 JUN 2018



TOP VIEW



END VIEW



SIDE VIEW



DETAIL A



RECOMMENDED
MOUNTING PATTERN

	PIN POSITION			PIN POSITION	
PIN	X	Y	PIN	X	Y
1	26.10	14.10	23	-4.85	3.40
2	20.10	14.10	24	-4.85	0.40
3	20.90	11.10	25	4.30	4.40
4	14.80	14.10	26	7.30	4.40
5	17.90	11.10	27	14.05	2.90
6	8.80	14.10	28	14.05	5.90
7	8.80	11.10	29	24.35	3.40
8	2.80	14.10	30	24.35	0.40
9	-0.20	12.10	31	-26.10	-2.25
10	-3.20	14.10	32	-26.10	-5.25
11	-3.20	11.10	33	-20.65	-14.10
12	-9.20	14.10	34	-17.85	-14.10
13	-9.20	11.10	35	-14.85	-14.10
14	-15.20	14.10	36	-11.85	-14.10
15	-15.20	11.10	37	-3.10	-14.10
16	-20.10	14.10	38	-0.10	-14.10
17	-18.20	11.10	39	2.90	-14.10
18	-26.10	14.10	40	5.70	-14.10
19	-21.35	5.20	41	14.30	-14.10
20	-24.35	6.20	42	17.10	-14.10
21	-12.85	0.40	43	20.10	-14.10
22	-12.85	3.40	44	23.10	-14.10

	MILLIMETERS		
DIM	MIN.	NOM.	MAX.
A	11.50	12.00	12.50
A3	15.50	16.00	16.50
A4	12.83 BSC		
A5	0.10	0.20	0.30
b	1.61	1.66	1.71
b1	0.75	0.80	0.85
D	70.50	71.00	71.50
D1	82.00	82.50	83.00
D2	81.50	82.00	82.50
E	36.90	37.40	37.90
E2	30.30	30.80	31.30
P	4.10	4.30	4.50
P1	9.30	9.50	9.70
P2	1.80	2.00	2.20

NOTE 4

	PIN POSITION			PIN POSITION	
PIN	X	Y	PIN	X	Y
1	26.10	-14.10	23	-4.85	-3.40
2	20.10	-14.10	24	-4.85	-0.40
3	20.90	-11.10	25	4.30	-4.40
4	14.80	-14.10	26	7.30	-4.40
5	17.90	-11.10	27	14.05	-2.90
6	8.80	-14.10	28	14.05	-5.90
7	8.80	-11.10	29	24.35	-3.40
8	2.80	-14.10	30	24.35	-0.40
9	-0.20	-12.10	31	-26.10	2.25
10	-3.20	-14.10	32	-26.10	5.25
11	-3.20	-11.10	33	-20.65	14.10
12	-9.20	-14.10	34	-17.85	14.10
13	-9.20	-11.10	35	-14.85	14.10
14	-15.20	-14.10	36	-11.85	14.10
15	-15.20	-11.10	37	-3.10	14.10
16	-20.10	-14.10	38	-0.10	14.10
17	-18.20	-11.10	39	2.90	14.10
18	-26.10	-14.10	40	5.70	14.10
19	-21.35	-5.20	41	14.30	14.10
20	-24.35	-6.20	42	17.10	14.10
21	-12.85	-0.40	43	20.10	14.10
22	-12.85	-3.40	44	23.10	14.10

NOTES:
1. DIMENSIONING AND TOLERANCING PER ASME Y14.5M, 2009.
2. CONTROLLING DIMENSION: MILLIMETERS
3. DIMENSIONS b AND b1 APPLY TO THE PLATED TERMINALS AND ARE MEASURED AT DIMENSION A4.
4. POSITION OF THE CENTER OF THE TERMINALS IS DETERMINED FROM DATUM B THE CENTER OF DIMENSION D, X DIRECTION, AND FROM DATUM A, Y DIRECTION. POSITIONAL TOLERANCE, AS NOTED IN DRAWING, APPLIES TO EACH TERMINAL IN BOTH DIRECTIONS.
5. PACKAGE MARKING IS LOCATED AS SHOWN ON THE SIDE OPPOSITE THE PACKAGE ORIENTATION FEATURES.

onsemi and onsemi are trademarks of Semiconductor Components Industries, LLC dba **onsemi** or its subsidiaries in the United States and/or other countries. **onsemi** reserves the right to make changes without further notice to any products herein. **onsemi** makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. **onsemi** does not convey any license under its patent rights nor the rights of others.

© Semiconductor Components Industries, LLC, 2018



PIM44, 71x37.4
CASE 180AS
ISSUE O

DATE 15 JUN 2018

GENERIC
MARKING DIAGRAM*



XXXXX = Specific Device Code
G = Pb−Free Package
AT = Assembly & Test Site Code
YYWW = Year and Work Week Code

*This information is generic. Please refer to device data sheet for actual part marking. Pb−Free indicator, “G” or microdot “▪”, may or may not be present. Some products may not follow the Generic Marking.

DOCUMENT NUMBER:	**98AON92314G**	Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped “CONTROLLED COPY” in red.	
DESCRIPTION:	**PIM44, 71x37.4**		**PAGE 2 OF 2**

onsemi and onsemi are trademarks of Semiconductor Components Industries, LLC dba **onsemi** or its subsidiaries in the United States and/or other countries. **onsemi** reserves the right to make changes without further notice to any products herein. **onsemi** makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. **onsemi** does not convey any license under its patent rights nor the rights of others.

© Semiconductor Components Industries, LLC, 2018

PIM44, 71x37.4 (SOLDER PINS)
CASE 180BN
ISSUE O

DATE 08 OCT 2019





TOP VIEW



END VIEW

DIM	MILLIMETERS		
	MIN.	NOM.	MAX.
A	11.50	12.00	12.50
A2	10.90	11.40	11.90
A3	15.90	16.40	16.90
A5	0.00	0.30	0.60
b	0.90	1.00	1.10
D	70.50	71.00	71.50
D1	82.00	82.50	83.00
D2	81.50	82.00	82.50
E	36.90	37.40	37.90
E2	30.30	30.80	31.30
P	4.30	4.40	4.50
P1	4.55	4.75	4.95
P2	2.00 REF		



SIDE VIEW



DETAIL A

NOTE 4

PIN	PIN POSITION		PIN	PIN POSITION	
	X	Y		X	Y
1	26.10	-14.10	23	-4.85	-3.40
2	20.10	-14.10	24	-4.85	-0.40
3	20.90	-11.10	25	4.30	-4.40
4	14.80	-14.10	26	7.30	-4.40
5	17.90	-11.10	27	14.05	-2.90
6	8.80	-14.10	28	14.05	-5.90
7	8.80	-11.10	29	24.35	-3.40
8	2.80	-14.10	30	24.35	-0.40
9	-0.20	-12.10	31	-26.10	2.25
10	-3.20	-14.10	32	-26.10	5.25
11	-3.20	-11.10	33	-20.65	14.10
12	-9.20	-14.10	34	-17.85	14.10
13	-9.20	-11.10	35	-14.85	14.10
14	-15.20	-14.10	36	-11.85	14.10
15	-15.20	-11.10	37	-3.10	14.10
16	-20.10	-14.10	38	-0.10	14.10
17	-18.20	-11.10	39	2.90	14.10
18	-26.10	-14.10	40	5.70	14.10
19	-21.35	-5.20	41	14.30	14.10
20	-24.35	-6.20	42	17.10	14.10
21	-12.85	-0.40	43	20.10	14.10
22	-12.85	-3.40	44	23.10	14.10



RECOMMENDED
MOUNTING PATTERN*

*FOR ADDITIONAL INFORMATION ON OUR Pb-FREE STRATEGY AND SOLDERING DETAILS, PLEASE DOWNLOAD THE ON SEMICONDUCTOR SOLDERING AND MOUNTING TECHNIQUES REFERENCE MANUAL, SOLDERRM/D.

GENERIC MARKING DIAGRAM*



XXXXX = Specific Device Code
G = Pb−Free Package
AT = Assembly & Test Site Code
YYWW = Year and Work Week Code

*This information is generic. Please refer to device data sheet for actual part marking. Pb−Free indicator, “G” or microdot “ ▪”, may or may not be present. Some products may not follow the Generic Marking.

NOTES:
1. DIMENSIONING AND TOLERANCING PERASME Y14.5M, 2009.
2. CONTROLLING DIMENSION: MILLIMETERS
3. DIMENSIONS b APPLIES TO THE PLATED TERMINALS AND IS MEASURED BETWEEN 1.00 AND 3.00 FROM THE TERMINAL TIP.
4. POSITION OF THE CENTER OF THE TERMINALS AND MOUNTING HOLES IS DETERMINED FROM DATUM B THE CENTER OF DIMENSION D, X DIRECTION, AND FROM DATUM A, Y DIRECTION. POSITIONAL TOLERANCE, AS NOTED IN THE DRAWING, APPLIES TO EACH TERMINAL IN BOTH DIRECTIONS.
5. PACKAGE MARKING IS LOCATED AS SHOWN ON THE SIDE OPPOSITE THE PACKAGE ORIENTATION FEATURES.

DOCUMENT NUMBER:	**98AON12615H**	Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped “CONTROLLED COPY” in red.	
DESCRIPTION:	**PIM44, 71x37.4 (SOLDER PINS)**		**PAGE 1 OF 1**

onsemi and onsemi are trademarks of Semiconductor Components Industries, LLC dba **onsemi** or its subsidiaries in the United States and/or other countries. **onsemi** reserves the right to make changes without further notice to any products herein. **onsemi** makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. **onsemi** does not convey any license under its patent rights nor the rights of others.

onsemi, , and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "**onsemi**" or its affiliates and/or subsidiaries in the United States and/or other countries. **onsemi** owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of **onsemi**'s product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent−Marking.pdf. **onsemi** reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as−is" and **onsemi** makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using **onsemi** products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by **onsemi**. "Typical" parameters which may be provided in **onsemi** data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. **onsemi** does not convey any license under any of its intellectual property rights nor the rights of others. **onsemi** products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use **onsemi** products for any such unintended or unauthorized application, Buyer shall indemnify and hold **onsemi** and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that **onsemi** was negligent regarding the design or manufacture of the part. **onsemi** is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

ADDITIONAL INFORMATION

TECHNICAL PUBLICATIONS:
Technical Library: www.onsemi.com/design/resources/technical−documentation
onsemi Website: www.onsemi.com

ONLINE SUPPORT: www.onsemi.com/support
For additional information, please contact your local Sales Representative at www.onsemi.com/support/sales

ENTEGRECİ

Bu belge www.entegreci.com üzerinden sunulmaktadır.

Elektronik komponent tedarikinde Entegreci

Entegreci, Eskişehir merkezli, Türkiye geneline satış yapan bir elektronik komponent mağazasıdır. Entegreler (IC), mikrodenetleyiciler, transistörler, diyotlar, pasif elemanlar, konnektörler, modüller ve geliştirme kartları tek adetten seri üretim adetlerine kadar satılır. Ürün sayfalarında güncel stok durumunu, fiyatı ve datasheet bağlantısını bulabilirsiniz.

Parça koduyla arama

Üretici parça numarasını yazın; stok ve fiyatı hemen görün.

www.entegreci.com

Ürün kategorileri

Entegreden kapasitöre tüm elektronik komponent kategorileri.

Kategorilere göz atın

Üreticiler

Aradığınız üreticinin ürünlerini tek sayfada inceleyin.

Üreticileri görün

Toplu alım ve teklif

Listede olmayan ya da yüksek adetli parçalar için teklif isteyin.

Teklif isteyin

www.entegreci.com | **destek@entegreci.com** | **0850 305 90 34**

Entegreci is an online electronic components store based in Türkiye. Search by manufacturer part number to see stock, prices and datasheets for integrated circuits, microcontrollers, transistors, passive components and connectors, or request a quote for parts that are not listed.

Bu sayfa Entegreci tarafından eklenmiştir. Belgenin önceki sayfaları asıl yayıncısına aittir ve içeriği değiştirilmemiştir; en güncel sürüm için belgenin yayıncısına başvurun.