Silicon Carbide (SiC) Module – EliteSiC, 80 mohm SiC M1 MOSFET, 1200 V + 20 A, 1200 V SiC Diode, Two Channel Full SiC Boost, Q0 Package

Product Preview

NXH80B120MNQ0SNG



Q0BOOST
CASE 180AJ
SOLDER PINS

The NXH80B120MNQ0SNG is a power module containing a dual boost stage. The integrated SiC MOSFETs and SiC Diodes provide lower conduction losses and switching losses, enabling designers to achieve high efficiency and superior reliability.

Features

- 1200 V 80 mΩ SiC MOSFETs
- Low Reverse Recovery and Fast Switching SiC Diodes
- 1600 V Bypass and Anti−parallel Diodes
- Low Inductive Layout
- Solderable Pins
- Thermistor
- These Devices are Pb−Free, Halogen Free/BFR Free and are RoHS Compliant

Typical Applications

- Solar Inverters
- Uninterruptable Power Supplies



Figure 1. NXH80B120MNQ0SNG Schematic Diagram

This document contains information on a product under development. **onsemi** reserves the right to change or discontinue this product without notice.

MARKING DIAGRAM



G = Pb−Free Package
AT = Assembly & Test Site Code
YYWW = Year and Work Week Code

PIN CONNECTIONS



ORDERING INFORMATION

See detailed ordering and shipping information on page 4 of this data sheet.

© Semiconductor Components Industries, LLC, 2019

ABSOLUTE MAXIMUM RATINGS (Note 1) T_J = 25°C unless otherwise noted

Rating	Symbol	Value	Unit
BOOST MOSFET			
Drain−Source Voltage	V_{DS}	1200	V
Gate−Source Voltage	V_{GS}	−15/+25	V
Continuous Drain Current (@ V_{GS} = 20 V, T_C = 80°C)	I_D	23	A
Pulsed Drain Current @ T_C = 80°C (T_J = 175°C)	$I_{D(Pulse)}$	69	A
Maximum Power Dissipation @ T_C = 80°C	P_{tot}	69	W
Minimum Operating Junction Temperature	T_{JMIN}	−40	°C
Maximum Operating Junction Temperature	T_{JMAX}	175	°C
BOOST DIODE			
Peak Repetitive Reverse Voltage	V_{RRM}	1200	V
Continuous Forward Current @ T_C = 80°C	I_F	31	A
Surge Forward Current (60 Hz single half−sine wave)	I_{FSM}	93	A
Maximum Power Dissipation @ T_C = 80°C (T_J = 175°C)	P_{tot}	97	W
I^2t − value (60 Hz single half−sine wave)	I^2t	19	A^2s
Minimum Operating Junction Temperature	T_{JMIN}	−40	°C
Maximum Operating Junction Temperature	T_{JMAX}	175	°C
BYPASS DIODE			
Peak Repetitive Reverse Voltage	V_{RRM}	1600	V
Continuous Forward Current @ T_C = 80°C (T_J = 150°C)	I_F	44	A
Repetitive Peak Forward Current (T_C = 80°C, t_p limited by T_{Jmax})	I_{FRM}	132	A
Power Dissipation Per Diode @ T_C = 80°C (T_J = 150°C)	P_{tot}	63	W
Minimum Operating Junction Temperature	T_{JMIN}	−40	°C
Maximum Operating Junction Temperature	T_{JMAX}	150	°C
THERMAL PROPERTIES			
Storage Temperature range	T_{stg}	−40 to 125	°C
INSULATION PROPERTIES			
Isolation test voltage, t = 1 sec, 60 Hz	V_{is}	3000	V_{RMS}
Creepage distance		12.7	mm

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

1. Refer to ELECTRICAL CHARACTERISTICS, RECOMMENDED OPERATING RANGES and/or APPLICATION INFORMATION for Safe Operating parameters.

RECOMMENDED OPERATING RANGES

Parameter	Symbol	Min	Max	Unit
Module Operating Junction Temperature	T_J	−40	(T_{JMAX} − 25)	°C

Functional operation above the stresses listed in the Recommended Operating Ranges is not implied. Extended exposure to stresses beyond the Recommended Operating Ranges limits may affect device reliability.

ELECTRICAL CHARACTERISTICS (T_J = 25°C unless otherwise specified)

Characteristic	Test Conditions	Symbol	Min	Typ	Max	Unit
BOOST MOSFET CHARACTERISTICS						
Zero Gate Voltage Drain Current	V_{GS} = 0 V, V_{DS} = 1200 V, T_J = 25°C	I_{DSS}	–	–	100	μA
Static Drain−to−Source On Resistance	V_{GS} = 20 V, I_D = 20 A, T_J = 25°C	$R_{DS(on)}$	–	80	110	mΩ
	V_{GS} = 20 V, I_D = 20 A, T_J = 150°C		–	114	162	
Gate−Source Threshold Voltage	V_{GS} = V_{DS}, I_D = 5 mA	$V_{GS(th)}$	1.8	2.0	4.3	V
Gate−Source Leakage Current	V_{GS} = 25 V, V_{DS} = 0 V	I_{GSS}	–	–	1	μA
Turn−on Delay Time	T_J = 25°C V_{DS} = 700 V, V_{GS} = 20 V, −5 V I_D = 30 A, R_G = 4.7 Ω	$t_{d(on)}$	–	13.4	–	ns
Rise Time		t_r	–	3.6	–	
Turn−off Delay Time		$t_{d(off)}$	–	27.6	–	
Fall Time		t_f	–	10.3	–	
Turn−on Switching Loss per Pulse		E_{on}	–	166	–	μJ
Turn−off Switching Loss per Pulse		E_{off}	–	49.2	–	
Turn−on Delay Time	T_J = 125°C V_{DS} = 700 V, V_{GS} = 20 V, −5 V I_D = 30 A, R_G = 4.7 Ω	$t_{d(on)}$	–	13.7	–	ns
Rise Time		t_r	–	3.5	–	
Turn−off Delay Time		$t_{d(off)}$	–	29.56	–	
Fall Time		t_f	–	10.36	–	
Turn−on Switching Loss per Pulse		E_{on}	–	154	–	μJ
Turn−off Switching Loss per Pulse		E_{off}	–	46.65	–	
Input Capacitance	V_{DS} = 800 V, V_{GS} = 0 V, f = 1 MHz	C_{iss}	–	1038.7	–	pF
Output Capacitance		C_{oss}	–	95.5	–	
Reverse Transfer Capacitance		C_{rss}	–	10.9	–	
Total Gate Charge	V_{DS} = 600 V, I_D = 20 A, V_{GS} = 20 V, −5 V	Q_g	–	74.72	–	nC
Thermal Resistance − chip−to−case	Thermal grease, Thickness = 2.1 Mil ±2% λ = 2.9 W/mK	R_{thJC}	–	1.37	–	K/W
Thermal Resistance − chip−to−heatsink		R_{thJH}	–	1.94	–	K/W
BOOST DIODE CHARACTERISTICS						
Diode Reverse Leakage Current	V_R = 1200 V	I_R	–	–	300	μA
Diode Forward Voltage	I_F = 20 A, T_J = 25°C	V_F	–	1.49	1.7	V
	I_F = 20 A, T_J = 150°C		–	2.17	–	
Reverse Recovery Time	T_J = 25°C V_{DS} = 700 V, V_{GS} = 20 V, −5 V I_D = 30 A, R_G = 4.7 Ω	t_{rr}	–	12	–	ns
Reverse Recovery Charge		Q_{rr}	–	159	–	nC
Peak Reverse Recovery Current		I_{RRM}	–	21.2	–	A
Peak Rate of Fall of Recovery Current		di/dt	–	7240	–	A/μs
Reverse Recovery Energy		E_{rr}	–	70	–	μJ
Reverse Recovery Time	T_J = 125°C V_{DS} = 700 V, V_{GS} = 20 V, −5 V I_D = 30 A, R_G = 4.7 Ω	t_{rr}	–	11.7	–	ns
Reverse Recovery Charge		Q_{rr}	–	153	–	nC
Peak Reverse Recovery Current		I_{RRM}	–	23.8	–	A
Peak Rate of Fall of Recovery Current		di/dt	–	8068	–	A/μs
Reverse Recovery Energy		E_{rr}	–	66.3	–	μJ

ELECTRICAL CHARACTERISTICS (T_J = 25°C unless otherwise specified) (continued)

Characteristic	Test Conditions	Symbol	Min	Typ	Max	Unit
BOOST DIODE CHARACTERISTICS						
Thermal Resistance – chip–to–case	Thermal grease, Thickness = 2.1 Mil ±2% λ = 2.9 W/mK	R_{thJC}	–	0.98	–	K/W
Thermal Resistance – chip–to–heatsink		R_{thJH}	–	1.33	–	K/W
BYPASS DIODE CHARACTERISTICS						
Diode Reverse Leakage Current	V_R = 1600 V, T_J = 25°C	I_R	–	–	100	μA
Diode Forward Voltage	I_F = 30 A, T_J = 25°C	V_F	–	1.04	1.4	V
	I_F = 30 A, T_J = 150°C		–	0.94	–	
Thermal Resistance – chip–to–case	Thermal grease, Thickness = 2.1 Mil ±2% λ = 2.9 W/mK	R_{thJC}	–	1.12	–	K/W
Thermal Resistance – chip–to–heatsink		R_{thJH}	–	1.56	–	K/W
THERMISTOR CHARACTERISTICS						
Nominal resistance		R_{25}	–	22	–	kΩ
Nominal resistance	T = 100°C	R_{100}	–	1486	–	Ω
Deviation of R25		ΔR/R	–5	–	5	%
Power dissipation		P_D	–	200	–	mW
Power dissipation constant			–	2	–	mW/K
B–value	B(25/50), tolerance ±3%		–	3950	–	K
B–value	B(25/100), tolerance ±3%		–	3998	–	K

Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

ORDERING INFORMATION

Part Number	Marking	Package	Shipping
NXH80B120MNQ0SNG	NXH80B120MNQ0SNG	Q0BOOST – Case 180AJ (Pb–Free and Halide–Free Solder Pins)	24 Units / Blister Tray

TYPICAL CHARACTERISTICS – MOSFET, BOOST DIODE AND BYPASS DIODE



Figure 2. MOSFET On Region Characteristics



Figure 3. MOSFET On Region Characteristics



Figure 4. MOSFET Transfer Characteristics



Figure 5. Boost Diode Forward Characteristics



Figure 6. Bypass Diode Forward Characteristics

TYPICAL SWITCHING CHARACTERISTICS – MOSFET



Figure 7. Typical Turn On Loss vs. I_D



Figure 8. Typical Turn Off Loss vs. I_D



Figure 9. Typical Turn On Loss vs. R_G



Figure 10. Typical Turn Off Loss vs. R_G



Figure 11. Typical Turn On Switching Time vs. I_D



Figure 12. Typical Turn Off Switching Time vs. I_D

TYPICAL CHARACTERISTICS – MOSFET



Figure 13. Typical Turn On Switching Time vs. R_G



Figure 14. Typical Turn Off Switching Time vs. R_G

TYPICAL CHARACTERISTICS – BOOST DIODE



Figure 15. Typical Reverse Recovery Energy Loss vs. I_D



Figure 16. Typical Reverse Recovery Energy Loss vs. R_G



Figure 17. Typical Reverse Recovery Time vs. I_D



Figure 18. Typical Reverse Recovery Time vs. R_G

TYPICAL SWITCHING CHARACTERISTICS – BOOST DIODE



Figure 19. Typical Reverse Recovery Charge vs. I_D



Figure 20. Typical Reverse Recovery Charge vs. R_G



Figure 21. Typical Reverse Recovery Peak Current vs. I_D



Figure 22. Typical Reverse Recovery Peak Current vs. R_G



Figure 23. Typical di/dt vs. I_D



Figure 24. Typical di/dt vs. R_G

TRANSIENT THERMAL IMPEDANCE – MOSFET, BOOST DIODE AND BYPASS DIODE



Figure 25. MOSFET Transient Thermal Impedance



Figure 26. Boost Diode Transient Thermal Impedance



Figure 27. Bypass Diode Transient Thermal Impedance

GATE CHARGE, CAPACITANCE CHARGE, SOA AND THERMISTOR CHARACTERISTICS



Figure 28. Gate Voltage vs. Gate Charge



Figure 29. Capacitance Charge



Figure 30. FBSOA



Figure 31. RBSOA



Figure 32. Thermistor Characteristics

PIM22, 55x32.5 / Q0BOOST
CASE 180AJ
ISSUE B

DATE 08 NOV 2017





TOP VIEW



END VIEW

NOTES:

1. DIMENSIONING AND TOLERANCING PER. ASME Y14.5M, 2009.
2. CONTROLLING DIMENSION: MILLIMETERS
3. DIMENSION b APPLIES TO THE PLATED TERMINALS AND IS MEASURED BETWEEN 1.00 AND 3.00 FROM THE TERMINAL TIP.
4. POSITION OF THE CENTER OF THE TERMINALS IS DETERMINED FROM DATUM B THE CENTER OF DIMENSION D, X DIRECTION, AND FROM DATUM A, Y DIRECTION. POSITIONAL TOLERANCE, AS NOTED IN DRAWING, APPLIES TO EACH TERMINAL IN BOTH DIRECTIONS.
5. PACKAGE MARKING IS LOCATED AS SHOWN ON THE SIDE OPPOSITE THE PACKAGE ORIENTATION FEATURES.



SIDE VIEW



DETAIL A

DIM	MILLIMETERS	
	MIN.	NOM.
A	13.50	13.90
A1	0.10	0.30
A2	11.50	11.90
A3	15.65	16.05
A4	16.35 REF	
b	0.95	1.05
D	54.80	55.20
D1	65.60	66.20
E	32.20	32.80
P	4.20	4.40
P1	8.90	9.10

MOUNTING HOLE POSITION

NOTE 4

PIN	HOLE POSITION	
	X	Y
1	-16.75	-11.25
2	-13.85	-11.25
3	-8.45	-11.25
4	-5.95	-11.25
5	2.85	-11.25
6	5.35	-11.25
7	12.35	-11.25
8	15.25	-11.25
9	16.75	-6.55
10	16.75	-4.05
11	16.75	4.05

PIN	PIN POSITION	
	X	Y
12	16.75	6.55
13	15.25	11.25
14	12.35	11.25
15	5.35	11.25
16	2.85	11.25
17	-5.95	11.25
18	-8.45	11.25
19	-13.85	11.25
20	-16.75	11.25
21	-16.75	3.25
22	-16.75	-3.25

PIN	PIN POSITION	
	X	Y
1	-16.75	11.25
2	-13.85	11.25
3	-8.45	11.25
4	-5.95	11.25
5	2.85	11.25
6	5.35	11.25
7	12.35	11.25
8	15.25	11.25
9	16.75	6.55
10	16.75	4.05
11	16.75	-4.05

PIN	PIN POSITION	
	X	Y
12	16.75	-6.55
13	15.25	-11.25
14	12.35	-11.25
15	5.35	-11.25
16	2.85	-11.25
17	-5.95	-11.25
18	-8.45	-11.25
19	-13.85	-11.25
20	-16.75	-11.25
21	-16.75	-3.25
22	-16.75	3.25

GENERIC MARKING DIAGRAM*



XXXXX = Specific Device Code
G = Pb−Free Package
AT = Assembly & Test Site Code
YYWW = Year and Work Week Code

*This information is generic. Please refer to device data sheet for actual part marking. Pb−Free indicator, “G” or microdot “ ▪”, may or may not be present. Some products may not follow the Generic Marking.

DOCUMENT NUMBER:	**98AON63481G**	Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped “CONTROLLED COPY” in red.
DESCRIPTION:	**PIM22 55X32.5 / Q0BOOST (SOLDER PIN)**	**PAGE 1 OF 2**

onsemi and onsemi are trademarks of Semiconductor Components Industries, LLC dba **onsemi** or its subsidiaries in the United States and/or other countries. **onsemi** reserves the right to make changes without further notice to any products herein. **onsemi** makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. **onsemi** does not convey any license under its patent rights nor the rights of others.

PIM22, 55x32.5 / Q0BOOST
CASE 180AJ
ISSUE B

DATE 08 NOV 2017



RECOMMENDED
MOUNTING PATTERN



MOUNTING HOLE DETAIL

DOCUMENT NUMBER:	**98AON63481G**	Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red.	
DESCRIPTION:	**PIM22 55X32.5 / Q0BOOST (SOLDER PIN)**		**PAGE 2 OF 2**

onsemi and onsemi are trademarks of Semiconductor Components Industries, LLC dba **onsemi** or its subsidiaries in the United States and/or other countries. **onsemi** reserves the right to make changes without further notice to any products herein. **onsemi** makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. **onsemi** does not convey any license under its patent rights nor the rights of others.

© Semiconductor Components Industries, LLC, 2019

onsemi, , and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "**onsemi**" or its affiliates and/or subsidiaries in the United States and/or other countries. **onsemi** owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of **onsemi**'s product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent−Marking.pdf. **onsemi** reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as−is" and **onsemi** makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using **onsemi** products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by **onsemi**. "Typical" parameters which may be provided in **onsemi** data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. **onsemi** does not convey any license under any of its intellectual property rights nor the rights of others. **onsemi** products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use **onsemi** products for any such unintended or unauthorized application, Buyer shall indemnify and hold **onsemi** and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that **onsemi** was negligent regarding the design or manufacture of the part. **onsemi** is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

ADDITIONAL INFORMATION

TECHNICAL PUBLICATIONS:
Technical Library: www.onsemi.com/design/resources/technical−documentation
onsemi Website: www.onsemi.com

ONLINE SUPPORT: www.onsemi.com/support
For additional information, please contact your local Sales Representative at www.onsemi.com/support/sales

ENTEGRECİ

Bu belge www.entegreci.com üzerinden sunulmaktadır.

Elektronik komponent tedarikinde Entegreci

Entegreci, Eskişehir merkezli, Türkiye geneline satış yapan bir elektronik komponent mağazasıdır. Entegreler (IC), mikrodenetleyiciler, transistörler, diyotlar, pasif elemanlar, konnektörler, modüller ve geliştirme kartları tek adetten seri üretim adetlerine kadar satılır. Ürün sayfalarında güncel stok durumunu, fiyatı ve datasheet bağlantısını bulabilirsiniz.

Parça koduyla arama

Üretici parça numarasını yazın; stok ve fiyatı hemen görün.

www.entegreci.com

Ürün kategorileri

Entegreden kapasitöre tüm elektronik komponent kategorileri.

Kategorilere göz atın

Üreticiler

Aradığınız üreticinin ürünlerini tek sayfada inceleyin.

Üreticileri görün

Toplu alım ve teklif

Listede olmayan ya da yüksek adetli parçalar için teklif isteyin.

Teklif isteyin

www.entegreci.com | **destek@entegreci.com** | **0850 305 90 34**

Entegreci is an online electronic components store based in Türkiye. Search by manufacturer part number to see stock, prices and datasheets for integrated circuits, microcontrollers, transistors, passive components and connectors, or request a quote for parts that are not listed.

Bu sayfa Entegreci tarafından eklenmiştir. Belgenin önceki sayfaları asıl yayıncısına aittir ve içeriği değiştirilmemiştir; en güncel sürüm için belgenin yayıncısına başvurun.